



Kissner Milling Company Limited
148 Manitou Drive, Suite 301
Kitchener, Ontario N2C 1L3
1 (800) 434-8248 • (519) 279-4860
Fax: (877) 434-8250



SAFETY DATA SHEET

Section 1: Product Identification

Product Name Landscaper's Choice® Ice Melter
Identified Uses Melt Snow and Ice
Supplier's Details Kissner Milling Company Limited
148 Manitou Drive, Suite 301
Kitchener, Ontario, Canada N2C 1L3
Phone Number (519) 279-4860
Available Packaging 50lb bag, 50lb box, 40lb pail, 50lb pail, 2000lb sac, 440lb drum
Emergency Contact (24 Hrs) (613) 996-6666 CANUTEC

Section 2: Hazard Identification

Classification (GHS) Not Classified
GHS Labelling No Labelling applicable
Percentage Not applicable
Other Hazards Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. Corrosive to metals upon prolonged contact.

Section 3: Composition/Information On Ingredients

Ingredients	Percentage	CAS. NO.	Classification
Sodium Chloride	85.0-99.9%	7647-14-5	Not Classified
Magnesium Chloride	0.01-5.0%	7786-30-3	Not Classified
Calcium Magnesium Acetate (CMA)	0.01-5.0%	76123-46-1	Acute Tox. 4 (Inhalation:dust,mist), H332; Eye Irrit. 2B, H320
Potassium Chloride	0.01-5.0%	7447-40-7	Aquatic Acute 3, H402
Product may contain color indicator			

Section 4: First-Aid Measures

Description of First Aid Measures

General Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.
Inhalation When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.
Skin Contact Remove contaminated clothing. Brush off loose particles. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation persists. Wash contaminated clothing before reuse.
Eye Contact Rinse cautiously with water for several minutes. Brush off loose particles. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.
Ingestion Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.



Kissner Milling Company Limited

148 Manitou Drive, Suite 301
Kitchener, Ontario N2C 1L3
1 (800) 434-8248 • (519) 279-4860
Fax: (877) 434-8250



Most Important Symptoms and Effects Both Acute and Delayed

General	Dust may cause mechanical irritation to eyes, nose, throat, and lungs
Inhalation	Prolonged contact with large amounts of dust may cause mechanical irritation.
Skin Contact	Skin contact with large amounts of dust may cause mechanical irritation.
Eye Contact	Contact may cause irritation due to mechanical abrasion
Ingestion	Ingestion is not likely to be harmful or have adverse effects
Other	Contact with large amount of dust may cause mechanical irritation to eyes, nose, throat, and lungs.
Chronic Symptoms	Not available

Section 5: Fire-Fighting Measures

Suitable Extinguishing Media:	Use extinguishing media appropriate for surrounding fire.
Unsuitable Extinguishing Media:	Do not use a heavy water stream. Use of heavy stream of water may spread fire.
Fire Hazard:	Not considered flammable but may burn at high temperatures.
Explosion Hazard:	Product is not explosive.
Reactivity:	When heated to decomposition, emits toxic fumes. Toxic Gas.
Hazardous Combustion Products:	Toxic fumes are released. Hydrogen chloride. Sodium oxides. Chlorine.
Other Information:	Do not allow run-off from firefighting to enter drains or water courses.

Section 6: Accidental Release Measures

Personal Precautions	Avoid breathing (dust). Avoid all contact with skin, eyes, or clothing.
Protective Equipment:	Use appropriate personal protection equipment (PPE).
Environmental Precautions	Prevent entry to sewers and public waters. Avoid release to the environment.
Methods for Cleaning Up	Clear up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Contact competent authorities after a spill.

Section 7: Handling And Storage

Precautions for Safe Handling

Additional Hazards When Processed	When heated to decomposition, emits toxic fumes. Contact with water causes an exothermic heat reaction, which may cause significant temperature rise. Corrosive to metals upon prolonged contact. May release hydrogen gas on prolonged contact with certain metals.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities



Kissner Milling Company Limited

148 Manitou Drive, Suite 301
Kitchener, Ontario N2C 1L3
1 (800) 434-8248 • (519) 279-4860
Fax: (877) 434-8250



Technical Measures	Comply with applicable regulations
Storage Conditions	Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from extremely high or low temperatures, direct sunlight, heat, ignition sources, and incompatible materials.
Incompatible Materials	Strong acids. Strong bases. Strong oxidizers.

Section 8: Exposure Controls/Personal Protection

Control Parameters	No Occupational Exposure Limits (OELs) have been established for this product or its chemical components.
Appropriate Engineering Controls	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas
Personal Protective Equipment	Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection. Gloves.



Materials for Protective Clothing:	Chemically resistant materials and fabrics.
Hand Protection:	Wear chemically resistant protective gloves.
Eye Protection:	Chemical goggles or face shield.
Skin and Body Protection:	Wear suitable protective clothing.
Respiratory Protection:	Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations are expected to exceed exposure limits.

Section 9: Physical And Chemical Properties

Appearance/ Physical State	Green coloured granules. Solid
Vapour Pressure (mm Hg at 20°C)	Not applicable
Vapour Density (Air = 1.0)	Not applicable
Bulk Density	Not applicable
Solubility in Water	Water Soluble
Specific Gravity (gm/cc, Water = 1.0)	Not applicable
% Volatile by Volume	Non-volatile
Boiling Range (Deg. Celsius)	Not available
Melting Point	Not available
Coefficient of Water/Oil Distribution	Not applicable
pH	10 (1% solution @ 20°C)

Section 10: Stability And Reactivity

Chemical Stability:	Stable under normal conditions.
----------------------------	---------------------------------



Kissner Milling Company Limited

148 Manitou Drive, Suite 301
Kitchener, Ontario N2C 1L3
1 (800) 434-8248 • (519) 279-4860
Fax: (877) 434-8250



Reactivity: When heated to decomposition, emits toxic fumes. Toxic Gas.
Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.
Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Incompatible materials.
Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Reactive metals.
Hazardous Decomposition Products: Toxic gases. Hydrogen chloride. Chlorine. Sodium oxides. Oxides of magnesium.

Section 11: Toxicological Information

Acute Toxicity: Not classified
LD50 and LC50 Data: Not available
Skin Corrosion/Irritation: Not classified
Serious Eye Damage/Irritation: Not classified
Respiratory or Skin Sensitization: Not classified
Germ Cell Mutagenicity: Not classified
Teratogenicity: Not available
Carcinogenicity: Not classified
Specific Target Organ Toxicity (Repeated Exposure): Not classified
Reproductive Toxicity: Not classified
Specific Target Organ Toxicity (Single Exposure): Not classified
Aspiration Hazard: Not classified

Information on Toxicological Effects - Ingredient(s)

Sodium chloride (7647-14-5)	LD50 Oral Rat	3 g/kg
	LC50 Inhalation Rat	> 42 g/m ³ (Exposure time: 1 h)
Calcium Magnesium Acetate (76123-46-1)	LC50 Inhalation Rat	> 4600 mg/m ³ (Exposure time: 4 h)
Potassium Chloride (7447-40-7)	LD50 Oral Rat	2600 mg/kg

Section 12: Ecological Information

Toxicity No additional information available

Sodium chloride (7647-14-5)

LC50 Fish 1	5560 (5560 - 6080) mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow- through])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	12946 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	340.7 (340.7 - 469.2) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Potassium Chloride (7447-40-7)

LC50 Fish 1	1060 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	825 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	750-1020 mg/l (Exposure time: 96 h - Species: Pimephales Promelas [static])
EC50 Daphnia 2	83 mg/l (Exposure time: 48 h - Species: Daphnia magna [static])

Persistence and degradability Not available

**Kissner Milling Company Limited**

148 Manitou Drive, Suite 301
 Kitchener, Ontario N2C 1L3
 1 (800) 434-8248 • (519) 279-4860
 Fax: (877) 434-8250

**Bio accumulative potential**

Sodium chloride (7647-14-5)	BCF Fish 1	(no bioaccumulation)
-----------------------------	------------	----------------------

Mobility in Soil

Not available

Other Information

Avoid release to the environment

Section 13: Disposal Considerations**Waste Disposal**

Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Recommendations**Section 14: Transport Information**

In Accordance with DOT

Not regulated for transport

In Accordance with IMDG

Not regulated for transport

In Accordance with IATA

Not regulated for transport

In Accordance with TDG

Not regulated for transport

Section 15: Regulatory Information**US Federal Regulations**

Sodium chloride (7647-14-5)	Listed on the United States TSCA (Toxic Substances Control Act) inventory
Potassium Chloride (7447-40-7)	Listed on the United States TSCA (Toxic Substances Control Act) inventory

Canadian Regulations

Landscaper's Choice® Ice Melter	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Sodium chloride (7647-14-5)	Listed on the Canadian DSL (Domestic Substances List)
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Calcium Magnesium Acetate (76123-46-1)	Listed on the Canadian DSL (Domestic Substances List)
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Magnesium Chloride (7786-30-3)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Potassium Chloride (7447-40-7)	Listed on the Canadian DSL (Domestic Substances List)
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.



Kissner Milling Company Limited

148 Manitou Drive, Suite 301
Kitchener, Ontario N2C 1L3
1 (800) 434-8248 • (519) 279-4860
Fax: (877) 434-8250



Section 16: Other Information

Other Information:

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Effective Date:

February 26, 2018

Version

1

Contact

sds@kissner.com

The information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to review this information, satisfy themselves as to its suitability and completeness and pass on the information to its employees or customers. Kissner Group does not accept responsibility for any loss or damage, which may occur from the use of this information.