Samuel Cabot Inc.

100 Hale Street Newburyport, MA 01950 Tel. 800-US-STAIN Fax. (978) 462-2720



33360 Central Avenue Union City, CA 94587 Tel. 888-WC-STAIN Fax. (510) 477-9615

Material Safety Data Sheet

IDENTITY (As Used on Label and List) **1800** Series Solid Color Decking Stains and Tint Bases Section I **Emergency Telephone Number** Call local emergency medical services. Call Chem-Tel 1-800-255-3924. Date Prepared Signature of Preparer (Optional) September 1997 Section II - Hazardous Ingredients/Identity Information Hazardous Components (Specific Chemical Identity; Common Name(s)) CAS # OSHA PEL ACGIH TLV Other Limits Recommended % (Optional) No hazardous ingredients. These products contain a Maximum Volatile Organic Compound (V.O.C.) content of 350 grams per liter (2.9 pounds per gallon). Section III - Physical/Chemical Characteristics **Boiling Point** 212°F Specific Gravity (H2O = 1) 1.1 - 1.3Water Vapor Pressure (mm Hg.) Melting Point 32°F @ 68°F 17mm Hg Vapor Density (AIR = 1) **Evaporation Rate** >1 (Butyl Acetate = 1) < 1 Solubility in Water Dilutable Appearance and Odor Colored liquid - latex emulsion with slight ammonia odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A Non-combustible Flammable Limits No fire hazard LEL --- UEL ---

Extinguishing Media No fire hazard.

Special Fire Fighting Procedures Does not apply.

Unusual Fire and Explosion Hazards

Product will not burn, but closed containers may burst; and stain may boil and spatter when exposed to extreme heat. The dried paint film is capable of burning.

Section V - Reactivity Data

Stability Unstable Conditions to Avoid Non-hazardous

Stable X

Incompatibility (*Materials to Avoi*d)

Does not apply.

Hazardous Decomposition or Byproducts

Does not apply.

Hazardous Polymerization May Occur Conditions to Avoid Does not apply.

Will Not Occur X

Section VI - Health Hazard Data

Routes of Entry Inhalation? Yes Skin? Yes Ingestion? Yes

Health Hazards (*Acute and Chronic*) May be irritating to eyes, skin, nose, throat. Inhalation may cause headaches and nausea. Ingestion may cause irritation and vomiting.

Carcinogenicity: NTP? NO IARC Monographs? NO OSHA Regulated? NO

Signs and Symptoms of Exposure Irritation to eyes, skin, respiratory tract. Possible headaches and nausea.

Medical Conditions Generally

Aggravated by Exposure Persons with breathing difficulties, skin sensitivities, eye sensitivities.

Emergency and First Aid Procedures

EYES: Flush with water for 15 minutes. Call physician. **SKIN:** Wash affected areas with soap and water. Remove contaminated clothing. **INHALATION:** Remove to fresh air. Restore normal breathing. **INGESTION:** Do not induce vomiting. Drink plenty of milk or water. Call physician immediately.

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Dike and contain spill with inert material (i.e. sand, earth). Add absorbent material and remove to closed containers for disposal. Wear protective clothing. Ventilate area.

Waste Disposal Method

Dispose of in accordance with local, state, and federal regulations. Incineration is impractical because of water content.

Precautions to be Taken in Handling and Storing

Do not store near excessive heat or food products. Keep containers closed when not in use. Keep from freezing. Keep away from children and animals.

Section VIII - Control Measures

Respiratory Protection (Specify Type) Use approved vapor/mist respirator in areas of poor ventilation.

Ventilation Local Exhaust In areas of poor ventilation Special None known Other None known

Mechanical (General) Local exhaust.

Protective Gloves Neoprene or rubber gloves if necessary. Eye Protection Splash proof safety goggles or glasses.

Other Protective Clothing or Equipment Wear a vapor/mist respirator during spray applications.

Work/Hygienic Practices Read label on can before using. Do not reuse empty containers. **Not intended for interior surfaces.**

For exterior use only.