

# SAFETY DATA SHEET

Revision Date 27-Sep-2018

Version 4

	1. IDENTIFICATION	
<u>Product identifier</u> Product Name	Rain-X Original Glass Treatment	
Other means of identification Product Code Document	11890 SKU: 800002242, 800002243, 800002245, 8	300002250
Recommended use of the chemica	al and restrictions on use	
Recommended Use	Glass Treatment Consumer Use	
Uses advised against	No information available	
Details of the supplier of the safet	<u>y data sheet</u>	
<u>Supplier Address</u> ITW Global Brands 16200 Park Row, Suite 120 Houston, TX 77084 <u>Distributor</u>	<u>Manufacturer Address</u>	<u>Manufactured and Distributed by:</u> May Also Be Distributed by:
Company Phone Number 24-hour emergency phone numbe (CHEMTREC) 1-800-424-9300 or 1- (RMPDC) 1-877-504-9352 (U.S.)		
E mail address, SDS @itugh com		

E-mail address: SDS@itwgb.com

# 2. HAZARDS IDENTIFICATION

## **Classification**

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

## Label elements

Signal word Warning Causes serious eye irritation May cause drowsiness or dizziness Highly flammable liquid and vapor Appearance Clear Colorless

Physical state Liquid

Odor Alcohol

## Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

## **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed Store locked up

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Not applicable

## Other Information

- Not applicable

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

## Substance(s)

Chemical Name	CAS No	Weight-%
ETHANOL	64-17-5	30 - 60
ACETONE	67-64-1	10 - 30
Isopropanol	67-63-0	10 - 30

## 4. FIRST AID MEASURES

#### Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

#### Most important symptoms and effects, both acute and delayed

#### Symptoms

See section 2 for more information.

#### Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

# **5. FIRE-FIGHTING MEASURES**

#### Suitable extinguishing media

Dry chemical, CO2, sand, earth, water spray or regular foam

#### Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient Do not use a solid water stream as it may scatter and spread fire

#### Specific hazards arising from the chemical

Flammable vapors may be present even at temperatures below the flash point.

## Explosion data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge

No information available. May be ignited by heat, sparks or flames.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and inhalation of vapors. Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).		
Environmental precautions			
Environmental precautions	See section 12 for additional ecological information.		
Methods and material for containm	ent and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods for cleaning up	Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.		
Conditions for safe storage, including any incompatibilities			
Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep out of the reach of children.		

Incompatible materials

None known

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>
		(vacated) TWA: 1900 mg/m <sup>3</sup>	
ACETONE	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	-
		(vacated) STEL: 2400 mg/m <sup>3</sup> The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
Isopropanol	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m <sup>3</sup>
		(vacated) TWA: 980 mg/m <sup>3</sup>	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m <sup>3</sup>
		(vacated) STEL: 1225 mg/m <sup>3</sup>	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

## Appropriate engineering controls

Engineering Controls	Showers	
	Eyewash stations Ventilation systems	

## Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses or goggles if splashing is likely to occur.	
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.	
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.	
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.	

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Appearance Odor Odor threshold	Liquid Clear Colorless Alcohol No information available	
<u>Property</u> pH Melting point / freezing point Boiling point / boiling range Flash point	<u>Values</u> 1.5 - 2.5 No information available No information available -3 °C / 27 °F	Remarks • Method

Evaporation rate
Flammability (solid, gas)
Flammability Limit in Air
Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density
Relative density
Water solubility
Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
Dynamic viscosity
Explosive properties
Oxidizing properties

### **Other Information**

.

Softening point Molecular weight VOC Content (%) Density Bulk density

No information available 0.810 - 0.812 Soluble in water No information available No information available

No information available No information available 89 0.806 - 0.808 g/cm3 No information available

# **10. STABILITY AND REACTIVITY**

#### Reactivity

Stable under normal use

#### Chemical stability

Stable under normal conditions

#### Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Heat, flames and sparks. Excessive heat.

# Incompatible materials

None known

# Hazardous Decomposition Products

Carbon oxides

# **11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

hemical Name	Oral LD50	Dermal   D50	Inhalation I C50	
Ingestion	Ingestion may cause irritation to mucous membranes. May be harmful if swallowed.			
Skin contact	May cause skin irritation ar	May cause skin irritation and/or dermatitis.		
Eye contact	Contact with eyes may cau	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.		
Inhalation	May cause irritation of resp	May cause irritation of respiratory tract. May be harmful if inhaled.		

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat)4 h
64-17-5			<b>-</b> , ,
ACETONE	= 5800 mg/kg (Rat)	-	= 50100 mg/m <sup>3</sup> (Rat) 8 h

		<u> </u>		
67-64-1				
sopropanol	= 1870 mg/kg	(Rat) = 4	4059 mg/kg (Rabbit)	= 72600 mg/m³(Rat)4 h
67-63-0				
nformation on toxicologica	al effects			
ymptoms	No information	n available.		
elayed and immediate effe	ects as well as chronic	effects from short	and long-term exposure	<u>e</u>
Sensitization	No information	n available.		
Germ cell mutagenicity	No information	n available.		
Carcinogenicity	The table belo	w indicates whether	each agency has listed a	any ingredient as a carcinogen
Chemical Name	ACGIH	IARC	NTP	OSHA
THANOL	A3	-	Known	Х
64-17-5				
opropanol	-	Group 3	-	Х
67-63-0				
ACGIH (American Confere		ustrial Hygienists)		
A2 - Suspected Human Care	cinogen			
A3 - Animal Carcinogen	, for Decerch on Concer	1		
IARC (International Agenc Group 1 - Carcinogenic to H		)		
Not classifiable as a human				
NTP (National Toxicology	0			
Known - Known Carcinogen				
OSHA (Occupational Safe		ion of the US Departn	nent of Labor)	
X - Present	<u>,</u>	· · · · · · · · · · · · · · · · · · ·	,	
hronic toxicity	May cause ac	lverse effects on the	bone marrow and blood-	forming system. May cause
-	adverse liver	effects. Contains a k	nown or suspected repro-	ductive toxin.
arget Organ Effects		Blood, Central nervous system, Eyes, Liver, Reproductive System, Respiratory system,		
he following values are ca	alculated based on cha	pter 3.1 of the GHS	document .	
ATEmix (oral)	9100 mg/kg			
ATEmix (dermal)	27060 mg/kg			

#### 27060 mg/kg

# ATEmix (dermal) ATEmix (inhalation-dust/mist) 120.1 mg/l

# **12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

0.75 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

## Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

## **Mobility**

Disperses in water.

Chemical Name	Partition coefficient
ETHANOL	-0.32
64-17-5	
ACETONE	-0.24
67-64-1	
Isopropanol	0.05
67-63-0	

#### Other adverse effects

No information available

# **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and<br/>regulations. Recover or recycle if possible. This material, as supplied, is a hazardous waste<br/>according to federal regulations (40 CFR 261).Contaminated packagingDo not reuse container.US EPA Waste NumberD001, U002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ETHANOL	Toxic
64-17-5	Ignitable
ACETONE	Ignitable
67-64-1	
Isopropanol	Toxic
67-63-0	Ignitable

# 14. TRANSPORT INFORMATION

<u>DOT</u> UN/ID No Proper shipping name: Hazard Class Packing Group	UN 1987 Alcohols, n.o.s, (Ethyl alcohol), Limited Quantity (LQ) 3 II
<u>IATA</u> UN/ID No Proper shipping name: Hazard Class Packing Group	UN 1987 Alcohols, n.o.s, (Ethyl alcohol), Limited Quantity (LQ) 3 II
IMDG UN/ID No Proper shipping name: Hazard Class Packing Group	UN 1987 Alcohols, n.o.s, (Ethyl alcohol), Limited Quantity (LQ) 3 II

# 15. REGULATORY INFORMATION

Legend:

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

#### TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

#### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
Isopropanol - 67-63-0	1.0	
SARA 311/312 Hazard Categories		
Acute health hazard	No	
Chronic Health Hazard	No	
Fire hazard	Yes	
Sudden release of pressure hazard	No	
Reactive Hazard	No	

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

	Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
	ACETONE	5000 lb	-	RQ 5000 lb final RQ
	67-64-1			RQ 2270 kg final RQ
110.04	to Dowylations		•	

US State Regulations

#### California Proposition 65

Ethanol is only considered a Proposition 65 developmental hazard when it is ingested as a alcoholic beverage. Intended use for this product does not include consumption.

Chemical Name	California Proposition 65
ETHANOL - 64-17-5	Carcinogen
	Developmental

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ETHANOL	Х	Х	Х
64-17-5 ACETONE	X	X	X
67-64-1	~		~
Isopropanol 67-63-0	Х	X	Х
WATER 7732-18-5	-	-	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

#### WHMIS Hazard Class

D2A - Very toxic materials, B2 - Flammable liquid, D2B - Toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 1	Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date	27-Sep-2018	
Revision Note		4

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet