

according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifierUFI: G96M-N0NC-76P6-QMF0

730(E) Spragrip®

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

End belt slippage for all V, flat and round belts - rubber, leather or fabric.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Chesterton International GmbH

Street: Am Lenzenfleck 23

Place: D-85737 Ismaning GERMANY

Telephone: +49 89 99 65 46 - 0 Telefax: +49 89 99 65 46 - 50

e-mail: eu-sds@chesterton.com
e-mail (Contact person): eu-sds@chesterton.com
Internet: www.chesterton.com
Responsible Department: eu-sds@chesterton.com

1.4. Emergency telephone +49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Signal word: Danger



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 2 of 12

Pictograms:







Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe gas.

P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	GHS Classification				
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
	920-750-0		01-2119473851-33		
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066				
75-28-5	isobutane		10-20 %		
	200-857-2	601-004-00-0	01-2119485395-27		
	Flam. Gas 1; H220				

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	35-45 %
	inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg		

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Prolonged and repeated inhalation of decomposition products may cause a pulmonary oedema. Causes eye irritation. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO2)
- Dry extinguishing powder

Unsuitable extinguishing media

Full water jet



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 4 of 12

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Special protective equipment for firefighters: Protective clothing.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Provide adequate ventilation. Safe handling: see section 7

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Personal protection equipment: see section 8

Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Further information on handling

Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Pressurised container: May burst if heated.

Store in a cool dry place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 5 of 12

Hints on joint storage

Protect from direct sunlight.

Further information on storage conditions

Protect against: Frost

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
Worker DNEL,	long-term	inhalation	systemic	2035 mg/m³	
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³	
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day	

8.2. Exposure controls

Appropriate engineering controls

Use only outdoors or in a well-ventilated area.

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Avoid contact with skin, eyes and clothes. Use protective skin cream before handling the product. Remove contaminated, saturated clothing immediately. When using do not eat, drink, smoke, sniff. Wash hands and face before breaks and after work and take a shower if necessary.

Eye/face protection

Suitable eye protection:

- Eye glasses with side protection
- goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374 NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material >= 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer.



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 6 of 12

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respirative protection necessary.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Half-face mask A-P2

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear

Odour: Washing and cleaning products

Test method

pH-Value: not applicable

Changes in the physical state

Melting point:

No data available
Boiling point or initial boiling point and

product only 93 °C

boiling range:

Sublimation point:

Softening point:

No data available

No data available

Pour point:

No data available

No data available

Flash point:

product only 5 °C

Flammability

Solid/liquid: No data available
Gas: No data available

Explosive properties

Vapours can form explosive mixtures with air.

Self-ignition temperature

Solid: No data available
Gas: No data available
Decomposition temperature: No data available

Oxidizing properties

No information available.

Vapour pressure:

Density (at 20 °C):

Water solubility:

No data available
product only 0,8 g/cm³
practically insoluble

Solubility in other solvents
No information available.



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 7 of 12

Partition coefficient n-octanol/water:

Viscosity / dynamic:

No data available

No data available

Viscosity / kinematic:

product only >20 mm²/s

(at 40 °C)

Relative vapour density: >1 (Air = 1)
Evaporation rate: <1 (Ether = 1)

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

This material is considered to be non-reactive under normal use conditions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

- Strong acid
- Strong alkali
- Oxidising agent

10.6. Hazardous decomposition products

- Nitrogen oxides (NOx)
- Carbon dioxide (CO2)
- Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics					
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	_ , , , ,	The acute toxicity of SBP 100/140 was de	
	' ' '	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403	



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 8 of 12

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 9 of 12

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
	Hydrocarbons, C7-C9, n-	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
	Acute fish toxicity	LL50 mg/l	3 - 10	96 h	Oncorhynchus mykiss	Study report (1995)	OECD Guideline 203	
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201	
	Acute crustacea toxicity	EL50	7,4 mg/l	48 h	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 202	
	Fish toxicity	NOEC mg/l	0,574	28 d	Oncorhynchus mykiss	Hydrocarbon Solvents Consortium SEIF (HS	The aquatic toxicity was estimated by a	
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211	
75-28-5	isobutane							
	Acute fish toxicity	LC50 mg/l	49,9		Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo	
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 10 of 12

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 11 of 12

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es): 2.1
14.4. Packing group: -

Hazard label: 2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: Hydrocarbons

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

isobutane

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID:Règlement international conernat le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods



according to Regulation (EC) No 1907/2006

730(E) Spragrip®

Revision date: 22.04.2021 Page 12 of 12

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society) GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effectice concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration PBT: Persistent. Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

This information is based solely on data privided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose.

The user must make their own determination as to suitability.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)