Revision Date: 02/28/2020

SAFETY DATA SHEET

1. Identification

Product identifier: GOODBYE GRAFFITI - F00178

Other means of identification

SDS number: RE1000036969

Recommended restrictions

Product use: Cleaner

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: VICTORIA BAY PRODUCTS

Address: 255 ROUTE 1 & 9

JERSEY CITY, NJ 07306

Telephone: 800-226-3233

Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Toxic to reproduction Category 2
Specific Target Organ Toxicity - Category 3¹

Single Exposure

Specific Target Organ Toxicity - Category 2

Repeated Exposure

Aspiration Hazard Category 1

Target Organs

Narcotic effect.

Environmental Hazards

Acute hazards to the aquatic Category 3

environment

Label Elements

Hazard Symbol:



Signal Word: Danger

Revision Date: 02/28/2020

Hazard Statement: Extremely flammable aerosol.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid release to the

environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific

treatment (see on this label). Take off contaminated clothing.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store locked up. Store in a well-ventilated place. Keep

container tightly closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Benzene, methyl-	108-88-3	10 - <25%
Propane	74-98-6	5 - <10%
2-Propanone	67-64-1	5 - <10%
Butane	106-97-8	5 - <10%
Ethanol, 2-butoxy-	111-76-2	1 - <5%
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - <5%
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, bis(hydrogenated tallow alkyl)dimethylammonium salt with b	71011-25-1	1 - <5%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Revision Date: 02/28/2020

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

Inhalation: Move to fresh air.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash contaminated clothing

before reuse. Get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Revision Date: 02/28/2020

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop

the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you

can do so without risk.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe

to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 2

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure	Limit Values	Source
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
2-Propanone	STEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL		2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	TWA	750 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (03 2015)
	REL	250 ppm	590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Ethanol, 2-butoxy-	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	REL	5 ppm	24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm	240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	25 ppm	120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Ethanol, 2-(2-butoxyethoxy) Inhalable fraction and vapor.	TWA	10 ppm		US. ACGIH Threshold Limit Values (03 2013)
Sodium hydroxide (Na(OH))	Ceiling		2 mg/m3	US. ACGIH Threshold Limit Values (2008)
	Ceiling		2 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceil_Time		2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL		2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Morpholine	REL	20 ppm	70 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)

Revision Date: 02/28/2020

	STEL	30 ppm	105 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA	20 ppm	70 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	30 ppm	105 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	20 ppm	70 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Crystalline Silica - Respirable dust.	REL		0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Crystalline Silica - Respirable.	TWA		2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica - Respirable fraction.	TWA		0.025 mg/m3	US. ACGIH Threshold Limit Values (2008)
Crystalline Silica - Respirable dust.	TWA		0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Crystalline Silica - Respirable dust.	TWA		0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
Crystalline Silica - Respirable dust.	PEL		0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Crystalline Silica - Respirable dust.	OSHA_AC T		0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
Ethanol, 2-methoxy-	TWA	0.1 ppm		US. ACGIH Threshold Limit Values (2008)
	REL	0.1 ppm	0.3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	25 ppm	80 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	25 ppm	80 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2-Ethanediamine	TWA	10 ppm		US. ACGIH Threshold Limit Values (2008)
	PEL	10 ppm	25 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 ppm	25 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	10 ppm	25 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)

Biological Limit Values

iological zimit raidoc		
Chemical Identity	Exposure Limit Values	Source
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEL (03 2015)
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling time: End of shift.)	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethanol, 2-methoxy- (2-Methoxyacetic acid: Sampling time: End of shift at end of work week.)	1 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

Revision Date: 02/28/2020

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Avoid contact with eyes. Observe good industrial hygiene practices. When

using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands

before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol
Color: No data available.
Odor: No data available.
Odor threshold: No data available.
PH: No data available.
Melting point/freezing point: No data available.
Initial boiling point and boiling range: No data available.

Flash Point: -104.44 °C

Evaporation rate: No data available. Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

No data available.

Vapor pressure: 3,102 - 4,481 hPa (20 °C)

Vapor density:No data available.Density:No data available.Relative density:No data available.

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Viscosity:
No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Revision Date: 02/28/2020

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 33,509.32 mg/kg

Dermal

Product: ATEmix: 17,309.88 mg/kg

Inhalation

Product: ATEmix: 496.89 mg/l ATEmix : 82.82 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

Benzene, methyl- LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target

Organ(s): Liver, Kidney) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation

Experimental result, Key study

Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

2-Propanone NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental

result, Key study

Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

Revision Date: 02/28/2020

Ethanol, 2-butoxy- NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key

study

NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal

Experimental result, Key study

Ethanol, 2-(2- NOAEL (Rat(Female, Male), Oral, 90 d): 250 mg/kg Oral Experimental

butoxyethoxy)- result, Key study

NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, 90 - 120 d): 14 ppm(m) Inhalation

Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Benzene, methyl- in vivo (Rabbit): Irritating Experimental result, Key study

2-Propanone in vivo (Rabbit): Not irritant Experimental result, Supporting study

Ethanol, 2-butoxy- in vivo (Rabbit): Irritating Experimental result, Key study

Ethanol, 2-(2-butoxyethoxy)-

in vivo (Rabbit): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Benzene, methyl- Rabbit, 24 - 72 hrs: Not irritating

2-Propanone Irritating.

Rabbit, 24 hrs: Minimum grade of severe eye irritant

Ethanol, 2-butoxy- Rabbit, 24 - 72 hrs: Irritating

Ethanol, 2-(2- Rabbit, 24 - 72 hrs: Highly irritating

butoxyethoxy)-

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Benzene, methyl2-Propanone
Skin sensitization:, in vivo (Guinea pig): Non sensitising

butoxyethoxy)-

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Revision Date: 02/28/2020

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specified substance(s):

Benzene, methyl- Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: Category 2

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Specified substance(s):

Benzene, methyl- May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Benzene, methyl- LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key

study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Ethanol, 2-butoxy- LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key

study

Ethanol, 2-(2- LC 50 (Lepomis macrochirus, 96 h): 1,300 mg/l Experimental result, Key

butoxyethoxy)- stu

LC 50 (Pimephales promelas, 96 h): 2,400 mg/l Experimental result,

Supporting study

Aquatic Invertebrates

Product: No data available.

Revision Date: 02/28/2020

Specified substance(s):

Benzene, methyl- LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality

LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study

2-Propanone LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Ethanol, 2-butoxy- EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study

Ethanol, 2-(2- LC 50 (Daphnia magna, 48 h): +/- 1,743 mg/l QSAR QSAR, Supporting

butoxyethoxy)- study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Benzene, methyl- NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study

LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study

Ethanol, 2-butoxy- NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Benzene, methyl- LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study

NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Ethanol, 2-butoxy- EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study

EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Benzene, methyl- 100 % (14 d) Detected in water. Experimental result, Weight of Evidence

study

86 % Detected in water. Experimental result, Weight of Evidence study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

2-Propanone 90.9 % (28 d) Detected in water. Experimental result, Key study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

Ethanol, 2-butoxy- 90.4 % Detected in water. Experimental result, Key study

Ethanol, 2-(2- 85 % (28 d) Detected in water. Experimental result, Key study

butoxyethoxy)-

Revision Date: 02/28/2020

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Benzene, methyl- Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment

Experimental result, Key study

2-Propanone Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment

Experimental result, Not specified

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Benzene, methylPropane
No data available.
Propanone
No data available.
Propanone
No data available.

tallow alkyl)dimethyl, bis(hydrogenated tallow

alkyl)dimethylammonium salt with b

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): –
Packing Group: II
Marine Pollutant: No

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

Revision Date: 02/28/2020

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2 Label(s): – EmS No.:

Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1
Label(s): –

Packing Group: –

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical IdentityOSHA hazard(s)Crystalline Silicalung effects

immune system effects

Cancer kidney effects

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Benzene, methyl-	lbs. 1000
Propane	lbs. 100
2-Propanone	lbs. 5000
Butane	lbs. 100
Sodium hydroxide (Na(OH))	lbs. 1000
Morpholine	lbs. 100
1,2-Ethanediamine	lbs. 5000

Revision Date: 02/28/2020

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable aerosol Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Toxic to reproduction

Specific Target Organ Toxicity - Single Exposure Specific Target Organ Toxicity - Repeated Exposure

Aspiration Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
2-Propanone		
1,2-Ethanediamine	lbs. 5000	lbs. 10000

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Benzene, methyl-	lbs. 1000
Propane	lbs. 100
2-Propanone	lbs. 5000
Butane	lbs. 100
Ethanol, 2-butoxy-	
Ethanol, 2-(2-butoxyethoxy)-	
Sodium hydroxide (Na(OH))	lbs. 1000
Morpholine	lbs. 100
Ethanol, 2-methoxy-	
1,2-Ethanediamine	lbs. 5000

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
1,2-Ethanediamine	lbs
Benzene, methyl-	10000 lbs
Propane	10000 lbs
2-Propanone	10000 lbs
Butane	10000 lbs
Ethanol, 2-butoxy-	10000 lbs
Ethanol, 2-(2-butoxyethoxy)-	10000 lbs
Quaternary ammonium compounds,	10000 lbs
benzyl(hydrogenated tallow alkyl)dimethyl,	
bis(hydrogenated tallow	
alkyl)dimethylammonium salt with b	
Sodium hydroxide (Na(OH))	10000 lbs
Morpholine	10000 lbs
Crystalline Silica	10000 lbs
Ethanol, 2-methoxy-	10000 lbs

SARA 313 (TRI Reporting)

	Reporting threshold	Reporting threshold for
Chemical Identity	for other users	manufacturing and processing
Benzene, methyl-	lbs	lbs.
Ethanol, 2-butoxy-	N230 lbs	N230 lbs.
Ethanol, 2-(2-butoxyethoxy)-	N230 lbs	N230 lbs.

Revision Date: 02/28/2020

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Benzene, methylCrystalline Silica
Ethanol, 2-methoxyEthanol, 2-methoxyDevelopmental toxin. 03 2008
Carcinogenic. 05 2011
Developmental toxin. 03 2008
Male reproductive toxin. 03 2008

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Benzene, methyl-

Propane

2-Propanone

Butane

Ethanol, 2-butoxy-

Ethanol, 2-(2-butoxyethoxy)-

US. Massachusetts RTK - Substance List

Chemical Identity

Crystalline Silica

1,2-Ethanediamine

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Benzene, methyl-

Propane

2-Propanone

Butane

Ethanol, 2-butoxy-

Ethanol, 2-(2-butoxyethoxy)-

9-Octadecenoic acid (9Z)-

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

2-Propanone

Stockholm convention

2-Propanone

Rotterdam convention

2-Propanone

Kyoto protocol

Revision Date: 02/28/2020

Inventory Status:

Australia AICS: On or in compliance with the inventory

Canada DSL Inventory List: On or in compliance with the inventory

EINECS, ELINCS or NLP: Not in compliance with the inventory.

Japan (ENCS) List: Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI): Not in compliance with the inventory.

Canada NDSL Inventory: Not in compliance with the inventory.

Philippines PICCS: Not in compliance with the inventory.

US TSCA Inventory: On or in compliance with the inventory

New Zealand Inventory of Chemicals:

On or in compliance with the inventory

Japan ISHL Listing: Not in compliance with the inventory.

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Mexico INSQ: Not in compliance with the inventory.

Ontario Inventory: On or in compliance with the inventory

Taiwan Chemical Substance Inventory: On or in compliance with the inventory

China Inv. Existing Chemical Substances:

On or in compliance with the inventory

16.Other information, including date of preparation or last revision

Issue Date: 02/28/2020

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.