# SAFETY DATA SHEET

INFLUENCE SPRAY AID

# SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:

**INFLUENCE SPRAY AID** 

DISTRIBUTOR:

Quest Products Corp.

ADDRESS:

11712 230th Street, Linwood, KS 66052

PHONE:

(785) 542-2577

EMERGENCY CHEMTREC PHONE: US: 1-800-424-9300 International: 1-202-483-7616

CHEMICAL NAME: CHEMICAL FAMILY: Proprietary mixture Acidifying surfactant

**CHEMICAL FORMULA: Mixture** 

PRODUCT USE:

Surfactant adjuvant

**SECTION 1 NOTES:** 

None

# **SECTION 2: HAZARDOUS INGREDIENTS**

# **GHS Ratings:**

**Toxicity Categories** Eye corrosion / irritation

Category 1 Category 4



Signal Word: DANGER

**GHS HAZARDS** 

H227 Combustible liquid.

H318 Causes serious eye damage.

**GHS PRECAUTIONS** 

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, sparks, open flames or hot surfaces - No smoking.

P233 Keep container tightly closed. P234 Keep only in original container.

P261 Avoid breathing dust, fume, gas, mist, vapors or spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection and face protection. P301+312 IF SWALLOWED: Call a POISON CENTER, doctor or physician if you feel unwell.

P302+352 IF ON SKIN: Wash with of plenty of soap and water.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do then continue rinsing cautiously. P310 Immediately call a POISON CENTER, doctor or physician.

P307+378 In case of fire: Use Foam, Dry Chemical, CO2, Water Spray to extinguish.

P403+235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents in container to an approved waste disposal facility in accordance with all local, regional, national and international regulations.

# **SECTION 3: HAZARDS IDENTIFICATION**

CAS NO. INGREDIENT % WT 30 - 50%Propionic Acid 79-09-4 Lecithin 8002-43-5 10 - 20% 61790-12-3 5 - 10% Fatty Acid Proprietary Proprietary 1 - 5% 30 - 40% Proprietary Proprietary

NOTE: Product does NOT contain any pesticides or pest control agents.

SECTION 3 NOTES: These specific chemical identities and or exact percentage (concentration) of composition have been withheld as a trade secret.

CARCINOGENICITY

OSHA:

No

ACGIH: No

NTP:

No

IARC:

No

OTHER: No

SDS DATE: 6/2/2015

PAGE 1 OF 5

**INFLUENCE SPRAY AID** 

#### **SECTION 4: FIRST AID MEASURES**

Have the product container with you when calling a poison control center or doctor, or going for treatment.

*IF IN EYES:* Immediately call a poison center, doctor or physician. Rinse cautiously with water for several minutes. Remove contact lenses if present, after the first 5 minutes, then continue cautiously rinsing eye.

IF ON SKIN OR CLOTHING: Take off contaminated clothing and wash it before reuse. Wash skin with plenty of soap and water for several minutes.

IF SWALLOWED: Unless advised otherwise by a poison control center or doctor, have person rinse mouth with water, if able. Do not give anything by mouth to an unconscious person.

*IF INHALED*: Remove person to fresh air and keep at rest in a position comfortable for breathing. If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth to mouth if possible. Call a poison center, doctor or physician if you feel unwell.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 4 NOTES: None

#### **SECTION 5: FIRE FIGHTING MEASURES**

NFPA HAZARD CLASSIFICATION

HEALTH: 3 FLAMMABILITY: 2 REACTIVITY: 0 OTHER: -

IN CASE OF FIRE: In case of fire: Use Foam, Dry Chemical, CO2, Water Spray to extinguish. Keep away from

heat, sparks, open flames or hot surfaces- NO SMOKING.

SPECIAL FIRE FIGHTING PROCEDURES: Use alcohol-type or universal-type foams on larger fires. Smaller fires should be

extinguished with carbon dioxide or dry chemical. Do not use water or foam directly on the fire. Use self-contained breathing apparatus with fighting any fire in an enclosed area.

SDS DATE: 6/2/2015

UNUSUAL FIRE AND EXPLOSION HAZARDS: May be ignited by heat, sparks or flames. Vapors may travel to a source of ignition and

flash back. Containers may explode in heat of fire.

HAZARDOUS DECOMPOSITION PRODUCTS: During combustion, oxides of carbon.

SECTION 5 NOTES: None

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

ACCIDENTAL RELEASE MEASURES: Surround and absorb all spills to prevent material damage. Material should be collected and disposed

in proper manner. Dike the area to prevent spill from spreading. Spilled material should be absorbed onto an inert material and scooped up. Soak up spill with a suitable absorbent. Sweep up absorbed material and place in a chemical waste container for disposal. Wear suitable protective equipment.

SECTION 6 NOTES: None

# **SECTION 7: HANDLING AND STORAGE**

HANDLING Keep out of reach of children. Read label before use. Keep away from heat, sparks, open flames or hot

surfaces – No smoking. Keep container tightly closed. Keep only in original container. Avoid breathing dust, fume, gas, mist, vapors or spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using

this product. Wear protective gloves, protective clothing, eye protection and face protection.

STORAGE: Store in a cool well-ventilated place. Keep in original container tightly closed. Do not reuse empty container. Do

not store with food, feed, or other material to be used or consumed by humans or animals. Do not contaminate

water supplies. For optimal storage, store between 40° and 90° F.

SECTION 7 NOTES: None

SDS DATE: 6/2/2015

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

	OSHA		ACGIH		NIOSH	
0000000-000000-000000-00000-0000-0000-0000	PEL	STEL	PEL	STEL	PEL	STEL
Propionic Acid 79-09-4	10 ppm /8hr 30 mg/m <sup>3</sup>	15 ppm / 15min				

VENTILATION: Normal room ventilation (mechanical) or outdoor use should be satisfactory.

RESPIRATORY PROTECTION: Wear a NIOSH/OSHA approved respirator, approved for use with propionic acid, if necessary.

EYE PROTECTION: Chemical goggles and face shield.

**SKIN PROTECTION:** Chemical gloves, long-sleeved shirts and pants.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash and safety shower should be easily accessible.

WORK HYGIENIC PRACTICES: Wash thoroughly with soap and water after handling product and before eating, drinking, or using

tobacco products. Clean affected clothing, shoes, and protective equipment before reuse.

**EXPOSURE GUIDELINES:** If exposed, see section 4 for acute exposure first aid.

F: Unknown

Combustible

SECTION 8 NOTES: None

INITIAL BOILING POINT:

FLAMMABILITY (solid, gas):

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE: Amber to dark brown FLAMMABLE LIMITS IN AIR, UPPER: Unknown (% BY VOLUME) LOWER: Unknown

ODOR: Strong, vinegar-like

ORDER THRESHOLD; Not known VAPOR PRESSURE (mmHg): @ Unknown

F: Unknown

PHYSICAL STATE: Liquid C: Unknown

pH AS SUPPLIED: Not applicable VAPOR DENSITY (AIR = 1): @ Unknown

pH (Other): Acidic F: Unknown C: Unknown

C: Unknown RELATIVE DENSITY: 0.989 to 1.027

BOILING POINT RANGE: F: Unknown EVAPORATION RATE: Unknown

C: Unknown BASIS (butyl acetate=1):

MELTING POINT: F: Unknown SOLUBILITY IN WATER: Dispersible

C: Unknown
PARTITION COEFFICIENT: (n-octanol/water): Unknown

FREEZING POINT: F: Unknown
C: Unknown AUTO-IGNITION TEMPERATURE: Unknown

FLASH POINT: F: 147 DECOMPOSITION TEMPERATURE: Unknown

C: 64

VISCOSITY: @ Unknown

METHOD USED: PMCC F: Unknown

C: Unknown

CORROSIVITY: Not corrosive to metal by ASTM G31-72

SECTION 9 NOTES: Values are not product specifications.

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

# SAFETY DATA SHEET

INFLUENCE SPRAY AID

**SECTION 10: STABILITY AND REACTIVITY** 

STABILITY:

Stable

Unstable

CONDITIONS TO AVOID (STABILITY):

None known

INCOMPATIBILITY (MATERIAL TO AVOID):

Strong oxidizing agents. Can react with metals, strong bases and amines.

SDS DATE: 6/2/2015

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

During combustion, oxides of carbon.

HAZARDOUS POLYMERIZATION:

Will not occur

CONDITIONS TO AVOID (POLYMERIZATION): No

None known

SECTION 10 NOTES:

None

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

MIXTURE TOXICITY

Dermal Toxicity: >5050mg/kg Oral Toxicity: >5000mg/kg

Acute eye Irritation (Rabbit) score of 65.0 out of 110 effect persisted through 21 day Acute Dermal irritation (Rabbit) 0.8 out of 8.0 based on a 72 hour observation

COMPONENT TOXICITY

Propionic Acid Lecithin Proprietary Fatty acids Proprietary

Not available

Not available

- Oral Toxicity: 2,001.00 mg/kg (Rat)

**SECTION 11 NOTES:** 

None

**SECTION 12: ECOLOGICAL INFORMATION** 

ECOLOGICAL INFORMATION: Not available

**BIOACCUMULATIVE POTENTIAL:** 

OTHER ADVERSE EFFECTS:

ECOTOXICITY: Not available

MOBILITY IN SOIL: Not available

SECTION 12 NOTES: None

**SECTION 13: DISPOSAL CONSIDERATIONS** 

WASTE DISPOSAL METHOD: Do not contaminate water, food or feed by storage or disposal. Dispose of contents in container to an

approved waste disposal facility in accordance with all federal, state and local regulations.

CONTAINER DISPOSAL: Triple rinse (or equivalent) adding rinse water to application tank. Offer container for recycling or

dispose of in a sanitary landfill or by other procedures approved by local regulations.

RCRA HAZARD CLASS: None

SECTION 13 NOTES: None

# SAFETY DATA SHEET

**INFLUENCE SPRAY AID** 

# **SECTION 14: TRANSPORT INFORMATION**

#### U.S. DEPARTMENT OF TRANSPORTATION

NMFC Proper Shipping Name: Adhesive, Adjuvants, Spreaders or Stickers, Sprayable Product, Dry or Liquid

DOT Shipping Description:

PROPER SHIPPING NAME:

Combustible Liquid, N.O.S.

HAZARD CLASS: ID NUMBER: PACKING GROUP: LABEL STATEMENT:

NA1993



120 gallons or more must be placarded as Combustible

SDS DATE: 6/2/2015

NOT REGULATED AS CORROSIVE WHEN TRANSPORTED BY MOTOR VEHICLE OR RAILCAR IN PACKAGING THAT WILL NOT REACT WITH OR BE DEGRADED BY THIS MATERIAL SUCH AS HDPE OR STAINLESS STEEL - 49 CFR 173.154 (d).

Average rate of corrosion for STEEL Coupon test 0.4316 mm/yr Average rate of corrosion for ALUMINUM ALLOY Coupon test .0231 mm/yr

U.S. Surface Freight Classification: ADHESIVES, ADJUVANTS, SPREADERS OR STICKERS (NMFC 4610; CLASS: 60) Consult appropriate ICAO/IATA and IMDG regulations for shipment requirements in the Air and Maritime shipping modes.

OTHER AGENCIES:

None

**SECTION 14 NOTES:** 

None

## **SECTION 15: REGULATORY INFORMATION**

## U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT):

Mixture not listed

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Not Regulated

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT): Not Regulated

311/312 HAZARD CATEGORIES:

None

313 REPORTABLE INGREDIENTS:

None

INTERNATIONAL REGULATIONS: None

SECTION 15 NOTES: None

# **SECTION 16: OTHER INFORMATION**

OTHER INFORMATION: None

# DISCLAIMER:

The recommendation for safe handling and protection procedures is believed to be generally suitable for the standard uses of this compound. However, each user should identify his intended uses of this material and determine whether they are appropriate. All data included in this document is released as typical values and should not be utilized to determine the suitability of this material for a particular use or purpose. No warranty, either expressed or implied, is hereby made, nor do we give permission, inducement, or recommendations to practice any patented invention without a license. All data is offered for consideration, investigation and verification purposes only.

,
WALLAMAWAYEE HALAWAYEE OO I SA
Essammin del Mandrews 10, vorsas es
and among the control
HILLIGO, ALL CORRESPONDED IN THE STATE OF TH
sc=##W##Arxcc1886086nxxYEF#
Straus-Höckebunker/mas/Gufferh
AAACIONYXXXXIIOOOGGECHIXXXXXXII
DAYORXIIFOOPHIBANCOACEPREAT
200CCZZ/2002mDCVC_swine_CCCm+sommune_
алиден данантанын айын айы
в по глужения в применения в пр
че явлого подселующих достой в
ISOCHANDERFRUIRACHISTORIA
евлизименны може петемологени
үүүүүүү далыны дайуулан аруынан
водиру инивививальный верхина в вельного
hada adina Mationomisioooni saatii
ALERI AZARA AL AZIRI KIRILI KARI AZIRI KIRI KIRI KIRI KIRI KIRI KIRI KIRI
WITH A DEVICE OF THE STATE OF T