Product Name: Everglaze Product identifier: 100403 Revision Date: 08-18-2016

Replaces:



#### 1. Identification

Product identifier used on the label:

Product Name: Everglaze Product identifier: 100403

Other means of identification

Synonyms: No data available

Recommended use of the chemical and restrictions on

**Glazing Spot Putty** 

use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Chemical Manufacturer / ITW Evercoat

**Importer / Distributor:** a division of Illinois Tool Works Inc.

6600 Cornell Road Cincinnati, OH 45242

513-489-7600

**Emergency phone number:** CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

### 2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:





**GHS Classification:** Flammable Liquid Category 2

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2A

Reproductive Toxicity Category 2

Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2

Hazardous to the aquatic environment - Acute Category 3 Hazardous to the aquatic environment - Chronic Category 3

GHS Signal Word: Danger

**GHS Hazard Statements:** Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

Page **1** of **11** 

Product Name: Everglaze Product identifier: 100403 Revision Date: 08-18-2016

Replaces:

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

**GHS Precautionary Statements:** 

Safety Precautions:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling. Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

**First Aid Measures:** IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

**Storage:** Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:** Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise

classified:

Reports have associated repeated and prolonged occupational overexposure to

solvents with permanent brain and nervous system damage.

Product Name: Everglaze Product identifier: 100403 Revision Date: 08-18-2016

Replaces:

3. Composition/information on ingredients **Chemical Component:** CAS number and other % (or range) of ingredient unique identifiers 5 - 10 Toluene 108-88-3 Xylene 1330-20-7 1 - 5 123-86-4 1 - 5 n-Butyl acetate Isobutyl Acetate 110-19-0 1 - 5 2-Propanol 67-63-0 0.5 - 1.5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

**Eye Contact:** Immediately flush eyes with plenty of water for at least 20 minutes

retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Flush eyes gently with water for at least 15 minutes, lifting upper &

lower eye lids. Seek immediate medical attention.

**Skin Contact:** Wash with soap and water. Remove contaminated clothing and

launder. Get medical attention if irritation develops or persists. Remove contaminated clothing and continue flushing with water.

Wash affected area thoroughly with soap and water.

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained

individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately. If symptoms develop, immediately move individual away from exposure and into a well ventilated

area/fresh air. Seek immediate medical attention.

**Ingestion:** Do not induce vomiting and seek medical attention immediately.

Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Do not induce vomiting unless directed to do so by medical personnel. Drink plenty of water. Call a physician

or poison control center immediately.

Most important symptoms/effects, acute and delayed:

Most important

No data available

symptoms/effects (Acute):

**Most important** Toluene may be harmful to the human fetus based on positive

**symptoms/effects (Delayed):** results with laboratory animals.

Overexposure to Toluene has been suggested as a cause of the following effects in humans: cardiac sensitization, kidney damage.

**Product Name: Everglaze Product identifier:** 100403 **Revision Date:** 08-18-2016

Replaces:

The substance may have effects on the central nervous system, resulting in decreased learning ability and psychological disorders. Di-2-Ethylhexyl Phthalate: This substance may be a carcinogenic risk

to humans based on animal data. Possible birth defects hazard.

Indication of immediate medical attention and special treatment needed, if necessary:

No additional first aid information available

### 5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical

> extinguishing agents. Water may be ineffective but water spray can be used extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire. Regular foam Carbon dioxide Dry chemical

No data available Unsuitable extinguishing media:

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Fire and/or Explosion

Hazards:

Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

**Hazardous Combustion Products:** 

Special protective equipment and precautions for fire-

fighters:

Toxic and corrosive gases, Carbon dioxide, Carbon monoxide, oxides of nitrogen, Hydrocarbons

Do not enter fire area without proper protection including selfcontained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for

cooling. Fight fire like a fuel oil fire.

Cool exposed containers with water to prevent pressure buildup. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat.

Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal

protective equipment.

Product Name: Everglaze Product identifier: 100403 Revision Date: 08-18-2016

Replaces:

#### 6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Activate available exhaust ventilation equipment in the immediate spill area. All personnel in the area should be protected as in Section 8. Avoid breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

### 7. Handling and storage

Precautions for safe handling:

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the reach of children.

#### Conditions for safe storage, including any incompatibilities

Conditions for safe storage:

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Store in a cool dry place For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact with

incompatible materials.

Materials to Avoid/Chemical Incompatibility:

Strong oxidizing agents Acids Alkalis

Product Name: Everglaze Product identifier: 100403 Revision Date: 08-18-2016

Replaces:

### 8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Toluene	100 ppm	100 ppm	No data available
Xylene	100 ppm	100 ppm	150 ppm
n-Butyl acetate	150 ppm	150 ppm	200 ppm STEL; 950
-			mg/m3 STEL
Isobutyl Acetate	150 ppm	150 ppm	No data available

Appropriate engineering

controls:

Local exhaust ventilation or other engineering controls are normally

required when handling or using this product to avoid

overexposure. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits.

Explosion proof exhaust ventilation should be used.

### Individual protection measures, such as personal protective equipment:

**Eye Protection:** Wear chemically resistant safety glasses with side shields when

handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Splash proof chemical goggles are recommended to

protect against the splash of product.

**Skin Protection:** Wear protective gloves. Inspect gloves for chemical break-through

and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent

repeated or prolonged skin contact, wear impervious clothing and

boots

**Respiratory Protection:** Respiratory protection will be required when handling this product.

Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors. NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter. Air purifying

respirators should not be used in oxygen deficient or IDLH

atmospheres

**Other Protective Equipment:** Splash proof chemical goggles are recommended to protect against

the splash of product. Protective gloves and proper clothing should

be worn to prevent skin contact. Gloves should be made of

neoprene or natural rubber. To prevent repeated or prolonged skin

Product Name: Everglaze Product identifier: 100403 Revision Date: 08-18-2016

Replaces:

contact, wear impervious clothing and boots

### 9. Physical and chemical properties

Appearance (physical state, color, etc.):

Appearance (physical state): Paste Color: Red

Odor: Aromatic solvent odor
Odor threshold: No data available

pH: Neutral

Melting Point/Freezing Point (°C): No data available

Initial Boiling Point and Boiling Range (°C): 111 Flash Point (°C): 7

**Evaporation Rate:**No data available **Flammability (solid, gas):**No data available

Upper/lower flammability or explosive limits:

Upper Flammable/Explosive Limit (%): 7.0 % Lower Flammable/Explosive Limit (%): 1.0%

**Vapor Pressure:**No data available

**Vapor Density:** Heavier than air. Vapors that evolve from this product

will tend to settle and accumulate near the floor.

Relative Density: 1.57
Solubility(ies): Insoluble
Partition coefficient: n-octanol/water: 1.36

Auto-ignition Temperature (°C):No data availableDecomposition Temperature:No data availableViscosity:No data availableVOC (as packaged-less exempts and water):3.9 lbs/qal or 467 g/L

#### 10. Stability and reactivity

**Reactivity:** No data available

**Chemical stability:** Stable under normal conditions.

Possibility of hazardous No data available

reactions:

Conditions to avoid (e.g., static Contamination

discharge, shock, or vibration):

Incompatible materials:Strong oxidizing agents Acids AlkalisHazardous decompositionCarbon dioxide Carbon monoxide

products:

### 11. Toxicological information

Product Name: Everglaze Product identifier: 100403 Revision Date: 08-18-2016

Replaces:

Information on the likely routes

Ingestion, Skin contact, Eye contact, Absorption

of exposure (inhalation,

ingestion, skin and eye contact):

Symptoms related to the physical, chemical and toxicological characteristics:

No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Immediate (Acute) Health Effects by Route of Exposure:

**Inhalation Irritation:** Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea,

headache and possible unconsciousness. Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatique, weakness,

nausea, headache and dizziness.

Can cause severe central nervous system depression (including unconsciousness). Aspiration of material into the lungs may result in chemical pneumonitis which can

be fatal.

**Inhalation Toxicity:** Harmful! Can cause systemic damage (see "Target Organs)

**Skin Contact:** Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

permanent damage.

**Skin Absorption:** Harmful if absorbed through the skin. May cause severe irritation and systemic

damage. Causes skin irritation. Contact may cause irritation and possible dermatitis or sensitization. Symptoms may include minor itching, burning and/or redness,

Dermatitis, defatting may be readily absorbed through the skin.

**Eye Contact:** Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may

include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible. Contact with liquid or vapor may result in irritation,

redness, tearing, and blurred vision.

**Ingestion Irritation:** Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. Causes gastrointestinal tract irritation, nausea, vomiting,

diarrhea and possible ulcerations to mucous membranes.

**Ingestion Toxicity:** Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

**Carcinogenicity:**None of the substances have been shown to cause cancer in long term animal

studies. Not a carcinogen according to NTP, IARC, or OSHA. Possible cancer hazard!

Contains a material that may cause cancer based on animal data.

Reproductive and

Suspected of damaging fertility or the unborn child.

**Developmental Toxicity:** 

**Mutagenicity:** No data available to indicate product or any components present at greater than

0.1% is mutagenic or genotoxic.

**Inhalation:** Upon prolonged and/or repeated exposure, can cause severe respiratory irritation,

dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure

(see "Target Organs)

**Skin Contact:** Upon prolonged or repeated contact, can cause moderate skin irritation, defatting,

Page **8** of **11** 

**Product Name: Everglaze Product identifier:** 100403 **Revision Date:** 08-18-2016

Replaces:

and dermatitis. Not likely to cause permanent damage.

**Skin Absorption:** Upon prolonged or repeated exposure, harmful if absorbed through the skin. May

cause severe irritation and systemic damage.

Numerical measures of toxicity (such as acute toxicity estimates) **Component Toxicology Data** 

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Toluene	Oral LD50 Rat 5000 mg/kg		Inhalation LC50 (4h) Rat 4000 ppm
Xylene	Oral LD50 Rat 4300 mg/kg		Inhalation LC50 (4h) Rat 5000 ppm
n-Butyl acetate	Oral LD50 Rat 13100 mg/kg		Inhalation LC50 (4h) Rat 2000 ppm
Isobutyl Acetate	Oral LD50 Rat 13400 mg/kg		

Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available	N	N	N

#### 12. Ecological information

**Ecotoxicity (aquatic and** terrestrial, where available): Toxic to aquatic life. Toxic to aquatic life with long lasting effects. Harmful to aquatic life. This material is toxic to aquatic organisms and should not be released to sewage, draining systems or any body

of water exceeding concentrations of approved limits under

applicable regulations and permits.

Persistence and degradability:

No data available

Bioaccumulative potential:

No data

Mobility in soil: Other adverse effects (such as No data available No data available

hazardous to the ozone layer):

**Ecological Toxicity Data** 

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
n-Butyl acetate			Aquatic LC50 (96h) 17 -
_			19 MG/L
Xylene			Aquatic LC50 (96h)
			7.711 - 9.591 MG/L

Product Name: Everglaze Product identifier: 100403 Revision Date: 08-18-2016

Replaces:

### 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

**Description of waste residues:**Spent or discarded material is a hazardous waste.
Disposal must be in accordance with applicable Federal,

State/Provincial and Local regulations.

Waste treatment methods Dispose of by incineration following Federal, State, Local, or

(including packaging): Provincial regulations.

Waste Disposal Code(s): D001

### 14. Transport information

UN number: UN1993

**UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (TOLUENE, XYLENE)

Transport hazard class(es): 3
Packing group: ||

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

#### 15. Regulatory information

#### Safety, health and environmental regulations specific for the product in question

**TSCA Status:** The intentional ingredients of this product are listed.

**Regulated Components** 

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Toluene	108-88-3	N	N	Υ	Υ
Xylene	1330-20-7	N	N	Υ	N

#### 16. Other information, including date of preparation or last revision.

**Revision Date:** 08-18-2016

Revision Number: 9

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use,

Product Name: Everglaze Product identifier: 100403 Revision Date: 08-18-2016

Replaces:

recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their

circumstances