

SAFETY DATA SHEET

Revision Date 03-Sep-2014 Version 1

1. IDENTIFICATION

Product identifier

Product Name Permacryl Int Latex Eggshell W/B

Other means of identification

Product Code DE-1531 SKU(s) None

Recommended use of the chemical and restrictions on use
Recommended Use
Uses advised against
No information available.
No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Diamond Vogel Paint 1020 Albany Place SE Orange City, IA 51041 Phone: 712-737-4993

Fax: 712-737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 1A

Emergency Overview

Danger

Hazard statements

May cause cancer



Appearance No information available

Physical state liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

Unknown acute toxicity 2.37% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Titanium dioxide	13463-67-7	10 - 30	*
Ethylene Glycol	107-21-1	1 - 5	*
Crystalline Silica	14808-60-7	1 - 5	*
Kaolin	1332-58-7	1 - 5	*
Texanol	25265-77-4	1 - 5	*
Heavy Paraffinic Distillate	64742-54-7	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice If symptoms persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact Immediate medical attention is not required. Wash off immediately with soap and plenty of

water while removing all contaminated clothes and shoes. If skin irritation persists, call a

physician.

Inhalation Immediate medical attention is not required. If symptoms persist, call a physician. Move to

fresh air in case of accidental inhalation of vapors or decomposition products.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Call a physician. Do NOT induce vomiting.

Self-protection of the first aider Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Alcohol resistant foam.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove all sources of ignition. Evacuate

personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to

flashback. Take precautionary measures against static discharges.

Environmental precautions

Environmental precautionsDo not flush into surface water or sanitary sewer system. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Dam up. Use personal protective equipment as required. Cover liquid spill with sand, earth

or other non-combustible absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers. Take precautionary

measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use

personal protective equipment as required. Do not breathe

dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

Keep away from heat. Keep in properly labeled containers.

Incompatible materialsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

	Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
--	---------------	-----------	----------	------------

Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m ³
Ethylene Glycol 107-21-1	Ceiling: 100 mg/m³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m³	-
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m³ respirable fraction	(vacated) TWA: 0.1 mg/m³ respirable dust : (30)/(%SiO2 + 2) mg/m³ TWA total dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust
Kaolin 1332-58-7	TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection No special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

Property Values Remarks • Method

pH 8.3±0.2
Melting point/freezing point No informa

Melting point/freezing point

No information available

>= 30 °C / 86 °F

Flash point > 94 °C / > 201 °F
Evaporation rate No information available
Flammability (solid, gas)
Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific Gravity 1.27

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available No information available **Decomposition temperature** Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available Oxidizing properties No information available

Other Information

Softening pointNo information availableMolecular weightNo information availableVOC Content (%)No information available

Density 10.61 lbs/gal

Bulk density No information available

Percent solids by weight 48.7% Percent volatile by weight 4.5% Percent solids by volume 37.0% Actual VOC (lbs/gal) 0.5 Actual VOC (grams/liter) 57.8 EPA VOC (lbs/gal) 1.1 EPA VOC (grams/liter) 136 EPA VOC (lb/gal solids) 1.3

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation No data available.

Eye contact No data available.

Skin Contact No data available.

Ingestion No data available.

Official Name Official ED30 Defined ED30 minded official ED30	Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
---	---------------	-----------	-------------	-----------------

Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Ethylene Glycol 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)= 9530 μL/kg (Rabbit)	-
Crystalline Silica 14808-60-7	= 500 mg/kg (Rat)	-	-
Texanol 25265-77-4	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	-
Heavy Paraffinic Distillate 64742-54-7	> 15 g/kg (Rat)	-	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity No information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
Crystalline Silica 14808-60-7	A2	Group 1	Known	Х
Heavy Paraffinic Distillate 64742-54-7	A2	Group 1	-	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Target Organ Effects Central nervous system, Eyes, lungs, Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

20.71% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Ethylene Glycol	6500 - 13000: 96 h	41000: 96 h Oncorhynchus mykiss	46300: 48 h Daphnia magna mg/L
107-21-1	Pseudokirchneriella subcapitata	mg/L LC50 14 - 18: 96 h	EC50
	mg/L EC50	Oncorhynchus mykiss mL/L LC50	
		static 27540: 96 h Lepomis	
		macrochirus mg/L LC50 static	
		40761: 96 h Oncorhynchus mykiss	
		mg/L LC50 static 40000 - 60000: 96	
		h Pimephales promelas mg/L LC50	
		static 16000: 96 h Poecilia reticulata	
		mg/L LC50 static	
Texanol	18.4: 72 h Pseudokirchneriella	30: 96 h Pimephales promelas mg/L	95: 96 h Daphnia magna mg/L LC50
25265-77-4	subcapitata mg/L EC50	LC50	

Heavy Paraffinic Distillate	=	5000: 96 h Oncorhynchus mykiss	1000: 48 h Daphnia magna mg/L
64742-54-7		mg/L LC50	ÉC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Ethylene Glycol 107-21-1	-1.93
Texanol 25265-77-4	3.47

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies Complies *

EINECS/ELINCS

Does not comply *
Does not comply *
IECSC

KECL

PICCS

AICS

Complies *
Complies *
Complies *
Complies *

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

^{*} This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Ethylene Glycol - 107-21-1	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethylene Glycol	5000 lb	-	RQ 5000 lb final RQ
107-21-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
Titanium dioxide - 13463-67-7	Carcinogen	
Crystalline Silica - 14808-60-7	Carcinogen	
Carbon Black - 1333-86-4	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Titanium dioxide 13463-67-7	X	X	X
Ethylene Glycol 107-21-1	X	X	X
Crystalline Silica 14808-60-7	X	X	X
Kaolin 1332-58-7	X	X	X
Ethanolamine 141-43-5	X	X	X
Magnesium nitrate 10377-60-3	X	X	X
Carbon Black 1333-86-4	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Chemical Name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Ethylene Glycol 107-21-1	2.92%	0.31

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0 Physical and Chemical

Properties -

Health hazards 2 * Flammability 1 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Revision Date 03-Sep-2014

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet