

PARKER SUPER O-LUBE SAFETY DATA SHEET

*Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)*

5/11/15

Section I

Product Name: Parker Super O-Lube
Recommended Use: Lubricant (not for medical purpose)
Company: Parker Hannifin Corp., O-Ring Division
2360 Palumbo Drive, PO Box 11751
Lexington, KY 40512
Emergency Telephone No. (859) 269-2351

Section II - Hazards Identification

Classification: Not Hazardous
Labeling: Symbol: None
Signal Word: None
Hazard Statements: Not Hazardous
Precautionary Statements: Use personal protective equipment as required. Wear safety glasses and gloves. Avoid contact with eyes. Nonflammable or combustible, but may burn if involved in a fire.

Section III – Composition/Information on ingredients

Chemical Identity: Dimethyl siloxanes and silicones, 100%
Common Name: Methyl silicone
CAS Number: 63148-62-9
Impurities: No information provided by manufacturer

Section IV – First Aid Measures

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. Obtain medical attention.
Skin Contact: Wash affected area with soap and water. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.
Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.
Ingestion: If swallowed, do not induce vomiting. If irritation or discomfort occurs, obtain medical attention.

Section V – Fire Fighting Measures

Autoignition Temperature: >300°C (572°F)
Flash Point: >300°C (572°F)
Flammable Limits (LEL): Not Determined

Flammable Limites (UEL):	Not Determined
Suitable Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
Unsuitable Extinguishing Media:	None
Specific hazards in case of fire:	Decomposes on heating and can release formaldehyde. Avoid reaction with oxidizers.
Special protective equipment and precautions for the fire fighters:	<p>No acute hazard. Move container from fire area if possible. Avoid breathing vapors and dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self-contained breathing apparatus with a full face piece.</p> <p>Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If so to do so, remove containers from path of fire.</p>

Section VI – Accidental Release Measures

Personal precautions:	Use appropriate person protection. (See section 8)
Environmental precautions:	For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected materials as soon as possible.
Methods for material containment and cleaning up:	Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

Section VII – Handling and Storage

Precautions for safe handling:	Avoid contact with skin, inhalation of mist, or ingestion. See section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated.
Conditions for safe storage, including any incompatibilities:	Store away from oxidizing materials. Store product in a closed

container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

Section VIII – Exposure Controls / Personal Protection

Control parameters:	Under most handling conditions, this product will not generate mist or dust.
Engineering controls:	In most conditions, no special local ventilation is needed. General ventilation recommended. If the product is heated about 150°F or atomized, ventilation should be used.
Personal Protective Equipment (PPE):	
Eyes:	Safety glass recommended
Skin:	Impermeable gloves should be worn. Product is compatible with most elastomers.
Inhalation:	No respiratory protection required under most conditions. If concentrations exceed exposure limits, approved respiratory equipment must be used.

Section IX – Chemical and Physical Properties

Physical State:	Liquid
Color:	Colorless
Odor:	Characteristic mild
Odor Threshold:	Not available
pH Value:	Not applicable
Melting Point:	-23°C
Freezing Point:	-33°C (pour point)
Initial Boiling Point:	>200°C
Flash Point:	>321°C COC
Evaporation Rate:	Not available
Flammability (solid, gas):	Not applicable
Explosion Limits:	Not available
Vapor Pressure:	Negligible at 20 °C
Vapor Density:	Not available
Solubility:	Insoluble in water at 20°C
Partition Coefficient:	Not available
Auto-ignition Temperature:	Not available
Decomposition Temperature:	Begins to decompose at 150°C

Section X – Stability and Reactivity

Chemical Stability:	Stable under ambient temperatures and pressures.
Possibility of hazardous reactions:	May react with air under very high pressure. Otherwise will not react or polymerize.
Conditions to Avoid:	No specific conditions to avoid have been identified.
Materials to Avoid:	Oxidizers
Hazardous decomposition products:	Decomposes on heating and produces formaldehyde, silicone dioxide, and completely burned carbon dioxide.

Section XI – Toxicological Information

(a) Acute toxicity	Not toxic. LD ₅₀ (rat) > 10,000 mg/kg
(b) Skin corrosion/irritation	Not irritation / not corrosive to the skin. LD ₅₀ (rabbit) > 2,000 mg/kg
(c) Serious eye damage/irritation	Possible irritant / not corrosive to the eyes
(d) Respiratory or skin sensitization	Not sensitizing to the skin
(e) Germ-cell mutagenicity	Not a germ cell mutagen
(f) Carcinogenicity	Not a carcinogen
(g) Reproductive toxicity	There are currently no reliable scientific data available indicating adverse effects of reproduction or fertility
(h) Aspiration hazard	Not applicable (not an aerosol/mist)

Section XII – Ecological Information

Toxicity:	Invertebrates: Daphnia magna 48h-LC ₅₀ >10,000 mg/L
Persistence and degradability:	In soil, siloxanes are degraded.
Bioaccumulative potential:	Not expected to bioaccumulate.
Mobility in soil:	Siloxanes are removed from water by sedimentation or binding to sewage sludge.

Section XIII – Disposal Procedures

Waste treatment methods: Waster (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible, or dispose of in an authorized landfill.

According to the European Waste Catalogue: Waster codes are not product specific but application specific. Waste codes should be assigned by the user based on the application in which the product is used.

For USA Disposal: Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

Section XIV – Transport Information

Class or Type: US DOT, IMO, ADR, RID, ADN, IMDG, and IATA: Non-hazardous

Section XV – Regulatory Information

Safety health and environmental regulations/legislations specific for the mixture:

Other Information:

U.S. Regulatory information

TSCA Inventory Status:	All ingredients listed or exempt
TSCA 12 (b) Export Notification:	Not listed
CERCLA Section 103 (40 CFR 302.4):	N
SARA Section 302 (40 CFR 355.30):	N
SARA Section 304 (40 CFR 355.40):	N
SARA Section 313 (40 CFR 372.65):	N
OSHA Process Safety (29 CFR 1910.119):	N
SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21)-	

Acute Hazard: N
Chronic Hazard: N
Fire Hazard: N
Reactivity Hazard: N
Sudden Release Hazard: N

State Regulations: Not on California Proposition 65 List. Does not contain any contaminants or by-products known to the State of California to cause cancer or reproductive toxicity.

Note: There are no known safety, health, or environmental restrictions or prohibitions in any country where this product is produced, imported or marketed.

Chemical Inventories:

DSL (Canada) All ingredients listed or exempt
EINECS (European Union) All ingredients listed or exempt
ENCS/ISHL (Japan) All ingredients listed or exempt
IECSC (Peoples Republic of China) All ingredients listed or exempt
TSCA (United States of America) All ingredients listed or exempt

Section XVI – Other Information

NFPA Hazard Classification:

Health: 1
Flammability: 1
Reactivity: 0
Special Hazards: None

National Fire Protection Associations (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification:

Health: 1
Flammability: 1
Reactivity: 0
Protection: B (See PPE)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and not intended for use in emergency situations.

Prepared by: Parker Hannifin: O-Ring Division
2360 Palumbo Drive
Lexington, KY 40509

Email: ORDmailbox@parker.com
Phone: (859) 335-5101

These data are offered in good faith as typical values and not as product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

Recommendations on application design and material selection are based on available technical data and are offered as suggestions only. Each user should make his own tests to determine the suitability for his own particular use. Parker offers no express or implied warranties concerning the form, fit, or function of a product in any application.