

M A T E R I A L S A F E T Y D A T A S H E E T

Page 1

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5686

PRODUCT NAME: RUSTAME (A/11)

PRODUCT CODE: 5686

HMIS CODES: H C F R P

1 3 0 B

WHMIS CLASS: A & B, 5 & D, 2, B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International

ADDRESS : 2136 Kingston Court
Marietta, GA 30067-8902

INFORMATION PHONE : (770)424-7550

DATE PRINTED: 05/09/2007

PREPARED BY: MAURICIO A. AMAYA, DIRECTOR OF TECHNICAL SERVICES

REVISION DATE: 05/09/2007

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
ANHYDROUS ALCOHOL	64-17-5	1000ppm	1000ppm	40-60%
LPG PROPELLANT	68476-85-7	1000ppm	1000ppm	20-40%
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	100ppm	100ppm	1-5%
TANNIC ACID	1401-55-4	ND	ND	1-5%

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 145 F	SPECIFIC GRAVITY (H2O=1): 0.895
VAPOR DENSITY: ND	EVAPORATION RATE: ND
DENSITY: 7.464 lb/gl	MATERIAL V.O.C.: Approx. 75%
SOLUBILITY IN WATER: SLIGHTLY SOLUBLE	pH (Concentrate): NA
APPEARANCE: OPAQUE BLACK/BROWN LIQUID.	pH (Diluted): NA
ODOR: MILD.	

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: EXTREMELY FLAMMABLE AEROSOL

FLASH POINT: (Conc. Only) 42.8 F

METHOD USED: TOC

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND

UPPER: ND

EXTINGUISHING MEDIA: Dry chemicals, Foam, or Carbon Dioxide.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to cool closed containers in order to prevent pressure build up which may result in containers rupturing. Use self contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to temperatures above 120 deg.F may cause bursting.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5686

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and burning may produce carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to upper respiratory tract, dizziness, nausea and other central nervous system effects.

EYE CONTACT: May cause eye irritation but does not injure eye tissue.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of product into lungs can cause chemical pneumonitis.

CHRONIC EFFECTS OF OVEREXPOSURE: Chronic effects and medical conditions aggravated by overexposure to this product have not been established. Unnecessary exposure to this product or any chemical should be avoided.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If breathing has stopped give artificial respiration. Get IMMEDIATE MEDICAL ATTENTION

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Wash exposed area thoroughly with soap and water. Consult a physician if irritation develops.

24-hour Emergency Phone: (800) 255-3924

PRODUCT CODE: 5686

INGESTION: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a dry, cool place away from heat or open flame. Do not store at temperatures above 120 F.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Not normally required if good ventilation is maintained. Avoid breathing vapors or mist.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: For prolonged contact wear impervious gloves.

EYE PROTECTION: Safety eye protection to protect against splash of liquids and also aerosol size particles is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard Pressure Hazard X

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Regulated only when offered for transportation by aircraft.

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.

M A T E R I A L S A F E T Y D A T A S H E E T

Page 1

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5685

PRODUCT NAME: RUSTAME II
PRODUCT CODE: 5685

HMIS CODES: H C F R P
2 0 0 B

WHMIS CLASS: Not Determined

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
ADDRESS : 1401 Barclay Circle
Marietta, GA 30060
INFORMATION PHONE : (770)424-7550

DATE PRINTED:11/3/2011

PREPARED BY: ALLEN BUCKALEW, TECHNICAL SERVICES
REVISION DATE: 11/03/2011

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
VINYL ACRYLIC POLYMER	Proprietary	ND	ND	
(*)ETHYLENE GLYCOL	107-21-1	50ppm	100ppm	3%
GALLOTANNIN	1401-55-4	ND	ND	

(*) Indicates toxic chemical subject to the reporting requirements of SARA Title III, Sec. 313.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE:	>212 F	SPECIFIC GRAVITY (H2O=1):	1.09
VAPOR DENSITY:	ND	EVAPORATION RATE:	ND
DENSITY:	9.1 lb/gl	MATERIAL V.O.C.:	< 19 grams/Liter
SOLUBILITY IN WATER:	DISPERSIBLE.	pH (Concentrate):	2.0- 2.5
APPEARANCE:	OFF-WHITE, OPAQUE, SLIGHTLY VISCOUS LIQUID	pH (Diluted):	ND
ODOR:	BLAND, ACIDIC-LIKE.		

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: CLASS IIIB

FLASH POINT: NONE

METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND

UPPER: ND

EXTINGUISHING MEDIA: In case of fire, use water fog, dry chemical carbon dioxide, or "alcohol" foam. Water stream may be ineffective and may result in spreading the fire. Water spray (fog) is particularly effective.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to cool closed containers in order to prevent pressure build up which may result in an explosion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. However, containers may burst if overheated in fire. Cool containers using water spray or water fog nozzles.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5685

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Protect product from freezing.

INCOMPATIBILITY (MATERIALS TO AVOID): Materials reactive to water or acids, strong alkali, strong acids, strong oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: May cause nose, throat, and lung irritation.

EYE CONTACT: May cause stinging of eyes followed by irritation.

SKIN CONTACT: Can cause irritation on prolonged or repeated contact which may include the following symptoms: reddening, swelling, or rash.

SKIN ABSORPTION: May be harmful if absorbed through skin.

INGESTION: Can cause mouth , throat, and gastrointestinal tract irritation, nausea, vomiting, and diarrhea. Seek medical attention as required.

CHRONIC EFFECTS OF OVEREXPOSURE: Inhalation or ingestion of material can be irritating and cause burning of the nose, throat and eyes, coughing, and tightness of the chest. Severe overexposure may result in difficulty breathing, headache, nausea, vomiting, drowsiness loss of coordination. Ingestion of small amounts can result in cumulative internal tissue and kidney damage. May result in central nervous system effects.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If person experiences nausea, headache, dizziness, or has difficulty breathing, get medical attention immediately.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Wash exposed area thoroughly with soap and water. Consult a physician if irritation develops.

24-hour Emergency Phone: (800) 255-3924

PRODUCT CODE: 5685

INGESTION: IMMEDIATELY contact a poison control center, emergency treatment center or physician. DO NOT INDUCE VOMITING. If victim is conscious, give large quantity of water or milk. Medical treatment is mandatory. Note: Ingestion of one gallon of this product will provide 100 mls of ethylene glycol, which is considered the lethal dose for an average adult.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistent with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store below 32 F, or above 120 F. Keep container tightly closed when not in use.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None needed unless ventilation is not adequate to reduce vapors below TLV levels. If needed, use a NIOSH approved respirator with an organic vapor cartridge.

VENTILATION: Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSHA safety and health requirements.

PROTECTIVE GLOVES: Impervious gloves recommended.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Synthetic apron to protect against splash of liquids.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard_X Chronic Health Hazard_X Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Cleaning Compound Liquid

DOT HAZARD CLASS: Non-Regulated

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5685

conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.