SAFETY DATA SHEET

1. Identification

Product number	n/a
Product identifier	DRY SIL XL7
Company information	CONTINENTAL RESEARCH CORP. 1180 Central Industrial Dr ST LOUIS, MO 63110-0204 United States
Company phone	General Assistance 314-776-0410
Emergency telephone US	1-800-255-3924

Version #	01
Recommended use	Lubricant
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards Health hazards OSHA defined hazards

Label elements

Flammable aerosols Aspiration hazard Not classified. Category 1 Category 1



Signal word	Danger	
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.	
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.	
Storage	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	40 - 60
Propane		74-98-6	20 - 40
Naphtha (petroleum), Heavy Alkylate		64741-65-7	10 - 20
Dimethylpolysiloxane		63148-62-9	2.5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Skin contact If symptoms develop move victim to fresh air. Get medical attention if symptoms persist. Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.	
Ingestion	Rinse mouth. Get medical attention if symptoms occur.	
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.	
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	
5. Fire-fighting measures		
Suitable extinguishing media	Water spray. Alcohol resistant foam. Powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.	
General fire hazards	Extremely flammable aerosol.	
6. Accidental release meas	sures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.	
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.	
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.	
7. Handling and storage		
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.	
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).	

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	

US. ACGIH Threshold Limit	Values	
Components	Туре	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
US. NIOSH: Pocket Guide to	Chemical Hazards	
Components	Туре	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
Biological limit values	No biological exposure limits noted	for the ingredient(s).
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
Individual protection measures,	such as personal protective equip	ment
Eye/face protection	Face shield is recommended. Wear safety glasses with side shields (or goggles).	
Skin protection		
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.	
Other	Wear suitable protective clothing.	
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.	
Thermal hazards	Wear appropriate thermal protective	e clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

Appearance		
Physical state	Gas.	
Form	Aerosol.	
Color	Not available.	
Odor	Not available.	
Odor threshold	Not available.	
рН	Not available.	
Melting point/freezing point	Not available.	
Initial boiling point and boiling	Not available.	
range Flash point	-156.0 °F (-104.4 °C) Propellant estimated	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or exp	losive limits	
Flammability limit - lower (%)	1 % estimated	
Flammability limit - upper (%)	7 % estimated	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	60 - 70 psig @70F estimated	
Vapor density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Not available.	

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	658 °F (347.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Flame extension	35 in estimated
Heat of combustion (NFPA 30B)	42.06 kJ/g estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.785 - 0.795 estimated
VOC (Weight %)	96 % estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition	No hazardous decomposition products are known.

11.	Toxicological	information

products

Information on likely routes of exposure

	, expectate	
Inhalation	No adverse effects due to inhalation are expected.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and	Aspiration may cause pulmonary edema and pneumonitis.	

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Addie toxicity			
Components	Species	Test Results	
Butane (CAS 106-97-8)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
Propane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Okin conosion/initiation	r folongod okin contact may cauce temperary initiation.

Serious eye damage/eye irritation Respiratory or skin sensitization Respiratory sensitization Skin sensitization Germ cell mutagenicity	Direct contact with eyes may cause temporary irritation.	
Respiratory sensitization Skin sensitization	ion	
Skin sensitization		
	Not a respiratory sensitizer.	
Germ cell mutagenicity	This product is not expected to cause skin sensitization.	
	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	II Evaluation of Carcinogenicity	
Not regulated.	ated Substances (29 CFR 1910.1001-1050)	
	Program (NTP) Report on Carcinogens	
Not listed.	This product is not expected to equipe reproductive or developmental effects	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure		
Specific target organ toxicity - repeated exposure	- Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
12. Ecological informatio	on	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclud possibility that large or frequent spills can have a harmful or damaging effect on the enviro	
Components	Species Test Results	
Naphtha (petroleum), Heavy	y Alkylate (CAS 64741-65-7)	
Aquatic		
Algae	IC50 Algae 30000 mg/L, 72 Hours	
* Estimates for product may	y be based on additional component data not shown.	
Persistence and degradability		
Bioaccumulative potential		
Partition coefficient n-octa	anol / water (log Kow)	
Butane	2.89	
Propane	2.36	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creati potential, endocrine disruption, global warming potential) are expected from this componential of the second	ion nt.
13. Disposal consideration	ons	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the disposal company.	waste
	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Waste from residues / unused products	Disposal instructions).	
	Disposal instructions). Since emptied containers may retain product residue, follow label warnings even after con emptied. Empty containers should be taken to an approved waste handling site for recyclir disposal. Do not re-use empty containers.	
products	Since emptied containers may retain product residue, follow label warnings even after con emptied. Empty containers should be taken to an approved waste handling site for recyclir disposal. Do not re-use empty containers.	
products Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after con emptied. Empty containers should be taken to an approved waste handling site for recyclir disposal. Do not re-use empty containers.	

Transport bazard alaaa(aa)	
Transport hazard class(es)	
Class	2.1
Subsidiary risk	
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Not available.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	
DOT	





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Hazard categories

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butane (CAS 106-97-8)

Naphtha (petroleum), Heavy Alkylate (CAS 64741-65-7)

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	02-19-2018
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names