

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 7/5/2023 Revision date: 7/5/2023 Supersedes: 6/12/2019 Version: 4.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Crosstrans 206
Product code : 531021

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Electrical insulating oil.

1.3. Supplier

Cross Oil Refining & Marketing, Inc.

484 E. 6th Street

Smackover, AR, 71762

US

T 870-864-7500

www.crossoil.com

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (inhalation:dust,mist) Category 4 H332 Harmful if inhaled.

Specific target organ toxicity - Repeated exposure, Category 2 H373 May cause damage to organs through prolonged or repeated

exposure.

Aspiration hazard, Category 1 H304 May be fatal if swallowed and enters airways.

Hazardous to the aquatic environment – Acute Hazard, Category 3 H402 Harmful to aquatic life

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412 Harmful to aquatic life with long lasting effects.

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H304 - May be fatal if swallowed and enters airways.

H332 - Harmful if inhaled.

H373 - May cause damage to organs through prolonged or repeated exposure.

H402 - Harmful to aquatic life

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS US) : P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a poison center or doctor if you feel unwell.

P314 - Get medical advice/attention if you feel unwell.

P331 - Do NOT induce vomiting.

P405 - Store locked up.

 $\ensuremath{\mathsf{P501}}$ - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Hydrotreated Light Naphthenic Base Oil	CAS-No.: 64742-53-6	80 – 100
2,6-di-tert-butylphenol	CAS-No.: 128-39-2	0 – 1

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor

if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

7/5/2023 (Revision date) US - en 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use

only outdoors or in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Crosstrans 206

No additional information available

Hydrotreated Light Naphthenic Base Oil (64742-53-6)

No additional information available

2,6-di-tert-butylphenol (128-39-2)

No additional information available

7/5/2023 (Revision date) US - en 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Amber, clear liquid. Dark amber.

Colour Brown to amber Odour Mild hydrocarbon Odour threshold No data available рΗ No data available Melting point Not applicable Freezing point : No data available : 200 - 423 °C Boiling point : 152 °C Flash point

Relative evaporation rate (butylacetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapour pressure : 0 mm Hg Relative vapour density at 20 °C : No data available

Relative density : 0.89
Density : 7.43 lb/gal

Solubility : Material insoluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available

Viscosity, kinematic : 9.15 mm²/s @ 40°C (104°F)

Viscosity, dynamic : No data available
Explosive limits : No data available
Explosive properties : No data available
Oxidising properties : No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

Crosstrans 206		
ATE US (dust,mist)	2.18 mg/l/4h	
Hydrotreated Light Naphthenic Base Oil (6474	12-53-6)	
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 Inhalation - Rat	2.18 mg/l	
ATE US (vapours)	2.18 mg/l/4h	
ATE US (dust,mist)	2.18 mg/l/4h	
2,6-di-tert-butylphenol (128-39-2)		
LD50 oral rat	> 5000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rat	> 1000 mg/kg Source: IUCLID	
ATE US (dermal)	1100 mg/kg bodyweight	

Skin corrosion/irritation : Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,6-di-tert-butylphenol (128-39-2)	
рН	No data available in the literature
Serious eye damage/irritation	: Not classified
2,6-di-tert-butylphenol (128-39-2)	
рН	No data available in the literature
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
2,6-di-tert-butylphenol (128-39-2)	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: 9.15 mm²/s @ 40°C (104°F)
2,6-di-tert-butylphenol (128-39-2)	
Hydrocarbon	Yes
Symptoms/effects after ingestion	: Risk of lung oedema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hydrotreated Light Naphthenic Base Oil (64742-53-6)		
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID	
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID	
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID	
2,6-di-tert-butylphenol (128-39-2)		
LC50 - Fish [1]	1.4 mg/l (ASTM E729-80, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)	
EC50 - Crustacea [1]	0.45 mg/l (US EPA, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, Locomotor effect)	
EC50 72h - Algae [1]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	1.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [1]	1.2 mg/l (EPA OTS 797.1050, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Cell numbers)	
EC50 96h - Algae [2]	1.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,6-di-tert-butylphenol (128-39-2)	
LOEC (chronic)	0.086 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.035 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

2,6-di-tert-butylphenol (128-39-2)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

Hydrotreated Light Naphthenic Base Oil (64742-53-6)		
Partition coefficient n-octanol/water (Log Pow) 3.9 – 6 Source: IUCLID		
2,6-di-tert-butylphenol (128-39-2)		
BCF - Fish [1]	660 l/kg (3 day(s), Leuciscus idus, Static system, Fresh water, Weight of evidence)	
Partition coefficient n-octanol/water (Log Pow)	4.5 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 24 °C)	
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).	

12.4. Mobility in soil

2,6-di-tert-butylphenol (128-39-2)	
Surface tension	30.1 mN/m (QSAR)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.65 (log Koc, Calculated value)
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	IATA
14.3. Transport hazard class(es	3)		
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

DOT

Not regulated

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Hydrotreated Light Naphthenic Base Oil	64742-53-6	Present	Active	
2,6-di-tert-butylphenol	128-39-2	Present	Active	TP

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Hydrotreated Light Naphthenic Base Oil (64742-53-6)

Listed on the Canadian DSL (Domestic Substances List)

2,6-di-tert-butylphenol (128-39-2)

Listed on the Canadian DSL (Domestic Substances List)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

2,6-di-tert-butylphenol (128-39-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 7/5/2023

Full text of H-statements		
H304 May be fatal if swallowed and enters airways.		
H332	Harmful if inhaled.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H402	Harmful to aquatic life	
H412	Harmful to aquatic life with long lasting effects.	

Safety Data Sheet (SDS), USA

Information provided in this Safety Data Sheet is considered accurate and reliable based on information issued from internal and outside sources to the best of Cross Oil Refining & Marketing, Inc.'s knowledge; however, Cross Oil Refining & Marketing, Inc. makes no representations, guarantees or warranties, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such information or the result to be obtained from the use thereof or as to the sufficiency of information herein presented. Cross Oil Refining & Marketing, Inc. assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.

This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Cross Oil Refining & Marketing, Inc. must rely upon information provided by the material manufacturers or distributors.