

Safety Data Sheet

Section 1: Identification

Product Identifier

Methanol

Product Name

Trade Name: SPLASH Concentrate 55 Gallon Drum

PN (Part number): 234755

Relevant identified uses of the substance or mixture and uses advised against

-Material for industrial applications

-Industrial and professional use

-Consumer end use

Details of the supplier of the safety data sheet

Manufacturer

FMP

1380 Corporate Center Curve, Suite 200

Eagan, MN 55121

Phone: (888) 784-0208

Emergency telephone number

1-800-535-5053

Section 2: Hazard(s) Identification

Hazard Classification of the substance or mixture

Physical Hazards

Flammable Liquid, Category 2

Health Hazards


Acute toxicity, Oral Category 3

Acute toxicity, Inhalation Category 3

Acute toxicity, Dermal Category 3

Specific Target Organ Toxicity (STOT) following single exposure, Category 1

GHS label elements



Hazard statements

Highly flammable liquid and vapor

Toxic if swallowed

Toxic if inhaled

Toxic in contact with skin

Causes damage to organs (liver, kidneys, central nervous system, optic nerve) (Dermal, inhalation, oral)

Precautionary statements

Prevention

Keep away from heat, sparks, open flames and ignition sources-No Smoking

Keep container tightly closed

Ground or Bond container and receiving equipment

Use explosion-proof electrical, ventilating and lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves and clothing, eye and face protection

Wash hands and arms (or other spilled on body parts) thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe fumes, mist, vapors or spray when using, pouring or transferring

Use only outdoors or in a well-ventilated area

Take off contaminated clothing and wash before use

Keep away from oxidizing materials and strong acids

Response

IF ON SKIN (or hair): Wash skin with soap and water, or shower. Call a poison center or physician if you feel unwell. Specific treatment (see warnings on this label), refer to Section 4 (First Aid Measures) Take off immediately all contaminated clothing and wash it before reuse. Get medical attention if irritation develops.

IF SWALLOWED: Immediately call a poison center or physician. Specific Treatment-Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband. Rinse mouth.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or physician. Specific treatment (see warnings on this label), refer to Section 4 (First Aid Measures)

IF IN EYES: Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 30 minutes. Cold water may be used. Get medical attention immediately.

IN CASE OF FIRE: SMALL FIRE: Use DRY chemical powder, CO_2 or appropriate foam. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

IF EXPOSED or CONCERNED: Immediately call a POISON CENTER or a doctor/physician. Specific treatment (see warnings on this label), refer to Section 4 (First Aid Measures)

Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed. Keep cool

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

Product is stable.

Section 3: Composition/Information on Ingredients					
Substance/mixture:Mixture					
Chemical name: Methanol					
Other means of identification: No					
CAS number/other ider	<u>ntifiers</u>				
Ingredient name	%	CAS number			
Methanol 100 67-56-1					
Section 4: First Aid Me	Section 4: First Aid Measurements				

Description of necessary first aid measures

Eye contact: Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 30 minutes. Cold water may be used. Get medical attention immediately.

Inhalation: Bring accident victims out into the fresh air. Call a physician immediately in severe cases or if recovery is not rapid.

Skin contact: After contact with skin, wash immediately with plenty of water. Remove contaminated clothing and wash before reuse.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact

Can cause irritation to eyes and mucous membranes.

Inhalation

Sore throat, shortness of breath, coughing and congestion.

Skin contact

Irritation, itching, dermatitis.

Ingestion

Irritation to mucous membranes.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Exposure may aggravate acute or chronic asthma, emphysema and bronchitis.

Specific treatments

N/A

Protection of first-aiders

N/A

See toxicological information (Section 11)

Section 5: Fire Fighting Measures

Extinguishing media

Suitable extinguishing media

SMALL FIRE: Use DRY chemical powder, CO₂ or appropriate foam.

LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Unsuitable extinguishing media

None known

Specific hazards arising from the chemical

Vapors may travel back to ignition source. Closed containers exposed to heat may explode.

Hazardous thermal decomposition products/Products of combustion

Products of combustion are carbon oxides (CO, CO_2).

Special protective actions for fire fighters

Do not release runoff from fire control methods to sewers or waterways.

Special protective equipment for fire-fighters

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering.

Environmental precautions

Methods and materials for containment and cleaning up:

Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including: the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Section 7: Handling and Storage

Precautions for safe handling

Protective measures, advice on general occupational hygiene and conditions for safe storage, including any incompatibilities:

Keep away from heat, sparks, open flames, hot surfaces.

- No smoking.

Keep container tightly closed. Ground or bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting, etc. equipment. Use only non-sparking tools. Take precautionary measures against static discharge. No not breathe dust, fumes, gas, mist, vapors or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, clothing, and eye and face protection. Keep container tightly closed in a cool, well-ventilated place. Keep away from oxidizing materials and strong acids.

Store in a well-ventilated area. Keep cool. Keep in an area suitable for flammable liquids.

Section 8: Exposure Controls/Personal Protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limi	its	
Methanol	ACGIH		<u>OSHA</u>	
	<u>(TWA)</u>	<u>(STEL)</u>	<u>(TWA)</u>	<u>(STEL)</u>
	200 ppm	250 ppm	200 ppm; 260 mg/m ³	N/A

Appropriate engineering controls and Environmental exposure controls

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

Individual protection measures

Hygiene measures

None

Eye/face protection: Use chemical safety goggles.

Skin protection

Hand protection and Body protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Other skin protection

Wash hands and other exposed areas with mild soap and water before eating or drinking.

Respiratory protection: No respiratory protection required under normal circumstances.

Respirator Type(s) (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half face piece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full face piece particulate respirator (NIOSH type N100 filter) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, Glycerin, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full face piece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in Oxygendeficient atmospheres.

Section 9: Physical and Chemical Properties

Appearance

Physical state: Colorless liquid Odor: Alcohol Odor threshold: 2620 - 11528 mg/m3 pH: No data available Specific Gravity: 0.792 Melting point: -98°C **Boiling point**: 65°C Flash point: 11°C Evaporation rate (BuAc=1): 4.1 Flammability (solid, gas): Yes Lower and upper explosive (flammable) limits: LEL 6%, UEL 36% Vapor pressure: 128 hPa at20°C Vapor density (Air=1): 1.11 Solubility: Soluble in water Partition coefficient: n-octanol/water: Not Established Auto-ignition temperature: Not Applicable

Decomposition temperature: Not Established

Viscosity: 0.6 mPa.s (20 °C)

VOC%: 100

Section 10: Stability and Reactivity

Reactivity

Stable under recommended storage conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Will not occur.

Conditions to avoid

Temperatures above the flash point and avoid excessive heat, open flame or other sources of ignition.

Incompatible materials

Strong acids

Strong oxidizing agents

Strong reducing agents

Magnesium

Water-reactive materials

Hazardous decomposition products

Will not occur.

Section 11: Toxicological Information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Test		Results	
Methanol	Acute toxic	ity, oral (male rat)	LD50 = 5,628 mg/kg	
	Acute toxic	ity, dermal	LD50 = 15,8	00 mg/kg
	Acute toxic	ity, inhalation (rat)	LC50 = 87.5	mg/l 6.00 Hours
Summary Comments:				
Sensitization				
Product/ingredient name	Test	Results	Basis	
Viethanol		No evidence of se	ensitization effect	
Summary Comments:				
Carcinogenicity				
Product/ingredient name	Test	Results	Basis	
Nethanol		No known carcino	ogenic effects	
ummary Comments:				
Specific target organ toxicity (single	<u>exposure)</u>			
Product/ingredient name	Test		Results	Basis
lethanol	STOT-one-	ime exposure-oral	>5,000 mg/kg	
	STOT-one-1	ime exposure-dermal	>20,000 mg/kg	
	STOT-one-1	ime exposure-inhalation	>20,000 mg/kg	
Summary Commonts:				

Summary Comments:

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Test	Results	Basis	
Methanol		RfD-oral 0.5 m	ng/kg Daily Exposure	
Summary Comments:				
Liver damage when RfD oral ingestion	is exceeded d	laily.		
Aspiration hazard				
Product/ingredient name	Test	Results	Basis	
Methanol	Human expo	osure studies	Tolerance at 200 ppm/40 hours	
Summary Comments:				
Information on the likely routes of ex	posure			
Inhalation may blur vision. Ingesting r	nay irritate th	e gastrointestinal tract		
Potential acute health effects				
Eye contact: Irritating to the	e eyes.			
			n or ingestion may result in visual disturbances, su al damage, specifically permanent motor dysfunc	
Skin contact: Contact of skin	n with methar	nol can produce mild d	ermatitis in humans.	
Ingestion: Tests involving a toxicity from oral exposure.	cute exposure	of rats, mice, and rab	pits have demonstrated methanol to have low acu	te
Symptoms related to the ph	ysical, chemi	cal and toxicological cl	haracteristics	
Eye contact: Eye irritation.				
Inhalation: Blurred vision.				
Skin contact: Skin irritation.				
Ingestion: May irritate the g	gastrointestina	al tract, cause nausea,	and vomiting.	
Potential chronic health effe	ects (Methan	<u>ol)</u>		
Carcinogenicity: N	lo known caro	cinogens.		
Mutagenicity: No	data available	2.		
Teratogenicity: N	o data availab	le.		
Developmental ef	fects: No data	a available.		
Fertility effects: N	lo data availal	ole.		
Numerical measures of toxicity				
Acute toxicity estimates				
Toxic by inhalation, in contact with ski	n and if swalld	owed. Amounts as sma	all as 30-250 mL of pure methanol may be fatal.	
Section 12: Ecological Information				
Toxicity				
Acute Fish toxicity: (Methanol)				
LC50 - Oncorhynchus mykiss (rainbow	trout) - 19,00	00 mg/l - 96 h		

LC50 – Lepomis macrochirus (Bluegill) - 15,400 mg/l - 96 h

Acute toxicity for daphnia: (Methanol)

EC50 - Daphnia magna (Water flea) - 24,500 mg/l - 48 h

EC100 - Daphnia magna (Water flea) - 10,000 mg/l - 24 h

Acute toxicity for algae: (Methanol)

EC50 - Scenedesmus capricornutum (fresh water algae) - 22,000 mg/l - 96 h

Acute bacterial toxicity: (Methanol)

No data available.

Ecotoxicology Assessment: (Methanol)

Material is expected to be slightly toxic to aquatic life.

Persistence and degradability

Biodegradability: (Methanol)

When released into the soil, this material is expected to readily biodegrade. When released into water, this material is expected to readily biodegrade. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals.

Stability in water: (Methanol)

When released into the soil, this material is expected to quickly evaporate. When released into the soil, this material is expected to leach into groundwater.

Photodegradation: (Methanol)

No data available

Volatility (Henry's Law constant): (Methanol)

Partition coefficient n-octanol/water (log K_{ow}) = -0.77

Bioaccumulative potential

Bioaccumulation: (Methanol)

Bioaccumulation Cyprinus carpio (Carp) - 72 d at 20°C

Bioconcentration factor (BCF): 1.0

Mobility in soil: (Methanol)

Distribution among environmental compartments:

When released into the soil, this material is expected to quickly evaporate. When released into the soil, this material is expected to leach into groundwater.

Other adverse effects:

When released into the water, this material is expected to have a half-life between 1 and 10 days. When released into the air, this material is expected to exist in the aerosol phase with a short half-life. When released into air, this material is expected to have a half-life between 10 and 30 days. When released into the air, this material is expected to be readily removed from the atmosphere by wet deposition.

Section 13: Disposal Considerations

Disposal methods

Dispose in accordance with applicable international, national and local laws, ordinances and statutes.

Section 14: Transport Information

UN Number: UN1230

UN Proper Shipping Name: METHANOL

Transport hazard Class(es): 3

Packing Group: II

Land Transport ADR/RID and GGVS/GGVE (Cross Border / Domestic)

Transport Hazard Class(es): 3

Maritime Transport IMDG/GGVSea

Transport Hazard Class(es): 3, 6.1

Marine Pollutant: No

Air Transport ICAO-TI and IATA-DGR

Transport Hazard Class(es): 3, 6.1

Section 15: Regulatory Information

Chemical Inventory Status-Part 1

Ingredient (CAS#)	TSCA	EC	Japan	Australia
Methanol	Yes	Yes	Yes	Yes
(67-56-1)				

Chemical Inventory Status-Part 2


Ingredient (CAS#)	Korea	Canada	Canada	Philippines
		DSL	NDSL	
Methanol	Yes	Yes	No	Yes
(67-56-1)				

Federal, State & International Regulations-Part 1

	SARA 302		SARA 313	
Ingredient (CAS#)	RQ	TPQ	List Chemical	Category
Methanol	No	No	Yes	No
(67-56-1)				

Federal, State & International Regulations-Part 2

	RC	TSCA	
Ingredient (CAS#)	CERCLA	8(d)	
Methanol	5000 lb.	U154	No
(67-56-1)			



Pressure: No,

Fire: Yes,

Reactivity: No

Chemical Weapons Convention: No

TSCA 12b: No

CDTA: No

SARA 311/312:

Acute: Yes, Chronic: Yes,

Mixture/Liquid

Australian Hazchem Code: 2PE

Poison Schedule: No information found

Section 16: Other Information

<u>History</u>

Date of issue: 04/11/17

Version: 2a

Revised Sections(s): Revised Section 2, address change

Prepared by: Andrew Gioino, SPLASH PRODUCTS

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.