



## SAFETY DATA SHEET

### Minus 70 Hydraulic Oil

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

#### 1. Identification

##### Product identifier

**Product name** Minus 70 Hydraulic Oil  
**Product number** L0769-057, L0769-059, L0769-060, L0769-061, L0769-062, L0769-070

##### Recommended use of the chemical and restrictions on use

**Restriction on use** Lubricating oil  
**Uses advised against** No specific uses advised against are identified.

##### Details of the supplier of the safety data sheet

**Manufacturer** Lubriplate Lubricants Co.  
 Corporate Headquarters  
 129 Lockwood Street  
 Newark, NJ 07105

Midwest Office & Plant  
 1500 Oakdale Ave.  
 Toledo, OH 43605  
 419-691-2491  
 419-693-3806

##### Emergency telephone number

**Emergency telephone** Chem-Tel: 1-800-255-3924 (US & Canada only)  
 01-813-248-0585 (Outside US & Canada)

#### 2. Hazard identification

##### Classification of the substance or mixture

**Physical hazards** Flam. Liq. 4 - H227  
**Health hazards** Skin Irrit. 2 - H315 Carc. 2 - H351 Repr. 2 - H361d STOT SE 3 - H336 Asp. Tox. 1 - H304  
**Environmental hazards** Aquatic Chronic 2 - H411

##### Label elements

##### Hazard pictograms



Signal word

Danger

## Minus 70 Hydraulic Oil

<b>Hazard statements</b>	<p>H227 Combustible liquid.  H315 Causes skin irritation.  H351 Suspected of causing cancer.  H361d Suspected of damaging the unborn child.  H336 May cause drowsiness or dizziness.  H304 May be fatal if swallowed and enters airways.  H411 Toxic to aquatic life with long lasting effects.</p>
<b>Precautionary statements</b>	<p>P201 Obtain special instructions before use.  P202 Do not handle until all safety precautions have been read and understood.  P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  P261 Avoid breathing vapour/ spray.  P264 Wash contaminated skin thoroughly after handling.  P271 Use only outdoors or in a well-ventilated area.  P273 Avoid release to the environment.  P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  P302+P352 IF ON SKIN: Wash with plenty of water.  P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  P308+P313 IF exposed or concerned: Get medical advice/ attention.  P312 Call a POISON CENTRE/doctor if you feel unwell.  P321 Specific treatment (see medical advice on this label).  P331 Do NOT induce vomiting.  P332+P313 If skin irritation occurs: Get medical advice/ attention.  P362+P364 Take off contaminated clothing and wash it before reuse.  P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  P391 Collect spillage.  P403+P233 Store in a well-ventilated place. Keep container tightly closed.  P405 Store locked up.  P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Contains</b>	Kerosine (petroleum), toluene
<b>Other hazards</b>	
This product does not contain any substances classified as PBT or vPvB.	

### 3. Composition/information on ingredients

#### Mixtures

<b>Kerosine (petroleum)</b>	<b>10-30%</b>
CAS number: 8008-20-6	
<b>Classification</b>	
Skin Irrit. 2 - H315	
Carc. 2 - H351	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Acute 2 - H401	
Aquatic Chronic 2 - H411	

## Minus 70 Hydraulic Oil

<b>2,6-di-tert-butylphenol</b> <span style="float: right;">&lt;1%</span> CAS number: 128-39-2 M factor (acute) = 1                      M factor (chronic) = 1
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410
<b>toluene</b> <span style="float: right;">&lt;1%</span> CAS number: 108-88-3
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304
<b>White mineral oil (petroleum)</b> <span style="float: right;">&lt;1%</span> CAS number: 8042-47-5
<b>Classification</b> Not Classified
<b>naphthalene</b> <span style="float: right;">&lt;1%</span> CAS number: 91-20-3 M factor (acute) = 1                      M factor (chronic) = 1
<b>Classification</b> Acute Tox. 4 - H302 Carc. 2 - H351 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

**Composition comments**                      \* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

#### 4. First-aid measures

##### Description of first aid measures

##### **General information**

Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

##### **Inhalation**

Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.

## Minus 70 Hydraulic Oil

<b>Ingestion</b>	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin contact</b>	Rinse with water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

### Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.
<b>Ingestion</b>	May cause irritation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.
<b>Skin contact</b>	Redness. Irritating to skin. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.
<b>Eye contact</b>	May cause temporary eye irritation.

### Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## 5. Fire-fighting measures

### Extinguishing media

<b>Suitable extinguishing media</b>	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### Specific hazards arising from the hazardous product

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

### Advice for firefighters

## Minus 70 Hydraulic Oil

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate.
-----------------------------	--

#### Environmental precautions

<b>Environmental precautions</b>	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).
----------------------------------	--

#### Methods and material for containment and cleaning up

<b>Methods for cleaning up</b>	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
--------------------------------	---

#### Reference to other sections

<b>Reference to other sections</b>	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	---

### 7. Handling and storage

#### Precautions for safe handling

## Minus 70 Hydraulic Oil

<b>Usage precautions</b>	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Suspected of causing cancer. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.
<b>Advice on general occupational hygiene</b>	Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### Conditions for safe storage, including any incompatibilities

<b>Storage precautions</b>	Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.
----------------------------	---

<b>Storage class</b>	Miscellaneous hazardous material storage.
----------------------	---

### Specific end use(s)

<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.
----------------------------	---

## 8. Exposure controls/Personal protection

### Control parameters

#### Occupational exposure limits

##### **Kerosine (petroleum)**

Long-term exposure limit (8-hour TWA): ACGIH 200 mg/m<sup>3</sup>

A3, Sk

##### **toluene**

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm 75 mg/m<sup>3</sup>

A4

##### **White mineral oil (petroleum)**

Mineral oil, excluding metal working fluids (pure, highly and severely refined)

##### **naphthalene**

Long-term exposure limit (8-hour TWA): ACGIH 10 ppm 52 mg/m<sup>3</sup>

A3, DSens, Sk

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

A4 = Not Classifiable as a Human Carcinogen.

Sk = Danger of cutaneous absorption.

DSens = Dermal sensitizer.

### Exposure controls

#### **Protective equipment**



## Minus 70 Hydraulic Oil

<b>Appropriate engineering controls</b>	Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.
<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and safety at work. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.
<b>Hand protection</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and any relevant provincial regulation relating to health and safety at work. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
<b>Other skin and body protection</b>	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
<b>Hygiene measures</b>	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
<b>Respiratory protection</b>	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.
<b>Environmental exposure controls</b>	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### 9. Physical and chemical properties

#### Information on basic physical and chemical properties

**Appearance**                      Liquid.

## Minus 70 Hydraulic Oil

<b>Colour</b>	Amber.
<b>Odour</b>	Mild.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	>288°C (>550.4°F)
<b>Flash point</b>	> 93°C/199.4°F Cleveland open cup.
<b>Evaporation rate</b>	< 0.01 (butyl acetate = 1)
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Vapour pressure</b>	<0.0013 kPa @ 25°C
<b>Vapour density</b>	> 5
<b>Relative density</b>	0.87
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	16 cSt @ 40°C
<b>Explosive properties</b>	Not applicable.
<b>Oxidising properties</b>	Not available.
<b>Other information</b>	None.

### 10. Stability and reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	No potentially hazardous reactions known.
<b>Conditions to avoid</b>	There are no known conditions that are likely to result in a hazardous situation.
<b>Materials to avoid</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

### 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity - oral



## Minus 70 Hydraulic Oil

<b>Summary</b>	Based on available data the classification criteria are not met.
<b>Notes (oral LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b><u>Acute toxicity - dermal</u></b>	
<b>Summary</b>	Based on available data the classification criteria are not met.
<b>Notes (dermal LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b><u>Acute toxicity - inhalation</u></b>	
<b>Summary</b>	Based on available data the classification criteria are not met.
<b>Notes (inhalation LC<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b><u>Skin corrosion/irritation</u></b>	
<b>Summary</b>	Causes skin irritation.
<b>Animal data</b>	Irritating.
<b><u>Serious eye damage/irritation</u></b>	
<b>Summary</b>	Based on available data the classification criteria are not met.
<b>Serious eye damage/irritation</b>	Based on available data the classification criteria are not met.
<b><u>Respiratory sensitization</u></b>	
<b>Summary</b>	Based on available data the classification criteria are not met.
<b>Respiratory sensitization</b>	Based on available data the classification criteria are not met.
<b><u>Skin sensitization</u></b>	
<b>Summary</b>	Based on available data the classification criteria are not met.
<b>Skin sensitization</b>	Based on available data the classification criteria are not met.
<b><u>Germ cell mutagenicity</u></b>	
<b>Summary</b>	Based on available data the classification criteria are not met.
<b>Genotoxicity - in vitro</b>	Based on available data the classification criteria are not met.
<b><u>Carcinogenicity</u></b>	
<b>Summary</b>	Suspected of causing cancer.
<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>IARC carcinogenicity</b>	Contains a substance which may be potentially carcinogenic. IARC Group 2B Possibly carcinogenic to humans.
<b><u>Reproductive toxicity</u></b>	
<b>Summary</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - development</b>	Based on available data the classification criteria are not met.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>Summary</b>	May cause drowsiness or dizziness.
<b>STOT - single exposure</b>	STOT SE 3 - H336 May cause drowsiness or dizziness.
<b>Target organs</b>	Central nervous system
<b><u>Specific target organ toxicity - repeated exposure</u></b>	

## Minus 70 Hydraulic Oil

<b>Summary</b>	Based on available data the classification criteria are not met.
<b>STOT - repeated exposure</b>	Not classified as a specific target organ toxicant after repeated exposure.
<b><u>Aspiration hazard</u></b>	
<b>Summary</b>	May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.
<b>Aspiration hazard</b>	Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.
<b><u>General information</u></b>	
<b>General information</b>	May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b><u>Inhalation</u></b>	
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
<b><u>Ingestion</u></b>	
<b>Ingestion</b>	May cause irritation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
<b><u>Skin contact</u></b>	
<b>Skin contact</b>	Redness. Irritating to skin.
<b><u>Eye contact</u></b>	
<b>Eye contact</b>	May cause temporary eye irritation.
<b><u>Route of exposure</u></b>	
<b>Route of exposure</b>	Ingestion Inhalation Skin and/or eye contact
<b><u>Target organs</u></b>	
<b>Target organs</b>	Central nervous system

### 12. Ecological information

<b>Ecotoxicity</b>	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
<b>Toxicity</b>	Based on available data the classification criteria are not met.
<b><u>Acute aquatic toxicity</u></b>	
<b>Summary</b>	Based on available data the classification criteria are not met.
<b><u>Chronic aquatic toxicity</u></b>	
<b>Summary</b>	Toxic to aquatic life with long lasting effects.
<b><u>Persistence and degradability</u></b>	
<b>Persistence and degradability</b>	The degradability of the product is not known.
<b><u>Bioaccumulative potential</u></b>	
<b>Bioaccumulative potential</b>	No data available on bioaccumulation.
<b><u>Partition coefficient</u></b>	
<b>Partition coefficient</b>	Not available.
<b><u>Mobility in soil</u></b>	
<b>Mobility</b>	No data available.
<b><u>Other adverse effects</u></b>	
<b>Other adverse effects</b>	None known.

### 13. Disposal considerations

#### Waste treatment methods

## Minus 70 Hydraulic Oil

### General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

### Disposal methods

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

## 14. Transport information

### General

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

### DOT transport notes

This product is not regulated for road transportation in accordance with 49 CFR Exceptions.

### UN number

UN No. (TDG) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (DOT) UN3082

### UN proper shipping name

**Proper shipping name (TDG)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 2,6-di-tert-butylphenol, naphthalene)

**Proper shipping name (IMDG)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 2,6-di-tert-butylphenol, naphthalene)

**Proper shipping name (ICAO)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 2,6-di-tert-butylphenol, naphthalene)

**Proper shipping name (DOT)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 2,6-di-tert-butylphenol, naphthalene)

### Transport hazard class(es)

DOT class 9

DOT hazard label 9


TDG class 9

TDG label(s) 9

IMDG class 9

ICAO class/division 9

### Transport labels



## Minus 70 Hydraulic Oil

### DOT transport label



### Packing group

TDG packing group	III
IMDG packing group	III
ICAO packing group	III
DOT packing group	III

### Environmental hazards

#### Environmentally hazardous substance/marine pollutant



### Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-A, S-F

DOT reportable quantity RQ: Toluene (980392.1569 lbs), RQ: Naphthalene (776699.0291 lbs)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### 15. Regulatory information

National regulations Hazardous Products Regulations - SOR/2015-17.  
Transportation of Dangerous Goods Regulations -SOR/2015-100.

### Inventories

#### Canada – DSL/NDSL

All the ingredients are listed or exempt.

*White mineral oil (petroleum)*

*Distillates (petroleum), hydrotreated light naphthenic*

*Kerosine (petroleum)*

*naphthalene*

*toluene*

*Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)*

*Benzenesulfonic acid*

### 16. Other information

## Minus 70 Hydraulic Oil

<b>Classification abbreviations and acronyms</b>	Asp. Tox. = Aspiration hazard Carc. = Carcinogenicity Skin Irrit. = Skin irritation STOT SE = Specific target organ toxicity-single exposure Aquatic Chronic = Hazardous to the aquatic environment (chronic)
<b>Training advice</b>	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
<b>Revision comments</b>	Rereleased through new GHS Software.
<b>Revision date</b>	2020-03-26
<b>Revision</b>	4
<b>Supersedes date</b>	2020-03-26
<b>SDS number</b>	4820
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H227 Combustible liquid. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

**End of SDS**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.