M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924
PRODUCT CODE: 3269

PRODUCT NAME: E-Z DOES IT
PRODUCT CODE: 3269

HMIS CODES: **H** 1 **C** 2 **F** 0 **R** 0 **P** A

WHMIS CLASS: Not Determined

========== SECTION I - MANUFACTURER IDENTIFICATION ==========

MANUFACTURER'S NAME: ATCO International
ADDRESS : 1401 Barclay Circle,S.E.
Marietta, GA 30060
INFORMATION PHONE : (770)424-7550
DATE PRINTED: 04/09/2012
PREPARED BY: Allen Buckalew, TECHNICAL SERVICES
REVISION DATE: 04/09/2012

========== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ==========

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
Aliphatic Petroleum Distillate	64742-88-7	100ppm	100ppm	75-85%

========== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ==========

BOILING RANGE: ND
VAPOR DENSITY: Heavier than air
DENSITY: 6.62 lb/gl
SOLUBILITY IN WATER: INSOLUBLE.
APPEARANCE: CLEAR, DARK AMBER LIQUID.
ODOR: SOLVENT.
SPECIFIC GRAVITY (H2O=1): 0.7937
EVAPORATION RATE: Slower than Butyl Acetate
MATERIAL V.O.C.: 35 %
pH (Concentrate): NA
pH (Diluted): NA

========== SECTION IV - FIRE AND EXPLOSION HAZARD DATA ==========

OSHA FLAMMABILITY CLASSIFICATION: CLASS IIIA
FLASH POINT: 150 F **METHOD USED:** TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND **UPPER:** ND

EXTINGUISHING MEDIA: In case of fire, use water fog, dry chemical carbon dioxide, or "alcohol" foam. Water stream may be ineffective and may result in spreading the fire. Water spray (fog) is particularly effective.

SPECIAL FIREFIGHTING PROCEDURES: Wear full protective clothing and positive pressure, self-contained breathing apparatus (SCBA). Evacuate nonessential personnel from the area to prevent human exposure to fire, smoke, fumes or products of combustion. Prevent use of contaminated building, area, and equipment until decontaminated.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. However, containers may burst if overheated in fire. Cool containers using water spray or water fog nozzles.

========== SECTION V - REACTIVITY DATA ==========

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

24-hour Emergency Phone: (800)255-3924
PRODUCT CODE: 3269

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

========== SECTION VI - HEALTH HAZARD DATA ==========

PRIMARY ROUTES OF ENTRY: Inhalation _X_ Eye Contact _X_
Skin Contact _X_ Ingestion _X_

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: May cause respiratory irritation.

EYE CONTACT: May cause severe eye irritation.

SKIN CONTACT: Product is irritating to the skin.

SKIN ABSORBTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: May result in central nervous system effects such as irregular eye movements, convulsions and coma. Aspiration hazard during ingestion or vomiting.

CHRONIC EFFECTS OF OVEREXPOSURE: May result in irreversible lung damage.

CARCINOGENICITY: NTP CARCINOGEN:___ IARC MONOGRAPHS:___ OSHA REGULATED:___

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No evidence of adverse effects from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If not breathing, give artificial respiration, preferably by mechanical means. Avoid mouth to mouth resucitation. If breathing is difficult, give oxygen. Get medical aid immediately.

EYE CONTACT: IN CASE OF CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Holding eyelids apart, irrigate thoroughly the entire surface of the eyes and lids. Do not apply any medicating agents except on the advice of a physician. Get immediate medical attention.

SKIN CONTACT: In case of contact, immediately flush skin with copious amounts of water for at least 15 minutes while removing contaminated clothing. Wash with plenty of soap and water including hair and under fingernails. Do not apply any medicating agents except on the advice from a physician. Get immediate medical attention.

INGESTION: IF SWALLOWED: If victim is fully conscious, immediately give a large quantity of water to drink and induce vomiting. Call a physician immediately and follow recommendations given. Never give anything by mouth to an unconscious person.

24-hour Emergency Phone: (800)255-3924
PRODUCT CODE: 3269

========== **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE** ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Wear chemical safety glasses with side shields or chemical goggles, rubber gloves, rubber boots, long-sleeved shirt, long pants and a NIOSH-approved chemical cartridge respirator with either P-100 or P-95 pre-filters, or use a positive pressure self-contained breathing apparatus (SCBA). Absorb with inert absorbant material, sweep up, and place in a chemical container which can be sealed. Flush the area with water to remove residue. Do not allow wash water to contaminate water supplies by entering floor drains. Dispose of in a manner consistant with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat, sparks, or flame. Store only in well-ventilated areas. Keep from freezing. Always wear appropriate chemical protective clothing when handling and always wash thoroughly afterwards.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

========== **SECTION VIII - PERSONEL SAFETY MEASURES** ==========

RESPIRATORY PROTECTION: Usually not required. Whenever there is potential for airborne exposures, wear NIOSH-approved respiratory protection.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: Wear chemical resistant rubber gloves.

EYE PROTECTION: Wear safety glasses with side shields or safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling. When working with this product, always know where the nearest safety shower and eye wash station are located.

========== **SECTION IX - REGULATORY INFORMATION** ==========

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard_X_ Reactivity Hazard___

Acute Health Hazard_X_ Chronic Health Hazard_X_ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

24-hour Emergency Phone: (800)255-3924
PRODUCT CODE: 3269

========== SECTION X - SHIPPING INFORMATION ==========

DOT SHIPPING NAME: Cleaning Compound - liquid

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

========== DISCLAIMER ==========

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924
PRODUCT CODE: 3270

PRODUCT NAME: E-Z DOES IT (A/16)
PRODUCT CODE: 3270

HMIS CODES:

H	C	F	R	P
1		3	0	C

WHMIS CLASS: Not Determined

========== SECTION I - MANUFACTURER IDENTIFICATION ==========

MANUFACTURER'S NAME: ATCO International
ADDRESS : 1401 Barclay Circle,S.E.
Marietta, GA 30060
INFORMATION PHONE : (770)424-7550
DATE PRINTED: 04/09/2012
PREPARED BY: Allen Buckalew, TECHNICAL SERVICES
REVISION DATE: 04/09/2012

========== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ==========

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
Aliphatic Petroleum Distillate	64742-88-7	100ppm	100ppm	75-85%
Liquefied Petroleum Gas	68476-86-8	NE	1000ppm	

========== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ==========

BOILING RANGE: ND
VAPOR DENSITY: Heavier than air
DENSITY: 6.62 lb/gl
SOLUBILITY IN WATER: INSOLUBLE.
APPEARANCE: CLEAR, AMBER LIQUID.
ODOR: SOLVENT.
SPECIFIC GRAVITY (H2O=1): 0.7937
EVAPORATION RATE: Slower than Butyl Acetate
MATERIAL V.O.C.: 55 %
pH (Concentrate): NA
pH (Diluted): NA

========== SECTION IV - FIRE AND EXPLOSION HAZARD DATA ==========

OSHA FLAMMABILITY CLASSIFICATION: Extremely Flammable (per flame projection method)
FLASH POINT: 150 F (Concentrate) **METHOD USED:** TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND **UPPER:** ND

EXTINGUISHING MEDIA: In case of fire, use water fog, dry chemical carbon dioxide, or "alcohol" foam. Water stream may be ineffective and may result in spreading the fire. Water spray (fog) is particularly effective.

SPECIAL FIREFIGHTING PROCEDURES: Wear full protective clothing and positive pressure, self-contained breathing apparatus (SCBA). Evacuate nonessential personnel from the area to prevent human exposure to fire, smoke, fumes or products of combustion. Prevent use of contaminated building, area, and equipment until decontaminated.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. However, containers may burst if overheated in fire. Cool containers using water spray or water fog nozzles.

========== SECTION V - REACTIVITY DATA ==========

STABILITY: Product is stable under normal conditions.

24-hour Emergency Phone: (800)255-3924
PRODUCT CODE: 3270
CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

========== SECTION VI - HEALTH HAZARD DATA ==========

PRIMARY ROUTES OF ENTRY: Inhalation _X_ Eye Contact _X_
Skin Contact _X_ Ingestion _X_

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: May cause respiratory irritation.

EYE CONTACT: May cause severe eye irritation.

SKIN CONTACT: Product is irritating to the skin.

SKIN ABSORBTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: May result in central nervous system effects such as irregular eye movements, convulsions and coma. Aspiration hazard during ingestion or vomiting.

CHRONIC EFFECTS OF OVEREXPOSURE: May result in irreversible lung damage.

CARCINOGENICITY: NTP CARCINOGEN:___ IARC MONOGRAPHS:___ OSHA REGULATED:___

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: Stomach or intestinal upset, respiratory irritation.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If not breathing, give artificial respiration, preferably by mechanical means. Avoid mouth to mouth resucitation. If breathing is difficult, give oxygen. Get medical aid immediately.

EYE CONTACT: IN CASE OF CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Holding eyelids apart, irrigate thoroughly the entire surface of the eyes and lids. Do not apply any medicating agents except on the advice of a physician. Get immediate medical attention.

SKIN CONTACT: In case of contact, immediately flush skin with copious amounts of water for at least 15 minutes while removing contaminated clothing. Wash with plenty of soap and water including hair and under fingernails. Do not apply any medicating agents except on the advice from a physician. Get immediate medical attention.

INGESTION: IF SWALLOWED: If victim is fully conscious, immediately give a large quantity of water to drink and induce vomiting. Call a physician immediately and follow recommendations given. Never give anything by mouth to an unconscious person.

24-hour Emergency Phone: (800)255-3924
PRODUCT CODE: 3270

NOTE TO PHYSICIAN: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia.

========== **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE** ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Wear chemical safety glasses with side shields or chemical goggles, rubber gloves, rubber boots, long-sleeved shirt, long pants and a NIOSH-approved chemical cartridge respirator with either P-100 or P-95 pre-filters, or use a positive pressure self-contained breathing apparatus (SCBA). Absorb with inert absorbant material, sweep up, and place in a chemical container which can be sealed. Flush the area with water to remove residue. Do not allow wash water to contaminate water supplies by entering floor drains. Dispose of in a manner consistant with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Exposure to temperatures above 120 F may cause container to burst. Keep closure tight and container upright to prevent leakage. Store out of sunlight and away from heat, sparks, or flame. Store only in well-ventilated areas. Keep from freezing. Always wear appropriate chemical protective clothing when handling and always wash thoroughly afterwards.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN. Do not puncture or incinerate container.

========== **SECTION VIII - PERSONEL SAFETY MEASURES** ==========

RESPIRATORY PROTECTION: Usually not required. Whenever there is potential for airborne exposures, wear NIOSH-approved respiratory protection.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: Wear chemical resistant rubber gloves.

EYE PROTECTION: Wear safety glasses with side shields or safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling. When working with this product, always know where the nearest safety shower and eye wash station are located.

========== **SECTION IX - REGULATORY INFORMATION** ==========

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

24-hour Emergency Phone: (800)255-3924
PRODUCT CODE: 3270
SARA Section 312 HAZARD CATEGORIES: Fire Hazard_X_ Reactivity Hazard___

Acute Health Hazard_X_ Chronic Health Hazard_X_ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

========== SECTION X - SHIPPING INFORMATION ==========

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Regulated only when offered for transportation by aircraft.

========== DISCLAIMER ==========

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.