Printing date 09.04.2013 Revision: 30.04.2017

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GAS LEAK DETECTOR LOW TEMP
- · Article number: 22008, 22032, 22128
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the preparation Leak detection fluid
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Highside Chemicals, Inc. 11114 Reichold Road Gulfport, MS 39503 USA Phone: (228) 896-9220

· 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



R36: Irritating to eyes.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



(Contd. on page 2)

Printing date 09.04.2013 Revision: 30.04.2017

Trade name: GAS LEAK DETECTOR - LOW TEMP

(Contd. of page 1)

· Signal word Warning

· Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

· Hazard description:

· WHMIS-symbols:

D2B - Toxic material causing other toxic effects



· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2Fire = 0

REACTIVITY Reactivity = 0

· HMIS Long Term Health Hazard Substances

None of the ingredients is listed.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · 3.2 Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 09.04.2013 Revision: 30.04.2017

Trade name: GAS LEAK DETECTOR - LOW TEMP

	(Conto	d. of page 2
Dangerous components:		
CAS: 57-55-6 EINECS: 200-338-0	Propylene Glycol substance with a Community workplace exposure limit	25-50%
CAS: 9016-45-9	4-nonylphenyl-polyethylene glycol Xi R41; Ŋ N R50 Eye Dam. 1, H318 Aquatic Acute 1, H400	<10%
CAS: 68603-42-9 EINECS: 271-657-0	Coconut diethanolamide Xi R36/38 ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	<10%
	Proprietary Anionic/Nonionic Detergent Blend Xn R22; Xi R36/38; N R51/53 Aquatic Chronic 2, H411 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<10%
CAS: 111-42-2 EINECS: 203-868-0 Index number: 603-071-00-1	2,2'-iminodiethanol Xn R22-48/22; Xi R38-41 STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315	<1,0%

Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

- · 4.2 Most important symptoms and effects, both acute and delayed Gastric or intestinal disorders
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

Medical supervision for at least 48 hours.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

If necessary oxygen respiration treatment.

Printing date 09.04.2013 Revision: 30.04.2017

Trade name: GAS LEAK DETECTOR - LOW TEMP

(Contd. of page 3)

5 Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information No further relevant information available.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

Ensure adequate ventilation

- · 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)

Printing date 09.04.2013 Revision: 30.04.2017

Trade name: GAS LEAK DETECTOR - LOW TEMP

(Contd. of page 4)

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

57-55-6 Propylene Glycol

WEEL (USA) 10 mg/m³

EV (Canada) 155* 10** mg/m³, 50* ppm

*vapour and aerosol;**aerosol only

- · **DNELs** No further relevant information available.
- · PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required under normal conditions of use.
- · Protection of hands: Rubber gloves
- · Eye protection:



Safety glasses

- · **Body protection:** Not required under normal conditions of use.
- · Limitation and supervision of exposure into the environment

No further relevant information available.

Risk management measures

See Section 7 for additional information.

No further relevant information available.

9 Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: Greenish-Yellow.

· Odour: Mild

· Odour threshold: Not determined.

(Contd. on page 6)

Printing date 09.04.2013 Revision: 30.04.2017

Trade name: GAS LEAK DETECTOR - LOW TEMP

	(Contd. o	of paç
pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	212 °F / 100 °C	
Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	>500 °F / >260 °C	
Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not self-igniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	2,6 Vol %	
Upper:	12,6 Vol %	
· Vapour pressure at 20 °C:	23 hPa	
· Density at 20 °C:	1,02 g/cm³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Fully miscible.	
· Partition coefficient (n-octanol/wa	eter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	Not determined.	
Solids content:	Not determined.	
· 9.2 Other information	No further relevant information available.	

10 Stability and reactivity

- · 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with strong acids and alkali.

Reacts with strong oxidizing agents.

(Contd. on page 7)

Printing date 09.04.2013 Revision: 30.04.2017

Trade name: GAS LEAK DETECTOR - LOW TEMP

(Contd. of page 6)

- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Possible in traces.

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Slight irritant effect on skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: The product contains materials that are harmful to the environment.
- · 12.2 Persistence and degradability biodegradable
- · 12.3 Bioaccumulative potential Does not accumulate in organisms
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Due to mechanical actions of the product (e.g. agglutinations) damages may occur.
- · Additional ecological information:
- · General notes:

This statement was deduced from products with a similar structure or composition.

Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 09.04.2013 Revision: 30.04.2017

Trade name: GAS LEAK DETECTOR - LOW TEMP

(Contd. of page 7)

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water only.

Transport information		
· 14.1 UN-Number · DOT, ADR, ADN, IMDG, IATA	N/A	
14.2 UN proper shipping name DOT, ADR, ADN, IMDG, IATA	N/A	
14.3 Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA	N/A	
· 14.4 Packing group · DOT, ADR, IMDG, IATA	N/A	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Ann MARPOL73/78 and the IBC Code	ex II of Not applicable.	
· UN "Model Regulation":	-	

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

111-42-2 2,2'-iminodiethanol

(Contd. on page 9)

Printing date 09.04.2013 Revision: 30.04.2017

Trade name: GAS LEAK DETECTOR - LOW TEMP

(Contd. of page 8)

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65 (California):
- · Chemicals known to cause cancer:

68603-42-9 Coconut diethanolamide

111-42-2 2,2'-iminodiethanol

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic Categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

111-42-2 2,2'-iminodiethanol

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · Canada
- · Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

57-55-6 Propylene Glycol

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

(Contd. on page 10)

Printing date 09.04.2013 Revision: 30.04.2017

Trade name: GAS LEAK DETECTOR - LOW TEMP

H373 Ma H400 Vei	(Contd. of page 9) uses serious eye irritation. y cause damage to organs through prolonged or repeated exposure. ry toxic to aquatic life. kic to aquatic life with long lasting effects.
R36/38 Irrit R38 Irrit R41 Ris R48/22 Ha R50 Vei	rmful if swallowed. ating to eyes and skin. ating to skin. ating to skin. k of serious damage to eyes. rmful: danger of serious damage to health by prolonged exposure if swallowed. ry toxic to aquatic organisms. kic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
ADR: According International (IMDG: International OT: US Deplay IATA: International GHS: Globally ACGIH: American NFPA: Nation HMIS: Hazard WHMIS: World DNEL: Derive	Ons and acronyms: I européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Carriage of Dangerous Goods by Road) ational Maritime Code for Dangerous Goods partment of Transportation tional Air Transport Association y Harmonized System of Classification and Labelling of Chemicals rican Conference of Governmental Industrial Hygienists all Fire Protection Association (USA) tous Materials Identification System (USA) explace Hazardous Materials Information System (Canada) d No-Effect Level (REACH) teled No-Effect Concentration (REACH)

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com