Printing date July 13, 2015

Reviewed on July 13, 2015

### 1 Identification

- · Product identifier
- · Trade name: Riot Control Continuous Discharge Grenade, CS
- · Article number: 1082 (1011574)
- · Recommended use and restriction on use
- · Recommended use: Crowd Control Device
- · Restrictions on use: Contact manufacturer.
- · Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Safariland, LLC 13386 International Parkway Jacksonville, FL 32218 Customer Care (800) 347-1200



ChemTel Inc.

(800)255-3924, +1 (813)248-0585



## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Sol. 1 H228 Flammable solid.



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed. Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· Additional information:

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of ingredient(s) of unknown toxicity.

(Contd. on page 2)

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 1)

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









GHS02 GHS06 GHS07 GHS08

· Signal word Danger

#### · Hazard-determining components of labeling:

[(2-chlorophenyl)methylene]malononitrile

potassium chlorate diphenylamine

potassium perchlorate

#### · Hazard statements

H228 Flammable solid.

H301+H331 Toxic if swallowed or if inhaled.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

### · Precautionary statements

P210 Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P284 Wear respiratory protection.
P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P301+P310 If swallowed: Immediately call a poison center/doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P320 Specific treatment is urgent (see on this label).

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P330 Rinse mouth.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P302+P352 If on skin: Wash with plenty of water.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 3)

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 4 Fire = 0 Reactivity = 4

The substance possesses oxidizing properties.

· HMIS-ratings (scale 0 - 4)



- \* Indicates a long term health hazard from repeated or prolonged exposures.
- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Product will contain various combinations of the following substances. Not all substances will be in each product. .

Mixture of the substances listed below with nonhazardous additions.

| . Dangerous | components:   |           |
|-------------|---|-----------|
|             | •   |           |
| 2698-41-1   | [(2-chlorophenyl)methylene]malononitrile  |           |
|             | Acute Tox. 3, H301; Acute Tox. 2, H330 Resp. Sens. 1, H334  |           |
|             | Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335 |           |
| 9004-70-0   | Nitrocellulose, colloided, granular   |           |
|             |   |           |
| 3811-04-9   | potassium chlorate  |           |
|             | ♠ Ox. Sol. 1, H271  |           |
|             | ♦ Acute Tox. 4, H302; Acute Tox. 4, H332  |           |
| 57-50-1     | sucrose, pure   |           |
| 598-62-9    | manganese carbonate   |           |
| 7757-79-1   | potassium nitrate   |           |
|             | ♠ Ox. Sol. 2, H272  |           |
| 7440-50-8   | copper  |           |
| 1309-48-4   | magnesium oxide   |           |
| 7440-66-6   | zinc metal  |           |
|             | (Contd.   | on page 4 |

Printing date July 13, 2015

Reviewed on July 13, 2015

#### Trade name: Riot Control Continuous Discharge Grenade, CS

| 7770 74 7  |  | l. of page 3) |
|------------|--|---------------|
|            | potassium perchlorate                                      |               |
|            | ♠ Ox. Sol. 1, H271   |               |
|            | Acute Tox. 4, H302   |               |
| 7704-34-9  | sulfur   |               |
|            | 🕠 Skin Irrit. 2, H315                                      |               |
| 592-87-0   | lead dithiocyanate   |               |
|            | & Carc. 1B, H350; Repr. 1A, H360; STOT RE 2, H373          |               |
|            | Acute Tox. 4, H302; Acute Tox. 4, H332                     |               |
| 122-39-4   | diphenylamine  |               |
|            | Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 |               |
|            | <b>♦</b> STOT RE 2, H373                                   |               |
| 557-04-0   | magnesium distearate, pure                                 |               |
| 10294-40-3 | barium chromate  |               |
|            | & Carc. 1A, H350   |               |
|            | Acute Tox. 4, H302; Acute Tox. 4, H332                     |               |
| 69012-64-2 | <u> </u>   | ≤ 2.5%        |
| 1317-61-9  | triiron tetraoxide   |               |
| 7440-21-3  | silicon  |               |
|            | ♠ Flam. Sol. 2, H228                                       |               |
| 7429-90-5  | aluminium powder (pyrophoric)                              |               |
|            | ♠ Pyr. Sol. 1, H250; Water-react. 2, H261                  |               |
| 16291-96-6 | •  |               |
|            |  |               |

#### · Additional information:

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

#### · Notable Trace Components (≤ 0,1% w/w)

### 4 First-aid measures

# · Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

### · After inhalation:

Supply fresh air.

Seek immediate medical advice.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Provide oxygen treatment if affected person has difficulty breathing.

#### · After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Protect unharmed eye.

Remove contact lenses if worn.

(Contd. on page 5)

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 4)

Rinse opened eye for several minutes under running water. Then consult a doctor.

#### · After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

#### · Information for doctor:

#### · Most important symptoms and effects, both acute and delayed

Asthma attacks

Blast injury if mishandled.

Dizziness

Irritant to eyes.

Irritant to skin and mucous membranes.

Breathing difficulty

Coughing

Allergic reactions

Disorientation

#### · Danger

Danger of blast or crush-type injuries.

Danger of pulmonary edema.

Danger of disturbed cardiac rhythm.

Danger of convulsion.

Danger of impaired breathing.

Danger of cerebral edema.

### · Indication of any immediate medical attention and special treatment needed

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

If necessary oxygen respiration treatment.

Contains lead chromate.

Later observation for pneumonia and pulmonary edema.

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

### **5 Fire-fighting measures**

### · Extinguishing media

# · Suitable extinguishing agents:

DO NOT fight fire when fire reaches explosives.

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

· For safety reasons unsuitable extinguishing agents: None.

# · Special hazards arising from the substance or mixture

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

Hazardous combustions products: Metal Compounds, Carbon Monoxide, Carbon Dioxide, Nitrous Oxides, Various complex oxides of metals, Nitrogen.

#### · Advice for firefighters

## · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 6)

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 5)

#### · Additional information

Evacuate area and fight fire from from the upwind side.

Cool endangered receptacles with water spray.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Isolate area and prevent access.

Keep people at a distance and stay upwind.

Wear protective equipment. Keep unprotected persons away.

Remove persons from danger area.

Ensure adequate ventilation.

Protect from heat.

Keep away from ignition sources.

· Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Suppress gases/fumes/haze with water spray.

· Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Handle with care. Avoid jolting, friction and impact.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

· Information about protection against explosions and fires:

Prevent impact and friction.

Keep respiratory protective device available.

Emergency cooling must be available in case of nearby fire.

Protect from heat.

Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

(Contd. on page 7)

Printing date July 13, 2015 Reviewed on July 13, 2015

### Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 6)

Store away from flammable substances.

Do not store together with oxidizing and acidic materials.

Store away from water.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store in dry conditions.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

| •               | vith limit values that require monitoring at the workplace:      |  |
|-----------------|--|--|
| 2698-41-1 [(2-c | hlorophenyl)methylene]malononitrile                              |  |
| PEL (USA)       | Long-term value: 0.4 mg/m³, 0.05 ppm                             |  |
| REL (USA)       | Ceiling limit value: 0.4 mg/m³, 0.05 ppm<br>Skin                 |  |
| TLV (USA)       | Ceiling limit value: 0.39 mg/m³, 0.05 ppm<br>Skin                |  |
| EL (Canada)     | Ceiling limit value: 0.05 ppm<br>Skin                            |  |
| EV (Canada)     | Ceiling limit value: 0.4 mg/m³, 0.05 ppm<br>Skin                 |  |
| LMPE (Mexico)   | Ceiling limit value: 0.05 ppm<br>A4, PIEL                        |  |
| 57-50-1 sucros  | e, pure  |  |
| PEL (USA)       | Long-term value: 15* 5** mg/m³ *total dust **respirable fraction |  |
| REL (USA)       | Long-term value: 10* 5** mg/m³ *total dust **respirable fraction |  |
| TLV (USA)       | Long-term value: 10 mg/m³  |  |
| EL (Canada)     | Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction |  |
| EV (Canada)     | Long-term value: 10 mg/m³ total dust                             |  |
| LMPE (Mexico)   | Long-term value: 10 mg/m³ A4                                     |  |
| 598-62-9 mang   | anese carbonate  |  |
| PEL (USA)       | Ceiling limit value: 5 mg/m³ as Mn                               |  |

Printing date July 13, 2015

Reviewed on July 13, 2015

|                 | (Contd. of pag   | e 7) |
|-----------------|--|------|
| REL (USA)       | Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ as Mn   |      |
| TLV (USA)       | Long-term value: 0.02* 0.1* mg/m³ as Mn; *respirable **inhalable fraction  |      |
| EL (Canada)     | Long-term value: 0.2 mg/m³ as Mn; R  |      |
| LMPE (Mexico)   | Long-term value: 0.2 mg/m³ como Mn   |      |
| 1309-48-4 mag   | nesium oxide   | _    |
| PEL (USA)       | Long-term value: 15* mg/m³ fume; *total particulate  |      |
| TLV (USA)       | Long-term value: 10* mg/m³ *as inhalable fraction  |      |
| EL (Canada)     | Short-term value: 10** mg/m³ Long-term value: 10* 3** mg/m³ *inhalable fume;**respirable dust and fume               |      |
| EV (Canada)     | Long-term value: 10 mg/m³ inhalable  |      |
| LMPE (Mexico)   | Long-term value: 10* mg/m³<br>A4, *fracción respirable   |      |
| 1309-37-1 diiro | n trioxide / iron (III) oxide  |      |
| PEL (USA)       | Long-term value: 10* 15** 5*** mg/m³ *Fume; Rouge: **Total dust, ***respirable                                       |      |
| REL (USA)       | Long-term value: 5 mg/m³ Dust & fume, as Fe  |      |
| TLV (USA)       | Long-term value: 5* mg/m³ *as respirable fraction  |      |
| EL (Canada)     | Short-term value: 10** mg/m³ Long-term value: 5* 10*** 3**** mg/m³ *dust & fume**fume; Rouge: ***total dust****resp. |      |
| EV (Canada)     | Long-term value: 5* 10** mg/m³ *respirable, including Rouge;**total dust   |      |
| LMPE (Mexico)   | Long-term value: 5* mg/m³ A4, *fracción respirable   |      |
| 7440-50-8 copp  | per  |      |
| PEL (USA)       | Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume  |      |
| REL (USA)       | Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume  |      |
| TLV (USA)       | Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu  |      |
|                 | (Contd. on pag   | e 9  |

Printing date July 13, 2015 Reviewed on July 13, 2015

|                   | (Contd. of page  | 8)        |
|-------------------|--|-----------|
| EL (Canada)       | Long-term value: 1* 0.2** mg/m³                                  | 0)        |
|                   | *dusts and mists; **fume, as Cu                                  |           |
| EV (Canada)       | Long-term value: 0.2* 1** mg/m³                                  |           |
|                   | as copper, *fume;**dust and mists                                |           |
| LMPE (Mexico)     | Long-term value: 0.2* 1** mg/m³                                  |           |
|                   | *humo (como Cu);**polvo y niebla (como Cu)                       |           |
| 7440-21-3 silico  |  |           |
| PEL (USA)         | Long-term value: 15* 5** mg/m³                                   |           |
| DEL (110A)        | *total dust **respirable fraction                                |           |
| REL (USA)         | Long-term value: 10* 5** mg/m³ *total dust **respirable fraction |           |
| TI \/ (LICA)      | TLV withdrawn  |           |
| TLV (USA)         |  |           |
| EL (Canada)       | Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction |           |
| EV (Canada)       | Long-term value: 10 mg/m <sup>3</sup>                            |           |
|                   | total dust   |           |
| LMPE (Mexico)     |  |           |
|                   | Long-term value: 10 mg/m <sup>3</sup>                            |           |
|                   | (e)  |           |
|                   | nium powder (pyrophoric)   |           |
| PEL (USA)         | Long-term value: 5 mg/m <sup>3</sup>                             |           |
|                   | as Zr  |           |
| REL (USA)         | Short-term value: 10 mg/m³                                       |           |
|                   | Long-term value: 5 mg/m³<br>as Zr                                |           |
| TLV (USA)         | Short-term value: 10 mg/m³                                       |           |
|                   | Long-term value: 5 mg/m³   |           |
|                   | as Zr  |           |
| EL (Canada)       | Short-term value: 10 mg/m³                                       |           |
|                   | Long-term value: 5 mg/m <sup>3</sup>                             |           |
|                   | as Zr  |           |
| EV (Canada)       | Short-term value: 10 mg/m³                                       |           |
|                   | Long-term value: 5 mg/m³ as zirconium                            |           |
| I MDE (Mavica)    | Short-term value: 10 mg/m³                                       |           |
| LIVIFE (IVIEXICO) | Long-term value: 5 mg/m <sup>3</sup>                             |           |
|                   | A4; como Zr  |           |
| 7429-90-5 alum    | inium powder (pyrophoric)  | $\dashv$  |
| PEL (USA)         | Long-term value: 15*; 15** mg/m³                                 | $\exists$ |
|                   | *Total dust; ** Respirable fraction                              |           |
| REL (USA)         | Long-term value: 10* 5** mg/m³                                   |           |
|                   | as Al*Total dust**Respirable/pyro powd./welding f.               |           |
|                   | (Contd. on page  | 10)       |

Printing date July 13, 2015

Reviewed on July 13, 2015

|                  |   | (Contd. of page 9)  |
|------------------|---|---------------------|
| TLV (USA)        | Long-term value: 1* mg/m³   | (Conta. or page 9)  |
|                  | as Al; *as respirable fraction  |                     |
| EL (Canada)      | Long-term value: 1.0 mg/m³  |                     |
|                  | respirable, as Al   |                     |
| EV (Canada)      | Long-term value: 5 mg/m³ aluminium-containing (as aluminium)  |                     |
| LMPE (Mexico)    | Long-term value: 1* mg/m³<br>A4, *fracciòn respirable   |                     |
| 592-87-0 lead d  | ithiocyanate  |                     |
| PEL (USA)        | Long-term value: 5 mg/m³ as CN; Skin  |                     |
| EV (Canada)      | Long-term value: 0.05 mg/m³ as Pb, Skin (organic compounds)   |                     |
| 122-39-4 diphe   | , , ,   |                     |
| REL (USA)        | Long-term value: 10 mg/m³   |                     |
| TLV (USA)        | Long-term value: 10 mg/m³   |                     |
| EL (Canada)      | Long-term value: 10 mg/m³   |                     |
| EV (Canada)      | Long-term value: 10 mg/m³   |                     |
| LMPE (Mexico)    | Long-term value: 10 mg/m³<br>A4   |                     |
| 557-04-0 magn    | esium distearate, pure  |                     |
| TLV (USA)        | Long-term value: 10 mg/m³   |                     |
| LMPE (Mexico)    | Long-term value: 10 mg/m³<br>A4   |                     |
| 10294-40-3 bar   | ium chromate  |                     |
| PEL (USA)        | Long-term value: 0.005* mg/m³ Ceiling limit value: 0.1** mg/m³ *as Cr(VI) **as CrO3; see 29 CFR 1910.1026 |                     |
| REL (USA)        | Long-term value: 0.0002 mg/m³ as Cr; See Pocket Guide Apps. A and C                                       |                     |
| TLV (USA)        | Long-term value: 0.01 mg/m³ as Cr   |                     |
| EL (Canada)      | Long-term value: 0.01 mg/m³ as Cr; ACGIH A1, IARC 1   |                     |
| LMPE (Mexico)    | Long-term value: 0.01 mg/m³ A1; como Cr   |                     |
| 69012-64-2 Silie | ca-Amorphous Silica fume  |                     |
| TLV (USA)        | TLV withdrawn   |                     |
| EL (Canada)      | Long-term value: 4* 1.5** mg/m³ fume *total; **respirable   |                     |
| EV (Canada)      | Long-term value: 2 mg/m³ respirable   |                     |
|                  |   | (Contd. on page 11) |

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 10)

LMPE (Mexico) Long-term value: 2 mg/m³

(j)

#### · Ingredients with biological limit values:

### 10294-40-3 barium chromate

BEI (USA) 25 µg/L

Medium: urine

Time: end of shift at end of workweek Parameter: Total chromium (fume)

10 μg/L Medium: urine

Time: increase during shift

Parameter: Total chromium (fume)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Avoid close or long term contact with the skin.

Avoid contact with the eyes.

Do not inhale dust / smoke / mist.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

- · Engineering controls: Provide adequate ventilation.
- · Breathing equipment:



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

Wear positive pressure NIOSH or European EN149 vapor respirators when deploying product in large quantities.

Respiratory protection required.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be (Contd. on page 12)

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 11)

checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

Organizational measures should be in place for all activities involving this product.

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Solid material

Color: Grey

Odor: Characteristic
 Odor threshold: Not determined.
 pH-value: Not applicable.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Undetermined.
Undetermined.

Not applicable.

Flammability (solid, gaseous):
Auto-ignition temperature:
Not determined.

Not determined.

Not determined.

· **Auto igniting:** Product is not self-igniting.

· Danger of explosion: Extreme risk of explosion by shock, friction, fire or other sources

of ignition.

· Explosion limits:

Lower:
Upper:
Not determined.

Vapor pressure:
Not applicable.

Density:
Relative density
Not determined.
Not determined.
Not determined.
Not determined.
Not applicable.

(Contd. on page 13)

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 12)

• Evaporation rate Not applicable.

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not applicable. **Kinematic:** Not applicable.

Other information
 No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Flammable solid.

Contact with acids releases toxic gases.

Toxic fumes may be released if heated above the decomposition point.

Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.

Strong exothermic reaction with acids.

Develops toxic gases / fumes.

Conditions to avoid

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

Keep away from heat and direct sunlight.

Cartridge may detonate if case is punctured or severely damaged.

- · Incompatible materials: Contact with acids liberates toxic gas.
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrocarbons

Leadoxide vapor

Bariumoxide vapor

Nitrogen oxides (NOx)

Chlorine compounds

Poisonous gases/vapors

Irritant gases/vapors

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

2698-41-1 [(2-chlorophenyl)methylene]malononitrile

Oral LD50 178 mg/kg (rat)

(Contd. on page 14)

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

|                               | (Contd. of page 13) |
|-------------------------------|---------------------|
| 3811-04-9 potassium chlorate  |                     |
| Oral LD50 1870 mg/kg (rat)    |                     |
| 122-39-4 diphenylamine        |                     |
| Oral LD50 1120 mg/kg (rat)    |                     |
| 7758-97-6 lead chromate       |                     |
| Oral LD50 12000 mg/kg (mouse) |                     |
| Dulman indiant affects        |                     |

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Additional toxicological information: Toxic and/or corrosive effects may be delayed up to 24 hours.
- · Carcinogenic categories

| · NTP (Natio | nal Toxicology Program) |   |
|--------------|-------------------------|---|
| 592-87-0     | lead dithiocyanate      | R |
| 10294-40-3   | barium chromate         | K |
|              |                         |   |

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Probable Routes of Exposure

Ingestion.

Inhalation.

Eye contact.

Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

Irritating to eyes, respiratory system and skin.

Harmful in contact with skin.

Toxic if swallowed or if inhaled.

May cause sensitisation by inhalation and skin contact.

· Repeated Dose Toxicity:

Repeated exposures may result in skin and/or respiratory sensitivity.

May cause damage to organs through prolonged or repeated exposure.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

Toxic for aquatic organisms

The product contains materials that are harmful to the environment.

#### 2698-41-1 [(2-chlorophenyl)methylene]malononitrile

EC50 0.2-0.3 mg/kg (Oncorhynchus mykiss)

- · Persistence and degradability The product is partially biodegradable. Significant residuals remain.
- · Behavior in environmental systems:
- Bioaccumulative potential May be accumulated in organism
- · Mobility in soil No further relevant information available.

(Contd. on page 15)

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 14)

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

This statement was deduced from the properties of the single components.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

· UN proper shipping name

· DOT

· ADR

· IMDG. IATA

· Transport hazard class(es)

UN1700

Tear gas candles

1700 TEAR GAS CANDLES TEAR GAS CANDLES

· DOT



· Class 6.1 Toxic substances

(Contd. on page 16)

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

Contd. of page 15) **Label** 6.1, 4.1

· ADR

· Class 6.1 (TF3) Toxic substances

• **Label** 6.1+4.1

· IMDG



· Class 6.1 Toxic substances

• **Label** 6.1/4.1

·IATA



· Class 6.1 Toxic substances

• **Label** 6.1 (4.1)

· Packing group

· DOT, ADR, IMDG, IATA

• Environmental hazards: Not applicable.

Special precautions for user
 Warning: Toxic substances

- Danger code (Kemler):

• **EMS Number**: F-A,S-G

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

• Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

• UN "Model Regulation": UN1700, Tear gas candles, 6.1 (4.1), II

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 17)

Printing date July 13, 2015

Reviewed on July 13, 2015

| Trade name: Riot Control | Continuous Dischard | ge Grenade, CS | , |
|--------------------------|---------------------|----------------|---|
|                          |                     |                |   |

|  | (Contd. of page 2                   |
|--|-------------------------------------|
| · Section 313 (Specific toxic chemical listings):  |                                     |
| 598-62-9 manganese carbonate   |                                     |
| 7757-79-1 potassium nitrate  |                                     |
| 7440-50-8 copper   |                                     |
| 7440-66-6 zinc metal   |                                     |
| 7429-90-5 aluminium powder (pyrophoric)  |                                     |
| · TSCA (Toxic Substances Control Act):   |                                     |
| All ingredients are listed.  |                                     |
| · Proposition 65 (California)  |                                     |
| Chemicals known to cause cancer:   |                                     |
| Contains trace quantities of substances known to the State of  | of California to cause cancer.      |
| 592-87-0 lead dithiocyanate  |                                     |
| 10294-40-3 barium chromate   |                                     |
| 7758-97-6 lead chromate  |                                     |
| Chemicals known to cause reproductive toxicity for fem   | ales:                               |
| Present in trace quantities.   |                                     |
| 10294-40-3 barium chromate   |                                     |
| 7758-97-6 lead chromate  |                                     |
| Chemicals known to cause reproductive toxicity for male  | es:                                 |
| Present in trace quantities.   |                                     |
| 10294-40-3 barium chromate   |                                     |
| 7758-97-6 lead chromate  |                                     |
| <ul> <li>Chemicals known to cause developmental toxicity:</li> <li>Present in trace quantities.</li> </ul> |                                     |
| 10294-40-3 barium chromate   |                                     |
| 7758-97-6 lead chromate  |                                     |
| · Carcinogenic categories  |                                     |
| · EPA (Environmental Protection Agency)  |                                     |
| 598-62-9 manganese carbonate   | D                                   |
| 7440-50-8 copper   | D                                   |
| 7440-66-6 zinc metal   | D, I, II                            |
| 7778-74-7 potassium perchlorate  | NL NL                               |
| 10294-40-3 barium chromate   | A(inh), D(oral), K/L(inh), CBD(oral |
| · IARC (International Agency for Research on Cancer)   | <b>_</b>                            |
| 1309-37-1 diiron trioxide / iron (III) oxide   |                                     |
| 10294-40-3 barium chromate   |                                     |
| 69012-64-2 Silica-Amorphous Silica fume  |                                     |
| · TLV (Threshold Limit Value established by ACGIH)   | <u> </u>                            |
| 2698-41-1 [(2-chlorophenyl)methylene]malononitrile   | A                                   |
| 57-50-1 sucrose, pure  | A                                   |
| 5. 55 .   545.555, paid  | (Contd. on page                     |

Printing date July 13, 2015

Reviewed on July 13, 2015

|              |   | (Contd. of page 17) |
|--------------|---|---------------------|
| 1309-48-     | 1 magnesium oxide                                       | A4                  |
| 1309-37-     | diiron trioxide / iron (III) oxide                      | A4                  |
| 7440-67-     | zirconium powder (pyrophoric)                           | A4                  |
| 7429-90-     | aluminium powder (pyrophoric)                           | A4                  |
| 122-39-4     | diphenylamine   | A4                  |
| 10294-40-    | B barium chromate                                       | A1                  |
| · NIOSH-Ca   | (National Institute for Occupational Safety and Health) | •                   |
| 10294-40-3   | B barium chromate                                       |                     |
| · State Righ | t to Know Listings                                      |                     |
|              | e ingredients is listed.                                |                     |
|              | substance listings:                                     |                     |
|              | Domestic Substances List (DSL)                          |                     |
| 9004-70-0    | Nitrocellulose, colloided, granular                     |                     |
|              | potassium chlorate                                      |                     |
| 57-50-1      | sucrose, pure   |                     |
| 598-62-9     | manganese carbonate                                     |                     |
| 7757-79-1    | potassium nitrate                                       |                     |
|              | magnesium oxide   |                     |
|              | diiron trioxide / iron (III) oxide                      |                     |
| 7440-50-8    | copper  |                     |
| 7440-32-6    | titanium  |                     |
|              | triiron tetraoxide                                      |                     |
| 7440-66-6    | zinc metal  |                     |
| 7440-21-3    | silicon   |                     |
| 7440-67-7    | zirconium powder (pyrophoric)                           |                     |
| 7429-90-5    | aluminium powder (pyrophoric)                           |                     |
| 7440-44-0    | carbon  |                     |
|              | Ingredient Disclosure list (limit 0.1%)                 |                     |
|              | manganese carbonate                                     |                     |
| 122-39-      | diphenylamine   |                     |
| 10294-40-    | B barium chromate                                       |                     |
| · Canadian   | Ingredient Disclosure list (limit 1%)                   |                     |
| 2698-41-1    | [(2-chlorophenyl)methylene]malononitrile                |                     |
|              | magnesium oxide   |                     |
| 1309-37-1    | diiron trioxide / iron (III) oxide                      |                     |
| 7440-50-8    | copper  |                     |
| 7429-90-5    | aluminium powder (pyrophoric)                           |                     |
|              |   | (Contd. on page 19  |

Printing date July 13, 2015 Reviewed on July 13, 2015

Trade name: Riot Control Continuous Discharge Grenade, CS

(Contd. of page 18)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision July 13, 2015 / -

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives, Division 1.1

Flam. Sol. 1: Flammable solids, Hazard Category 1

Flam. Sol. 2: Flammable solids, Hazard Category 2

Pyr. Sol. 1: Pyorphoric Solids, Hazard Category 1

Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2

Ox. Sol. 1: Oxidising Solids, Hazard Category 1

Ox. Sol. 2: Oxidising Solids, Hazard Category 2

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Acute Tox. 2: Acute toxicity, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 1A: Carcinogenicity, Hazard Category 1A

Carc. 1B: Carcinogenicity, Hazard Category 1B

Repr. 1A: Reproductive toxicity, Hazard Category 1A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

#### Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com