

TURTLE WAX, INC. 2250 W. Pinehurst Blvd., STE 150 Addison, IL 60101

SAFETY DATA SHEET

1. Product and Company Identification

1.1 Product Identifier

Product Name: Turtle Wax Color Back Finish Restorer

Product Code (SKU): T270R1 (50220)

1.2 Relevant Identified Uses Of The Substance

Product Use: Automotive Wax, Polish, Sealant & Glaze - All Other Forms

1.3 Details of the Supplier of the SDS

Company Name: Turtle Wax, Inc.

Street Address: 2250 W. Pinehurst Blvd., Suite 150

City, State, Zip Code: Addison, IL 60101

1.4 Emergency Telephone Numbers

Phone Number: 1(630)455-3700 Fax Number: 1(630)455-3868

Transportation: 1(800)424-9300 (CHEMTREC)
Medical Assistance: Call your local Poison Control Center

2. Hazard Identification:

2.1 Classification of the Substance or Mixture

Hazard Classification: not classified

2.2 Label Elements

Pictogram: not required

Signal Word: none
Hazard Statement: none
Precautionary Statement: none

2.3 Other Hazards

Description of additional HNOC: none

3. Information on Ingredients:

3.1 Substance not applicable

3.2 Mixture

Component	CAS Number	Concentration (wt%)
Water	7732-18-5	>70%
Petroleum Distillates Hydrotreated Light	64742-47-8	7–13%
Kaolin Clay	1332-58-7	8-12%
Polydimethyl Siloxanes	63148-62-9	3-8%
White Mineral Oil	8042-47-5	1–5%

4. First Aid Measures:

4.1 Description of First Aid Measures

Inhalation: Remove to fresh air and promote deep breathing. Get medical attention if effects persist.

Skin: In case of skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention.

Eyes: In case of eye contact, immediately flush eyes with plenty of water. Remove contact lenses if worn. If irritation persists, get medical attention

Ingestion: If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if effects persist.

4.2 Most important symptoms and effects – acute and chronic

Inhalation: May cause respiratory tract irritation.

Skin: May cause skin irritation. Symptoms may include drying, cracking, or mild

dermatitis.

Eyes: May cause temporary eye irritation. Symptoms may include redness,

discomfort, and excess tearing.

Ingestion: May be harmful is swallowed. May cause stomach distress, nausea and

vomiting.

4.3 Indication of any immediate medical attention and special treatment

Symptoms may not appear immediately. Seek medical attention if effects persist and you feel unwell.

5. Fire Fighting Measures:

5.1 Extinguishing media

Water spray, carbon dioxide, dry chemical, and alcohol foam

5.2 Special hazards arising from the substance or mixture

CO₂, CO, and hydrocarbons

5.3 Advice for Fire Fighters

Keep up wind of fire. Wear full firefighting turn out gear (full bunker gear) and respiratory protection (SCBA). See Section 8 for personal protection.

6. Accidental Release Measures:

6.1 Personal precautions, protective equipment, and emergency procedures

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 Methods and materials for containment and clean up

For containment: Contain and absorb spill with inert material. Place in suitable container for disposal.

For clean up: Take up material and place in a suitable container. Provide adequate ventilation. Spilled material may be slippery.

7. Handling and Storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not swallow. Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing before re-use.

7.2 Conditions for safe storage including incompatibilities

Keep out of reach of children. Keep container tightly closed. Store in a well ventilated place. Do not store above 49°C (120°F).

7.3 Specific end uses

Shelf Life: Shelf life is considered to be 7 – 10 years when properly stored and kept closed.

8. Exposure Control/Personal Protection:

8.1 Control parameters

Exposure Limits 8 hr TWA:	<u>(OSHA PEL)</u>	(ACGIH TWA)
Petroleum Distillates Hydrotreated Light	100 ppm	200 ppm
Kaolin Clay	15 mg/m³ (total dust)	2 mg/m ³
	5 mg/m³ (Respirable fraction)	
Polydimethyl Siloxanes	not applicable	not applicable
White Mineral Oil	not applicable	not applicable

8.2 Exposure controls

Use adequate ventilation to keep exposure below recommended limits. Ensure that eye wash station and safety shower are close to work station.

Hand Protection Equipment: Wear chemical resistant gloves and clothing to prevent skin contact.

Eye Protection Equipment: Wear safety glasses or splash goggles to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

Respiration/Ventilation Protection Requirements: Provide good ventilation.

Ingestion Protection Requirements: Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use.

9. Physical And Chemical Properties:

9.1 Information of basic chemical and physical properties

Physical Form: viscous liquid

Color: white

Odor: typical solvent

Odor Threshold: not available

pH: 8.75

Melting Point/Freeze Point: 0°C (32°F) – Based on Water **Initial Boiling Point:** 100°C (212°F) – Based on Water

Flash Point (Seta Closed Cup): >93°C (200°F)

Flammability Limits: Explosive Limits: Upper: not available Lower: not available

Evaporation Rate:not availableFlammability Solid/Gas:not applicableVapor Pressure:not availableVapor Density:not available

Specific Gravity: 1.042
Solubility in Water: dispersible
Auto Ignition Temperature: not available
Partition coefficient (n/octonol/water): not available
Viscosity: 12000 cP

9. 2 Other information

%NVM by Weight: 16.0% %VOC Content (California): 4.0%

10. Stability and Reactivity:

10.1 Reactivity

Does not react under normal conditions

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

Does not react under normal conditions

10.4 Conditions to avoid

Heat and incompatible materials

10.5 Incompatible materials

Strong oxidizers such as bleach and peroxides

10.6 Hazardous decomposition products

CO₂, CO and hydrocarbons

11. Toxicological Information:

11.1 Information on Toxicological Effects

Turtle Wax Color Back Finish Restorer

LD50 – Oral Rat >2000 mg/Kg

LD50 – Dermal Rat >2000 mg/Kg

LC50 – Inhalation Rat >20 mg/L (4 hr)

Petroleum Distillate Hydrotreated Light (64742-47-8)

LD50 – Oral Rat >5000 mg/Kg LD50 – Dermal Rat >2000 mg/Kg LC50 – Inhalation Rat 5.2 mg/L (4 hr) Skin corrosion/irritation
Serious eye damage/irritation
Respiratory or skin sensitization
Germ cell mutagenicity
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met

Specific target organs - single exposure

Based on available data, classification data are not met

Specific target organs - repeated exposure

Based on available data, classification data are not met Based on available data, classification data are not met

Symptoms/injuries after inhalation May cause respiratory tract irritation

Symptoms/injuries after skin contact May cause skin irritation. Symptoms may include drying,

cracking, or mild dermatitis

Symptoms/injuries after eye contact May cause temporary eye irritation. Symptoms may include

redness, discomfort, and excess tearing.

Symptoms/injuries after ingestion May be harmful is swallowed. May cause stomach distress,

nausea and vomiting.

12. Ecological Information:

Aspiration hazard

12.1 Toxicity

Not recommended for release into aquatic systems without treatment

12.2 Persistence and degradability

Not established

12.3 Bioaccumulative potential

Not established

12.4 Mobility in soil

Not established

12.5 Other adverse effects

None known

13. <u>Disposal Considerations</u>:

13.1 Waste treatment methods

RCRA Hazardous Waste: Not regulated as a hazardous waste

Waste Disposal Method: Dispose of in accordance with local, state and federal

regulations

Waste Disposal Vessel: Plastic or metal drums.

14. Transportation Information:

14.1 UN number

None - not regulated as a hazardous material

14.2 UN Proper shipping name

None

14.3 Transport Hazard class

Not applicable

14.4 Packaging group

Not applicable

14.5 Marine Pollutant

No

14.6 Transportation in Bulk

Not applicable

14.7 Special precautions

None

15. Regulatory Information:

15.1 US Federal Regulations

TSCA Status: All ingredients are commercially available and listed by the manufacturer under TSCA.

15.2 Foreign Regulations

Canadian Status: All materials contained in this product are listed on the Canadian Domestic Substance List (DSL). Consult Turtle Wax, Inc. regarding status of ingredients.

European Union: All materials contained in this product are listed on EINECS.

AICS: All materials are registered for AICS (Australia)

15.3 State Regulations

State Regulatory Information:

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements, contact the appropriate agency in your state.

California Prop 65:

NFPA Classification:

CAS Number	Concentration	State Code		
None				
15.4 HMIS & NFPA Classifications				
HMIS Classification:	Health Flammability Reactivity	1 1 0		

Health

Flammability

Reactivity

1

1

0

16. Other Information:

Reason For Issue Address Update

Prepared By Jean Mayszak

Preparer's Title Technical Compliance Manager, R&D

SDS Administrator Jean Mayszak - Technical Compliance Manager, R&D

Approval Date February 2, 2017

Supersedes Date May 19, 2015

Revision Number A-5

This information is, to the best of Turtle Wax, Inc.'s knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitableness and completeness of such information for their own particular use.