

Version 1.2	Revision Date 06/07/2018	Print Date 07/03/2018
SECTION 1. PRODUCT AND	COMPANY IDENTIFICATION	
Material name	: ZEP INSTANT HND SANITIZER I	NEW 1CS 24-4OZ
Material number	: 00000000000090812	

Manufacturer or supplier's details

Company	:	Zep Inc.
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137

Telephone : 404-352-1680

Emergency telephone numbers

For SDS Information	: C	ompliance Services 1-877-428-9937
For a Medical Emergency	: 8	77-541-2016 Toll Free - All Calls Recorded
For a Transportation	: C	HEMTREC: 800-424-9300 - All Calls Recorded.
Emergency	Ir	the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Hand Care

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	clear
Odour	alcohol-like

GHS Classification

Flammable liquids Eye irritation	: Category 3 : Category 2A
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	 H226 Flammable liquid and vapour. H319 Causes serious eye irritation.
Precautionary statements	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting



equipment. P242 Use only non-sparking tools P243 Take precautionary measur P264 Wash skin thoroughly after P280 Wear protective gloves/ pro protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN immediately all contaminated clot water/shower. P305 + P351 + P338 IF IN EYES for several minutes. Remove cont easy to do. Continue rinsing. P337 + P313 If eye irritation persi attention. P370 + P378 In case of fire: Use alcohol-resistant foam to extinguis Storage: P403 + P235 Store in a well-venti Disposal: P501 Dispose of contents/contain regulation.	es against static discharge. handling. tective clothing/ eye (or hair): Take off hing. Rinse skin with : Rinse cautiously with water cact lenses, if present and sts: Get medical advice/ dry sand, dry chemical or sh. lated place. Keep cool.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
ethanol	64-17-5	>= 70 - < 90
glycerol	56-81-5	>= 5 - < 10
propane-1,2-diol	57-55-6	>= 5 - < 10
2,2',2"-nitrilotriethanol	102-71-6	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	 Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. Get medical attention if symptoms occur.
If inhaled	 If unconscious, place in recovery position and seek medical advice. Consult a physician after significant exposure.
In case of skin contact	: This product is formulated for use on skin but should always be immediately washed off with plenty of water. Discontinue use if irritation and redness develop. If conditions persist for more than 72 hours, consult a physician.



Version 1.2	Revision Date 06/07/2018	Print Date 07/03/2018
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing If eye irritation persists, consult a Rinse immediately with plenty of	specialist.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to If symptoms persist, call a physic DO NOT induce vomiting unless physician or poison control cente Take victim immediately to hospit	ian. directed to do so by a r.
Most important symptoms and effects, both acute and delayed	 Effects are dependent on exposu contact time). Effects are immediate and delaye Symptoms may include irritation, Causes serious eye irritation. Review section 2 of SDS to see a 	ed. redness, pain, and rash.
Notes to physician	: Treat symptomatically. Symptom	ns may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke Nitrogen oxides (NOx)
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Standard procedure for chemical fires.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES



Version 1.2	Revision Date 06/07/2018	Print Date 07/03/2018
Personal precautions, protective equipment and emergency procedures	: Material can create slippery condit Use non-slip safety shoes in areas occur. Refer to protective measures lister	where spills or leaks can
Environmental precautions	: Prevent product from entering dra Prevent further leakage or spillage If the product contaminates rivers respective authorities.	e if safe to do so.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent mate acid binder, universal binder, sawe Keep in suitable, closed containers	dust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	 No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Keep away from oxidizing agents and strongly acid or alkaline materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm	OSHA P0



Version	1.2
101011	1.4

Revision Date 06/07/2018

Print Date 07/03/2018

		1,900 mg/m3	
	STEL		ACGIH
	PEL		CAL PEL
			-
56-81-5	TWA (mist,		OSHA Z-1
	respirable	Ŭ	
	fraction)		
	TWA (mist,	15 mg/m3	OSHA Z-1
		5	
	PEL (Mist -	10 mg/m3	CAL PEL
		Ū	
		5 mg/m3	CAL PEL
		- 5	
		10 ma/m3	OSHA P0
	,		
		5 ma/m3	OSHA P0
102-71-6	TWA	5 mg/m3	ACGIH
			CAL PEL
57-55-6			US WEEL
		-	ACGIH
04170			NIOSH REL
			NICOLLINE
	Τ\//Δ		OSHA Z-1
			0011721
	Τ\Λ/Δ		OSHA P0
	1 0 0 / 0		001///10
	STEL		ACGIH
			CAL PEL
56 01 F	TWA (mist,		
			$OSHA 7_1$
50-01-5		5 mg/m3	OSHA Z-1
50-61-5	respirable	5 mg/m3	OSHA Z-1
	respirable fraction)		
	respirable fraction) TWA (mist,	15 mg/m3	OSHA Z-1
	respirable fraction) TWA (mist, total dust)	15 mg/m3	OSHA Z-1
	respirable fraction) TWA (mist, total dust) PEL (Mist -		
	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction)	15 mg/m3 10 mg/m3	OSHA Z-1 CAL PEL
	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction) PEL (Mist -	15 mg/m3	OSHA Z-1
	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction) PEL (Mist - respirable	15 mg/m3 10 mg/m3	OSHA Z-1 CAL PEL
	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction) PEL (Mist - respirable fraction)	15 mg/m3 10 mg/m3 5 mg/m3	OSHA Z-1 CAL PEL CAL PEL
	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction) PEL (Mist - respirable fraction) TWA (Mist -	15 mg/m3 10 mg/m3	OSHA Z-1 CAL PEL
	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction) PEL (Mist - respirable fraction) TWA (Mist - total dust)	15 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3	OSHA Z-1 CAL PEL CAL PEL OSHA P0
	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction) PEL (Mist - respirable fraction) TWA (Mist - total dust) TWA (Mist -	15 mg/m3 10 mg/m3 5 mg/m3	OSHA Z-1 CAL PEL CAL PEL
	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction) PEL (Mist - respirable fraction) TWA (Mist - total dust) TWA (Mist - respirable	15 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3	OSHA Z-1 CAL PEL CAL PEL OSHA P0
	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction) PEL (Mist - respirable fraction) TWA (Mist - total dust) TWA (Mist - respirable fraction)	15 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3	OSHA Z-1 CAL PEL CAL PEL OSHA P0 OSHA P0
57-55-6	respirable fraction) TWA (mist, total dust) PEL (Mist - total fraction) PEL (Mist - respirable fraction) TWA (Mist - total dust) TWA (Mist - respirable	15 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3	OSHA Z-1 CAL PEL CAL PEL OSHA P0
		56-81-5TWA (mist, respirable fraction)TWA (mist, total dust)TWA (mist, total dust)PEL (Mist - total fraction)PEL (Mist - respirable fraction)PEL (Mist - total dust)TWA (Mist - respirable fraction)TWA (Mist - respirable fraction)TWA (Mist - respirable fraction)102-71-6TWA102-71-6TWA57-55-6TWA64-17-5TWATWATWATWATWATWATWAPELSTELPELSTELPELSTELPELSTELPELSTEL	PEL 1,000 ppm 1,900 mg/m3 56-81-5 TWA (mist, respirable fraction) 5 mg/m3 TWA (mist, respirable fraction) 15 mg/m3 PEL (Mist - total dust) 10 mg/m3 PEL (Mist - total fraction) 10 mg/m3 PEL (Mist - total fraction) 5 mg/m3 PEL (Mist - respirable fraction) 5 mg/m3 TWA (Mist - total dust) 10 mg/m3 TWA (Mist - respirable fraction) 5 mg/m3 TWA 10 mg/m3 TWA 1,000 ppm 1,900 mg/m3 TWA 1,000 ppm 1,900 mg/m3 TWA 1,000 ppm 1,900 mg/m3 TWA 1,000 ppm 1,900 mg/m3

Engineering measures

: effective ventilation in all processing areas

Personal protective equipment

Respiratory protection

: Use respiratory protection unless adequate local exhaust



Version 1.2	Revision Date 06/07/2018	Print Date 07/03/2018
	ventilation is provided or exposure that exposures are within recomm	
Hand protection Remarks	: No special protection is required.	
Eye protection	: Eye protection is not required while In the workplace, the use of safety avoid eye exposure during the har during spill clean-up.	glasses is recommended to
Skin and body protection	: No special protection is required.	
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at	the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	clear
Odour	:	alcohol-like
Odour Threshold	:	No data available
рН	:	7.5
Melting point/freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	23.33 °C
Evaporation rate		No data available
Evaporation rate	•	
Upper explosion limit	:	19 %(V)
Lower explosion limit	:	3.3 %(V)
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	No data available



ersion 1.2

Revision Date 06/07/2018

Print Date 07/03/2018

64-17-5

Viscosity

Viscosity, kinematic

: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	 Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	Confirmed animal carcinogen with unknown relevance to humans

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

ethanol

by NTP.

NTP

Acute toxicity

Product:



Version 1.2	Revision Date 06/07/2018	Print Date 07/03/2018
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
Components:		
ethanol: Acute oral toxicity	: LD50 Oral Rat: 7,060 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 124.7 mg/l Exposure time: 4 h Test atmosphere: vapour	
2,2',2''-nitrilotriethanol: Acute oral toxicity	: LD50 Rat: 6,400 mg/kg	
Acute dermal toxicity	: LD50 Rabbit: > 2,000 mg/kg	
Skin corrosion/irritation		
Product:		
Result: No skin irritation		
Serious eye damage/eye irritation	ı	
Product:		
Remarks: Irritating to eyes.		
Respiratory or skin sensitisation		
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		
Aspiration toxicity		
No data available		
Further information		
Product:		



Version 1.2

Revision Date 06/07/2018

Print Date 07/03/2018

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:

Partition coefficient: n- octanol/water <u>Components:</u> ethanol :	: Remarks: No data available
Partition coefficient: n- octanol/water glycerol :	: Remarks: No data available
Partition coefficient: n- octanol/water propane-1,2-diol :	: log Pow: -1.76
Partition coefficient: n- octanol/water 2,2',2''-nitrilotriethanol :	: log Pow: -1.07
Partition coefficient: n- octanol/water	: Pow: 1
Mobility in soil	
No data available	
Other adverse effects	
No data available <u>Product:</u>	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: No data available

SECTION 13. DISPOSAL CONSIDERATIONS



Version 1.2	Revision Date 06/07/2018	Print Date 07/03/2018
Disposal methods		
Waste from residues	: Do not dispose of waste into sewe Do not contaminate ponds, watery chemical or used container. Dispose of in accordance with loc	vays or ditches with
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch 	on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1993, FLAMMABLE LIQUID, N.O.S., (ETHANOL), 3, III - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1993, Flammable liquid, n.o.s., (ETHANOL), 3, III - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1993, Flammable liquid, n.o.s., (ETHANOL), 3, III - Limited quantity

Transportation Regulation: TDG (Canada): UN1993, FLAMMABLE LIQUID, N.O.S., (ETHANOL), 3, III - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.



Version 1.2	Revision Date 06/07/2018	Print Date 07/03/2018
SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids Serious eye damage or eye irritatior	
SARA 302	: No chemicals in this material are su requirements of SARA Title III, Sect	, ,
SARA 313	 This material does not contain any of known CAS numbers that exceed th reporting levels established by SAR 	he threshold (De Minimis)
California Prop. 65		
	This product does not contain any California to cause cancer, birth d reproductive harm.	

The components of this product are reported in the following inventories:


DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION



OSHA - GHS Label Information:



. <i>.</i> .		
Version	1.2	

Revision Date 06/07/2018

Print Date 07/03/2018

Hazard pictograms

Signal word Hazard statements Precautionary statements Warning:

Flammable liquid and vapour. Causes serious eye irritation.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.2
Revision Date:	06/07/2018
Print Date:	07/03/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.