

ZEP 45 DUAL FORCE AERO DZ

Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP 45 DUAL FORCE AERO DZ

Material number : 0000000000374301

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : 404-352-1680

Emergency telephone numbers

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas
Colour	amber
Odour	characteristic

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Compressed gas

GHS label elements

Hazard pictograms :





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

Precautionary statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

use.



Print Date 03/16/2018 Version 2.0 Revision Date 02/23/2018

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F. P403 Store in a well-ventilated place.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 50 - < 70
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 10 - < 20
Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate	88917-22-0	>= 1 - < 5
carbon dioxide	124-38-9	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.

If swallowed : Keep respiratory tract clear.

> Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a

physician or poison control center. If symptoms persist, call a physician.

Most important symptoms

and effects, both acute and

delayed

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation.

: Treat symptomatically. Symptoms may be delayed. Notes to physician



Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the



Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

egulations.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

No smoking.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
		PEL	5,000 ppm	CAL PEL



Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

	9,000 mg/m3	
STEL	30,000 ppm	CAL PEL
	54,000 mg/m3	

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Colour : amber

Odour : characteristic
Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : Not applicable
Boiling point : Not applicable

Flash point :

Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available



ZEP 45 DUAL FORCE AERO DZ

Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

Density : 0.8715 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : > 20 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.



ZEP 45 DUAL FORCE AERO DZ

Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute dermal toxicity : Acute toxicity estimate : 3,754 mg/kg

Method: Calculation method

Components:

Distillates (petroleum), hydrotreated light:

: LD50 Rat: > 5,000 mg/kg Acute oral toxicity

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

: LD50 Rat: > 2,000 mg/kg Acute dermal toxicity

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

: LC50 Rat: > 5 mg/l Acute inhalation toxicity

Exposure time: 4 h

: LD50 Rabbit: > 5,000 mg/kg Acute dermal toxicity

Skin corrosion/irritation

Product:

Remarks: May cause skin and eye irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available



ZEP 45 DUAL FORCE AERO DZ

Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available



Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

Components:

Distillates (petroleum), hydrotreated light :

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.



Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
naphthalene	91-20-3	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Gases under pressure

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including naphthalene, which is/are known to the State of California to cause cancer. For more information go to

www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)


SECTION 16. OTHER INFORMATION



Version 2.0 Revision Date 02/23/2018 Print Date 03/16/2018

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms





Signal word Hazard statements Precautionary statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Prevention: Keep aw ay from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place.

Version:	2.0
Revision Date:	02/23/2018
Print Date:	03/16/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.