DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Version 3.0	Revision Date: 09/14/2017		OS Number: 97483-00010	Date of last issue: 03/14/2017 Date of first issue: 02/09/2015				
SECTION 1. IDENTIFICATION								
Product name		:	DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY					
Product code		:	0000000002468476					
Manuf	Manufacturer or supplier's details							
Compa	any name of supplier	:	Dow Corning Cor	poration				
Addres	SS	:	South Saginaw R Midland Michigan					
Teleph	one	:	(989) 496-6000					
Emerg	ency telephone	:	24 Hour Emerger CHEMTREC : (80	ncy Telephone : (989) 496-5900 00) 424-9300				
Recon	nmended use of the c	hen	nical and restriction	ons on use				
Recom	nmended use	:	Adhesive, binding	agents				

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

:

Not a hazardous substance or mixture.

GHS label elements

П

Not a hazardous substance or mixture.

Precautionary Statements

Prevention:

P271 Use only outdoors or in a well-ventilated area.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Sealant

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Calcium carbonate treated with stearic acid	Not Assigned	>= 41 - <= 43
Titanium dioxide	13463-67-7	>= 0.46 - <= 0.62

SECTION 4. FIRST AID MEASURES

DOW CORNING

DOW CORNING

DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Versi 3.0	ion	Revision Date: 09/14/2017)S Number: 97483-00010	Date of last issue: 03/14/2017 Date of first issue: 02/09/2015
	lf inhale	ed	:	If inhaled, remove Get medical atten	e to fresh air. tion if symptoms occur.
	In case	of skin contact	:		and soap as a precaution. tion if symptoms occur.
	In case	of eye contact	:		rater as a precaution. tion if irritation develops and persists.
	If swall	owed	:	Get medical atten	NOT induce vomiting. tion if symptoms occur. oughly with water.
		nportant symptoms ects, both acute and d	:	None known.	
	Protect	ion of first-aiders	:	No special precau	utions are necessary for first aid responders.
11	Notes t	o physician	:	Treat symptomati	cally and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Carbon oxides Silicon oxides Formaldehyde Metal oxides
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Version 3.0	Revision Date: 09/14/2017		97483-00010	Date of last issue: 03/14/2017 Date of first issue: 02/09/2015
tive e	nal precautions, protec- quipment and emer- v procedures	:	Follow safe handli equipment recom	ing advice and personal protective mendations.
Envir	onmental precautions	:	Prevent further lea Retain and dispos	e environment must be avoided. akage or spillage if safe to do so. se of contaminated wash water. should be advised if significant spillages ed.
	ods and materials for inment and cleaning up	:	For large spills, pr containment to ke can be pumped, s container. Clean up remainir absorbent. Local or national r disposal of this ma employed in the c determine which r Sections 13 and 1	absorbent material. Tovide diking or other appropriate ep material from spreading. If diked material atore recovered material in appropriate ing materials from spill with suitable regulations may apply to releases and aterial, as well as those materials and items leanup of releases. You will need to egulations are applicable. 5 of this SDS provide information regarding tional requirements.

DOW CORNING

SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	:	Keep in properly labeled containers. Store in accordance with the particular national regulations.
Materials to avoid	:	Do not store with the following product types: Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Calcium carbonate treated with	Not Assigned	TWA (Res-	5 mg/m³	NIOSH REL

I

I

DOW CORNING

DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

ersion 0	Revision Date: 09/14/2017		OS Number: 97483-00010		st issue: 03/14/2017 st issue: 02/09/2015		
steari	ic acid			pirable)	(Calcium car- bonate)		
				TWA (total)	10 mg/m ³ (Calcium car- bonate)	NIOSH REL	
Titani	ium dioxide		13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1	
				TWA	10 mg/m ³ (Titanium dioxide)	ACGIH	
	e substance(s) are in dust inhalation hazaro		ably bound in	the product a	nd therefore do not	contribute	
	Calcium carbo	onate	treated with ste	earic acid			
	Titanium dioxi	ide					
Engineering measures :			Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.				
Perso	onal protective equip	ment					
Respiratory protection :			No personal respiratory protective equipment normally required.				
Hand	protection						
Re	emarks	:			ntact use protective on at the end of work		
Eye p	protection	:	Wear the follo Safety glasse		protective equipment:		
Skin a	and body protection	:	Skin should b	e washed after	contact.		
Hygie	ene measures	:	located close When using d Wash contam These precau	to the working p lo not eat, drink inated clothing tions are for roo perature or aero	or smoke.	ling. Use at	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Color	:	gray
Odor	:	alcohol-like

DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Version 3.0	Revision Date: 09/14/2017		S Number: 97483-00010	Date of last issue: 03/14/2017 Date of first issue: 02/09/2015
Odor	Threshold		No data available	
	Threshold	•		÷
pН		•	Not applicable	
Melti	ng point/freezing point	:	No data available	9
Initia range	l boiling point and boiling e	:	Not applicable	
Flash	n point	:	Not applicable	
Evap	oration rate	:	Not applicable	
Flam	mability (solid, gas)	:	Not classified as	a flammability hazard
Self	ignition	:		r mixture is not classified as pyrophoric. The ture is not classified as self heating.
	er explosion limit / Upper nability limit	:	No data available	9
	er explosion limit / Lower nability limit	:	No data available	e
Vapo	or pressure	:	Not applicable	
Relat	tive vapor density	:	No data available	e
Relat	tive density	:	1.1	
	bility(ies) /ater solubility	:	No data available	e
	tion coefficient: n- nol/water	:	No data available	9
Autoi	gnition temperature	:	No data available	9
Decc	mposition temperature	:	No data available	e
Visco Vi	osity iscosity, dynamic	:	Not applicable	
Explo	osive properties	:	Not explosive	
Oxidi	zing properties	:	The substance o	r mixture is not classified as oxidizing.
Mole	cular weight	:	No data available	9
Partie	cle size	:	No data available	5

SECTION 10. STABILITY AND REACTIVITY

DOW CORNING

DOW CORNING

DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Vers 3.0	ion	Revision Date: 09/14/2017		S Number: 97483-00010	Date of last issue: 03/14/2017 Date of first issue: 02/09/2015		
	Reactiv	vity	:	Not classified as	a reactivity hazard.		
	Chemi	cal stability	:	Stable under normal conditions.			
	Possibility of hazardous reac- tions		:	Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Methyl alcohol is formed upon contact with water or humid a Hazardous decomposition products will be formed at elevate temperatures.			
	Conditi	ons to avoid	:	None known.			
	Incomp	oatible materials	:	Oxidizing agents			
		lous decomposition p al decomposition		ucts Formaldehyde			

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:

Titanium dioxide:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 6.82 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhala- tion toxicity

Skin corrosion/irritation

Not classified based on available information.

Ingredients:

Titanium dioxide:

Species: Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.



DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2017
3.0	09/14/2017	1197483-00010	Date of first issue: 02/09/2015

Ingredients:

Titanium dioxide:

Species: Rabbit Result: No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:

Titanium dioxide:

Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Titanium dioxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: In vivo micronucleus test Species: Mouse Result: negative

Carcinogenicity

Not classified based on available information.

Ingredients:

Titanium dioxide:

Species: Rat Application Route: inhalation (dust/mist/fume) Exposure time: 24 Months Method: OECD Test Guideline 453 Result: positive Remarks: The mechanism or mode of action may not be relevant in humans. These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assess- :	:	Limited evidence of carcinogenicity in inhalation studies with
ment		animals.

DOW CORNING

DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Version 3.0	Revision Date: 09/14/2017	SDS Number: 1197483-00010	Date of last issue: 03/14/2017 Date of first issue: 02/09/2015
IARC		Group 2B: Possibly	carcinogenic to humans
		Titanium dioxide	13463-67-7
OSHA		•	s product present at levels greater than or OSHA's list of regulated carcinogens.
NTP			product present at levels greater than or ntified as a known or anticipated carcinogen

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

Titanium dioxide:

Species: Rat NOAEL: 24,000 mg/kg Application Route: Ingestion Exposure time: 28 Days

Species: Rat NOAEL: 10 mg/m³ Application Route: inhalation (dust/mist/fume) Exposure time: 2 y Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Titanium dioxide:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h

DOW CORNING

DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Version 3.0	Revision Date: 09/14/2017		DS Number: 97483-00010	Date of last issue: 03/14/2017 Date of first issue: 02/09/2015
Toxicit	y to algae	:	EC50 (Skeletone Exposure time: 7	ema costatum (marine diatom)): > 10,000 mg/l 72 h
Toxicit	y to microorganisms	:	Exposure time: 3	
Persis	stence and degradabi	lity		
No dat	a available			
Bioac	cumulative potential			
No dat	a available			
Mobili	ty in soil			
No dat	a available			
Other	adverse effects			
N 1 1 1	a available			

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and Recovery Act (RCRA)	:	This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.
Waste from residues	:	Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2017
3.0	09/14/2017	1197483-00010	Date of first issue: 02/09/2015

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ	Calculated product RQ
_		(lbs)	(lbs)
Methanol	67-56-1	5000	*
Butan-1-ol	71-36-3	5000	*
Ethylenediamine	107-15-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethylenediamine	107-15-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
----------------------	---	-----------------

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Polysiloxane	Trade secret
Calcium carbonate treated with stearic acid	Not Assigned
Dimethyl Siloxane, Dimethylvinylsiloxy-terminated	68083-19-2
Methanol	67-56-1

California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Permissible Exposure Limits for Chemical Contaminants

Calcium carbonate treated with stearic acid

Not Assigned

DOW CORNING

The ingredients of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.

DOW CORNING

0

1


0

DOW CORNING(R) 832 MULTI-SURFACE **ADHESIVE SEALANT, GREY**

Version 3.0	Revision Date: 09/14/2017		DS Number: 97483-00010	Date of last issue: 03/14/2017 Date of first issue: 02/09/2015	
AICS		:	All ingredients list	ed or exempt.	
IECSC		:	All ingredients listed or exempt.		
TSCA		:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.		
KECI		:	All ingredients list	ed, exempt or notified.	
DSL		:	1999 and NSNR	tances in this product comply with the CEPA and are on or exempt from listing on the tic Substances List (DSL).	
TCSI		:	All ingredients list	ed or exempt.	

SECTION 16. OTHER INFORMATION





Full text of other abbreviations

ACGIH NIOSH REL OSHA Z-1	:	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA NIOSH REL / TWA		8-hour, time-weighted average Time-weighted average concentration for up to a 10-hour
OSHA Z-1 / TWA	:	workday during a 40-hour workweek 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Sub-

DOW CORNING

DOW CORNING(R) 832 MULTI-SURFACE ADHESIVE SEALANT, GREY

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2017
3.0	09/14/2017	1197483-00010	Date of first issue: 02/09/2015

stances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Revision Date : 09/14/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8