

<b>ASHLAND®</b>		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Pyroil™ POWER STEERING FLUID

### Recommended use of the chemical and restrictions on use

<b>Details of the supplier of the safety data sheet</b> Ashland P.O. Box 2219 Columbus, OH 43216 United States of America  EHS Customer Requests@ashland.com	<b>Emergency telephone number</b> 1-800-ASHLAND (1-800-274-5263)  <b>Regulatory Information Number</b> 1-800-325-3751  <b>Product Information</b> 614-790-3333
--	---

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

### Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	12.41

<b>ASHLAND</b>		Page: 2
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

---

#### SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)
- Notes to physician : No hazards which require special first aid measures.

---

#### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)

<b>ASHLAND</b>		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

Dry chemical

- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.  
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

---

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.

<b>ASHLAND®</b>		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

Materials to avoid : No materials to be especially mentioned.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:  
Safety shoes  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : No data available

Odour Threshold : No data available

<b>ASHLAND®</b>		Page: 5
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 424.99 °F / 218.33 °C  
(1,013.333333 hPa)  
Calculated Phase Transition Liquid/Gas

Flash point : 347.00 °F / 175.00 °C  
Method: Open Cup

Evaporation rate : > 1  
Ethyl Ether

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0.00004 hPa  
Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.87 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 42 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous : Product will not undergo hazardous polymerization.

<b>ASHLAND®</b>		Page: 6
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

reactions

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide  
Hydrocarbons

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

### **Acute toxicity**

Not classified based on available information.

### **Skin corrosion/irritation**

Not classified based on available information.

#### **Product:**

Result: Repeated exposure may cause skin dryness or cracking.

### **Components:**

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Product:**

Remarks: Unlikely to cause eye irritation or injury.

### **Components:**

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to eyes

### **Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

Not classified based on available information.

### **STOT - repeated exposure**

Not classified based on available information.

<b>ASHLAND</b>		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : The product should not be allowed to enter drains, water

<b>ASHLAND®</b>		Page: 8
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

courses or the soil.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Empty containers should be taken to an approved waste handling site for recycling or disposal.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods

**U.S. DOT - RAIL**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TRANSPORT CANADA - ROAD**

Not dangerous goods

**TRANSPORT CANADA - RAIL**

Not dangerous goods

**TRANSPORT CANADA - INLAND WATERWAYS**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**



<b>ASHLAND®</b>		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

Not dangerous goods

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

Not dangerous goods

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313 Component(s)** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Pennsylvania Right To Know**

HYDROTREATED LIGHT PARAFFINIC 64742-55-8 10.00 - 20.00 %  
DISTILLATE

**New Jersey Right To Know**

HYDROTREATED LIGHT PARAFFINIC 64742-55-8 10.00 - 20.00 %  
DISTILLATE

DISTILLATES (PETROLEUM), 64742-53-6 0.10 - 1.00 %  
HYDROTREATED LIGHT NAPHTHENIC

**California Prop 65** Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

NZIOC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

<b>ASHLAND®</b>		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

KECL : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 05/22/2015

<p><b>NFPA:</b></p> <p style="text-align: center;">Flammability</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">Health 1</div> <div style="text-align: center;"> </div> <div style="text-align: center;">Instability 0</div> </div> <p style="text-align: center;">Special hazard.</p>	<p><b>HMIS III:</b></p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>1</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>1</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**Full text of H-Statements referred to under sections 2 and 3.**

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet

Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

<b>ASHLAND®</b>		Page: 11
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/22/2015
		SDS Number: R0177840
Pyroil™ POWER STEERING FLUID		Version: 1.0
PYPSF32		

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System