

MATERIAL SAFETY DATA SHEET

Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

PENETONE 19

Page: 1 of 4 Date Prepared: September 20, 2011 MSDS No.: 1862-109N

SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME: PENETONE 19 GENERAL USE: Cleaning, degreasing PRODUCT DESCRIPTION: Solvent emulsion GENERIC INGREDIENTS: Water, surfactants, aromatic hydrocarbons and other solvents, soap

EMERGENCY TELEPHONE NUMBERS: PENETONE 201-567-3000 CHEMTREC 800-424-9300

SECTION 2 HAZARDOUS INGREDIENT SECTION

This product is hazardous as defined in 29 CFR1910.1200.

OSHA HAZARD: Combustible

OSHA HAZARDOUS INGREDIENTS

		EXPOSURE LIMITS 8 hrs. TWA (ppm)		
	CAS#	OSHA PEL	ACGIH TLV	Supplier
Aromatic Hydrocarbon	64742-94-5			100
Diethanolamine	111-42-2	3	3	
Hexylene Glycol	107-41-5	25	25	
			Ceiling	

SECTION 3 HEALTH INFORMATION & PROTECTION

EMERGENCY OVERVIEW:

Clear, straw-colored liquid with mild solvent odor. Combustible. Can be irritating to skin, eyes, and respiratory tract.

POTENTIAL HEALTH EFFECTS:

May cause irritation to eyes on prolonged contact. High vapor concentrations may be irritating.

SKIN CONTACT:

Frequent or prolonged contact may irritate or dry the skin or cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION:

High vapor/aerosol concentrations may be irritating to the respiratory tract and may cause headaches, dizziness,

anesthesia, drowsiness, unconsciousness, and other central nervous system effects.

INGESTION:

Small amounts of this liquid may be drawn into the lungs by either swallowing or vomiting. This may cause severe and delayed health effects such as inflammation of the lungs and infection of the bronchi. Ingestion may cause irritation to the digestive tract.

EYE CONTACT:

CHRONIC:

An increased incidence of liver tumors in both sexes of mice and an increased incidence of kidney tumors in male mice dermally exposed for their lifetime to diethanolamine was observed. The significance of these findings and their relevance to humans are not clear as diethanolamine was not genotoxic (neither mutagenic nor clastogenic), and did not induce tumors in rats or transgenic mice similarly tested.

FIRST AID MEASURES:

EYE CONTACT:

Flush eyes with large amounts of water. See physician immediately.

SKIN CONTACT:

Flush skin with large amounts of water. Remove contaminated clothing and launder before reuse. If skin irritation develops or persists, consult physician.

INHALATION:

Remove person to fresh air. Administer oxygen or artificial respiration as needed. Call a physician immediately.

INGESTION:

If swallowed, give plenty of milk or water. DO NOT INDUCE VOMITING. Use stomach pump. Call a physician immediately.

WORKPLACE EXPOSURE CONTROLS:

PERSONAL PROTECTION:

Safety glasses are recommended for all workplace conditions. Solvent resistant gloves should be used. Other protective gear, including splash proof goggles or face shield, rubber boots, apron, gauntlets, or rain gear should be worn depending on how the product is used.

VENTILATION:

None needed under normal use conditions. For enclosed areas, or where large amounts of the product are being used, the use of fans or other mechanical ventilation is recommended. An organic vapor mask should be used if the TLV is exceeded and a particle mask if the product is sprayed. DO NOT MIST THIS PRODUCT. Use coarse spray only.

SECTION 4 FIRE & EXPLOSION HAZARDS

FLASH POINT: 155° F (PMCC), None (COC) FLAMMABLE LIMITS: Not determined AUTOIGNITION TEMPERATURE: Not determined

GENERAL HAZARD:

Combustible liquid. Can form combustible mixtures at or above the flash point. Containers can rupture and explode under fire conditions due to pressure and vapor buildup.

FIRE FIGHTING:

Either allow fire to burn out under controlled conditions or extinguish with water, foam, or dry chemical. Cool exposed containers with water spray.

HAZARDOUS COMBUSTION PRODUCTS:

Smoke, fumes, and oxides of carbon and nitrogen.

SECTION 5 SPILL CONTROL MEASURES

LAND SPILL:

Eliminate sources of ignition. For small spills, use absorbent material such as towels or absorbent powders. Put all material into proper waste disposal container with lid tightly covered. **Solvent soaked materials may spontaneously combust.** For larger spills, dike spill, recover free liquid, and use absorbent material to dry area. Rinse area with water. Put all material into appropriate waste containers.

Page: 3 of 4 Date Prepared: September 20, 2011 MSDS No.: 1862-109N

WATER SPILL:

Remove product from water surface by skimming or with suitable absorbents. This product contains surfactants which will cause it to disperse in water. Localized high concentrations of this product may cause fish kills, but no persistent or long term effects will result. Check with local environmental regulatory agencies for reporting requirements.

SECTION 6 HANDLING & STORAGE

STORAGE TEMPERATURE, °F: ambient. DO NOT STORE ABOVE 120 Deg. F. KEEP FROM FREEZING.

GENERAL: Keep away from heat sources, open flames, and other ignition sources. Do not store near strong oxidants.

SECTION 7 TYPICAL PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT, °F: Approximately 212 **EVAPORATION RATE, Acetone = 1:** Less than 0.1 SOLUBILITY IN WATER: Emulsifies SPECIFIC GRAVITY at 75°F: 0.99 **ODOR AND APPEARANCE:** Clear, straw-colored liquid with mild solvent odor.

VAPOR PRESSURE, mm Hg at 20°C: Equal to water VAPOR DENSITY (Air = 1): Equal to water WT% ORGANIC VOLATILES: About 30 pH: 10.0

SECTION 8 REACTIVITY DATA

GENERAL:

This product is stable and hazardous polymerization will not occur.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Strong oxidizing agents.

SECTION 9 REGULATORY INFORMATION

DEPARTMENT OF TRANSPORTATION (DOT):

PROPER SHIPPING NAME:

NONHAZARDOUS (nonregulated) MATERIAL HAZARD CLASS: none **IDENTIFICATION NUMBER:** none PACKING GROUP: none LABEL: not required

FLASH POINT: 155° F (PMCC), None (COC) **pH:** 10.0

TSCA: The ingredients in this product are listed on the TSCA inventory.

CERCLA:

This product contains the following reportable CERCLA material.

Diethanolamine CAS# 111-42-2 RQ = 100 lbs

Releases exceeding the RQ must be reported to the National Response Center, 800-424-8802, and may be subject to state and local reporting.

RCRA HAZARD CLASS:

nonhazardous waste

SARA TITLE III:

311/312 HAZARD CATEGORIES: Acute health 313 REPORTABLE INGREDIENTS: Diethanolamine CAS# 111-42-2 <3 wt%

NEW JERSEY RIGHT-TO-KNOW INFORMATION:

This product contains water (CAS# 7732-18-5), alkylphenol ethoxylate (CAS# 9016-45-9), aromatic hydrocarbon (CAS# 64742-94-5), hexylene glycol (CAS# 107-41-5), diethanolamine tallate (CAS# 68002-82-4), and diethanolamine (CAS# 111-42-2).

CALIFORNIA PROPOSITION 65 INFORMATION:

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

SCAQMD INFORMATION:

Is there a photochemically reactive material present? Yes What is the % by volume of photochemically reactive material? 15-20 What is the VOC content? 280 g/L What is the vapor pressure of VOC's? 0.03 mm Hg @ 20° C

SECTION 10 NOTES

HAZARD RATING SYSTEMS:

	HMIS	NFPA
HEALTH	1	1
FLAMMABILITY	2	2
REACTIVITY	0	0

KEY 4 = Severe 3 = Serious 2 = Moderate 1 = Slight

0 = Minimal

REVISION SUMMARY:

Change in Section 7

SUPERSEDES ISSUE DATE:

June 24, 2004

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.