MATERIAL SAFET	Y DATA SHEET Page 1	
24-hour Emergency Phone: (800)255-3924 PRODUCT CODE: 5686	Fage 1	
PRODUCT NAME: RUSTAME (A/11) PRODUCT CODE: 5686	HMIS CODES: H C F R P 1 3 0 B	
WHMIS CLASS: A & B,5 & D,2,B		
======================================		
MANUFACTURER'S NAME:ATCO InternationalADDRESS: 2136 Kingston CourMarietta, GA 3006		
INFORMATION PHONE : (770)424-7550	DATE PRINTED: 05/09/2007	
PREPARED BY: MAURICIO A. AMAYA, DIRECTOR OF TECHNICAL SERVICES REVISION DATE: 05/09/2007		
========= SECTION II - HAZARDOUS IN	GREDIENTS/SARA III INFORMATION =========	
REPORTABLE COMPONENTS	WEIGHT	
ANHYDROUS ALCOHOL	<u>CAS NUMBER PEL TLV PERCENT</u> 64-17-5 1000ppm 1000ppm 40-60%%	
LPG PROPELLANT	68476-85-7 1000ppm 1000ppm 20-40%	
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2 100ppm 100ppm 1-5%	
TANNIC ACID	1401-55-4 ND ND 1-5%	
======================================		
VAPOR DENSITY: ND	SPECIFIC GRAVITY (H2O=1): 0.895 EVAPORATION RATE: ND MATERIAL V.O.C.: Approx. 75% E pH (Concentrate): NA pH (Diluted): NA	
SECTION IV - FIRE AND EXPLOSION HAZARD DATA		
OSHA FLAMMABILITY CLASSIFICATION: EXTREMELY FLAMMABLE AEROSOL FLASH POINT: (Conc. Only) 42.8 F METHOD USED: TOC FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND UPPER: ND		
EXTINGUISHING MEDIA: Dry chemicals, Foam, or Carbon Dioxide.		

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to cool closed containers in order to prevent pressure build up which may result in containers rupturing. Use self contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to temperatures above 120 deg.F may cause bursting.

MATERIAL SAFETY DATA SHEET

24-hour Emergency Phone: (800)255-3924 **PRODUCT CODE:** 5686

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and burning may produce carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

 PRIMARY ROUTES OF ENTRY:
 Inhalation _X
 Eye Contact _X

 Skin Contact _X
 Ingestion _____

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to upper respiratory tract, dizziness, nausea and other central nervous system effects.

EYE CONTACT: May cause eye irritation but does not injure eye tissue.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORBTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of product into lungs can cause chemical pneumonitis.

CHRONIC EFFECTS OF OVEREXPOSURE: Chronic effects and medical conditions aggravated by overexposure to this product have not been established. Unnecessary exposure to this product or any chemical should be avoided.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If breathing has stopped give artificial respiration. Get IMMEDIATE MEDICAL ATTENTION

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Wash exposed area thoroughly with soap and water. Consult a physician if irritation develops.

Page 2

24-hour Emergency Phone: (800)255-3924 **PRODUCT CODE:** 5686

INGESTION: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a dry, cool place away from heat or open flame. Do not store at temperatures above 120 F.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

RESPIRATORY PROTECTION: Not normally required if good ventilation is maintained. Avoid breathing vapors or mist. VENTILATION: Local mechanical exhaust to provide normal ventilation. PROTECTIVE GLOVES: For prolonged contact wear impervious gloves. EYE PROTECTION: Safety eye protection to protect against splash of liquids and also aerosol size particles is recommended. OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required. WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard Pressure Hazard X

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

DOT SHIPPING NAME: ORM-D Consumer Commodity DOT HAZARD CLASS: Not Applicable UN NUMBER: Not Applicable DOT PACKING GROUP: Not Applicable SPECIAL SHIPPING INFORMATION: Regulated only when offered for transportation by aircraft.

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.