

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP DRY GRAPHITE AERO DZ

Material number : 000000000000016401

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.

In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	dark grey
Odour	solvent-like

GHS Classification

Flammable aerosols : Category 2
 Gases under pressure : Liquefied gas
 Skin irritation : Category 2
 Eye irritation : Category 2A
 Carcinogenicity : Category 1B
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :    

Signal word : Danger

Hazard statements : H223 Flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

H350 May cause cancer.

Precautionary statements

: Prevention:

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
trichloroethylene	79-01-6	>= 50 - < 70
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 10 - < 20
propan-2-ol	67-63-0	>= 5 - < 10
graphite	7782-42-5	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
If on clothes, remove clothes.
In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

In case of eye contact : Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.

Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include blistering, irritation, burns, and pain.
Chronic effects are delayed and symptoms may not be observed during an exposure.
Effects are dependent on exposure (dose, concentration, contact time).
Causes serious eye damage.
Suspected of causing cancer.
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Smoke Chlorine compounds
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Sweep up or vacuum up spillage and collect in suitable container for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

red-hot objects.
 No smoking.
 Keep in a dry, cool and well-ventilated place.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
trichloroethylene	79-01-6	TWA	10 ppm	ACGIH
		STEL	25 ppm	ACGIH
		TWA	100 ppm	OSHA Z-2
		CEIL	200 ppm	OSHA Z-2
		Peak	300 ppm	OSHA Z-2
		TWA	50 ppm 270 mg/m ³	OSHA P0
		STEL	200 ppm 1,080 mg/m ³	OSHA P0
		STEL	100 ppm 537 mg/m ³	CAL PEL
		C	300 ppm	CAL PEL
		PEL	25 ppm 135 mg/m ³	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m ³	OSHA P0
butane	106-97-8	PEL	1,000 ppm 1,800 mg/m ³	CAL PEL
		TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		TWA	800 ppm 1,900 mg/m ³	OSHA P0
propan-2-ol	67-63-0	PEL	800 ppm 1,900 mg/m ³	CAL PEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1
		TWA	400 ppm	OSHA P0

SAFETY DATA SHEET**ZepInc****ZEP DRY GRAPHITE AERO DZ**

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

			980 mg/m ³	
		STEL	500 ppm 1,225 mg/m ³	OSHA P0
		PEL	400 ppm 980 mg/m ³	CAL PEL
		STEL	500 ppm 1,225 mg/m ³	CAL PEL
graphite	7782-42-5	TWA (Respirable)	2.5 mg/m ³	NIOSH REL
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
TRICHLOROETHENE	79-01-6	Trichloroacetic acid	Urine	End of shift at end of workweek	15 mg/l	ACGIH BEI
TRICHLOROETHENE		Trichloroethanol	In blood	End of shift at end of workweek	0.5 mg/l	ACGIH BEI
TRICHLOROETHENE		Trichloroethylene	In end-exhaled air	End of shift at end of workweek		ACGIH BEI
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

: Protective gloves

Material : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas
Colour : dark grey
Odour : solvent-like
Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : not determined
Boiling point : 82.2 - 87.8 °C
Flash point :
Not applicable
Evaporation rate : > 1
n-Butyl Acetate = 1.0
Flammability (solid, gas) : Flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Density : 1.32 g/cm³
Solubility(ies)
Water solubility : insoluble
Solubility in other solvents : not determined

Partition coefficient: n-octanol/water : No data available
Auto-ignition temperature : not determined
Thermal decomposition : No data available

Viscosity
Viscosity, kinematic : No data available
Heat of combustion : > 20 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Phosgene Hydrogen chloride gas Chlorine Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include blistering, irritation, burns, and pain. Chronic effects are delayed and symptoms may not be observed during an exposure. Effects are dependent on exposure (dose, concentration, contact time).

Carcinogenicity:

IARC	Group 1: Carcinogenic to humans	
ACGIH	trichloroethylene Suspected human carcinogen	79-01-6
OSHA	trichloroethylene	79-01-6
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. Reasonably anticipated to be a human carcinogen trichloroethylene	79-01-6

Acute toxicity**Product:**

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
---------------------	---

Components:

trichloroethylene:	
Acute oral toxicity	: LD50 Oral Rat: 4,920 mg/kg

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

Acute inhalation toxicity : LC50 Mouse: 8450 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal Rabbit: > 20,000 mg/kg

propane:

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 658 mg/l
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

butane:

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 1,355 mg/l

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg
Method: Calculation method

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

trichloroethylene:**propane:****butane:****propan-2-ol:****graphite:**

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

Components:**trichloroethylene :**

Partition coefficient: n-octanol/water : log Pow: 2.29

butane :

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

ZEP DRY GRAPHITE AERO DZ

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION**TSCA list**

: No substances are subject to a Significant New Use Rule.
The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
trichloroethylene

79-01-6

SAFETY DATA SHEET**Zep Inc****ZEP DRY GRAPHITE AERO DZ**

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
trichloroethylene	79-01-6	100	159
butan-1-ol	71-36-3	5000	100
butan-1-ol	71-36-3	100	100

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

- : Fire Hazard
- Sudden Release of Pressure Hazard
- Acute Health Hazard
- Chronic Health Hazard

SARA 302

- : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313

- : The following components are subject to reporting levels established by SARA Title III, Section 313:

trichloroethylene	79-01-6	62.8498 %
-------------------	---------	-----------

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

trichloroethylene

79-01-6

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

trichloroethylene

79-01-6

The components of this product are reported in the following inventories:**TSCA**

On TSCA Inventory

DSL

All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

ZEP DRY GRAPHITE AERO DZ


Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	3*
FLAMMABILITY	0
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms :



Signal word

: **Danger**:

Hazard statements

: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer.

Precautionary statements

: **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	03/20/2017
Print Date:	11/17/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

SAFETY DATA SHEET**ZEP DRY GRAPHITE AERO DZ**

Version 1.1

Revision Date 03/20/2017

Print Date 11/17/2017

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.