

Safety Data Sheet

Issue Date 05-Feb-2024

Revision Date 05-Feb-2024

Revision Number 15

1. IDENTIFICATION

Product identifier

Product Code B700-1070B
Product Name SERIES 700/1070 CONVERTER ISO

Other means of identification

Common Name SERIES 700/701/1070/1071/1072/1078, PART B
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address
Tnemec Company, Inc. 123 W. 23rd Avenue, North Kansas City, MO 64116-3094 (816) 474-3400

Distributor
Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status
This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


Acute toxicity - Inhalation (Vapors)	Category 4
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

WARNING

Hazard statements
Harmful if inhaled
May cause an allergic skin reaction
May cause respiratory irritation. May cause drowsiness or dizziness
Flammable liquid and vapor



Appearance opaque

Physical state liquid

Odor Slight

Precautionary Statements

Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Contaminated work clothing should not be allowed out of the workplace
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Wear protective gloves/protective clothing/eye protection/face protection
 Keep cool

Response

Get medical advice/attention if you feel unwell
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician if you feel unwell
 In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed
 Store locked up
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

Toxic to aquatic life with long lasting effects
 SEE SAFETY DATA SHEET

Acute Toxicity 89.8 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
HEXAMETHYLENE DIISOCYANATE (HDI) POLYMER	28182-81-2	60 - 100%
PETROLEUM SOLVENT (NAPHTHA)	64742-95-6	1 - <10%
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - <10%
N-BUTYL ACETATE	123-86-4	1 - <10%
HEXAMETHYLENE DIISOCYANATE (HDI)	822-06-0	0.1 - <1%

MONOMER		
---------	--	--

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
Skin contact	Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.
<u>Most important symptoms and effects, both acute and delayed</u>	
Notes to physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Water.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Hydrogen cyanide.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Strong oxidizing agents, caustic. Water, alcohols, amines, strong bases, metal components, surface active materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,2,4-TRIMETHYLBENZENE 95-63-6	TWA: 10 ppm	-	
N-BUTYL ACETATE 123-86-4	TWA: 50 ppm STEL: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³	1700 ppm
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	TWA: 0.005 ppm	-	

NIOSH IDLH: *Immediately Dangerous to Life or Health*

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses with side-shields. If splashes are likely to occur, wear face-shield.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (TC 19C NIOSH/MSHA) is recommended. A vapor-particulate respirator (TC 23C NIOSH/MSHA) may be appropriate where air monitoring demonstrates vapors are less than ten times the applicable exposure limits and the isocyanate concentration is less than its applicable exposure limit. The use of an air-supplied respirator is mandatory whenever the airborne concentration of isocyanate monomer is unknown.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Slight
Appearance	opaque	Odor threshold	No information available
Color	No information available		
<u>Property</u>	<u>Values</u>	<u>Remarks</u>	
pH		No data available	
Melting point / freezing point	No data available	No data available	
Boiling point / boiling range	72 °C / 162 °F		
Flash point	38 °C / 100.4 °F	Pensky Martens - Closed Cup	
Evaporation rate		No data available	
Flammability (solid, gas)	No data available	Not applicable	
Flammability Limit in Air		approximate	
Upper flammability limit	12.3		
Lower flammability limit	0.9		
Vapor pressure		No data available	
Vapor density		No data available	
Specific gravity	1.12107	g/cm3	
Water solubility	Insoluble in cold water		
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition temperature	No data available	No data available	
Decomposition temperature	No information available	No data available	
Kinematic viscosity	No information available	No data available	
Dynamic viscosity	875 centipoises	approx	

Other Information

Molecular weight	No information available
Density	9.34973 lbs/gal
Volatile organic compounds (VOC) content	0.93497 lbs/gal
Total volatiles weight percent	10 %
Total volatiles volume percent	13.9 %
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity
No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Keep away from children. Amines.

Incompatible materials

Strong oxidizing agents, caustic, Water, alcohols, amines, strong bases, metal components, surface active materials

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Nitrogen oxides (NOx). Hydrocarbons. Hydrogen cyanide.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	Contains isocyanate monomer. If subject to spray application, engineering and administrative controls must be instituted to maintain an exposure level below .005ppm. If these controls are not adequate, the use of an air-supplied respirator is mandatory. Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. May cause sensitization of susceptible persons.
Eye contact	Causes serious eye irritation.
Skin contact	May cause sensitization of susceptible persons. Irritating to skin.
Ingestion	Harmful if swallowed.

Information on toxicological effects

Symptoms	Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Skin disorders. Respiratory disorders. Irritating to eyes and skin.
-----------------	---

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity	Avoid repeated exposure. Prolonged exposure may cause chronic effects. Contains isocyanates. May produce an allergic reaction. Causes damage to organs through prolonged or repeated exposure.
Sensitization	May cause sensitization of susceptible persons.
Mutagenicity	No information available.
Carcinogenicity	There are no known carcinogenic chemicals in this product.
Reproductive effects	No information available.
STOT - single exposure	Causes damage to organs
STOT - repeated exposure	No information available
Aspiration hazard	Not applicable.
Acute Toxicity	89.8 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

98.801 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
PETROLEUM SOLVENT (NAPHTHA) 64742-95-6	-	LC50: 9.22 mg/L Oncorhynchus mykiss 96 h	EC50: 6.14 mg/L Daphnia magna 48 h
1,2,4-TRIMETHYLBENZENE 95-63-6	-	LC50: 7.19 - 8.28 mg/L Pimephales promelas 96 h flow-through	EC50: 6.14 mg/L Daphnia magna 48 h
N-BUTYL ACETATE 123-86-4	EC50: 674.7 mg/L Desmodesmus subspicatus 72 h	LC50: 100 mg/L Lepomis macrochirus 96 h static LC50: 17.1/19 mg/L Pimephales promelas 96 h flow-through	-
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	-	LC50: 26.1 mg/L Brachydanio rerio 96 h static	-

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Chemical name	log Pow
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63
N-BUTYL ACETATE 123-86-4	1.81

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239

California Hazardous Waste Status

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical name	CAWAST
N-BUTYL ACETATE 123-86-4	Toxic

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name

PAINT & RELATED MATERIAL NOT REGULATED

IATA

UN/ID no. UN1263
 Proper Shipping Name PAINT
 Hazard Class 3
 Packing Group III
 ERG Code 128

IMDG/IMO

Proper Shipping Name PAINT & RELATED MATERIAL, NOT REGULATED

Additional Information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Complies
 ENCS Does Not Comply
 IECS Complies
 KECL Complies
 PICCS Complies
 AICS Complies

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECS - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name	HAPS Data
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER - 822-06-0	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
N-BUTYL ACETATE	5000 lb			X

123-86-4			
----------	--	--	--

CERCLA

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
N-BUTYL ACETATE 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

California Prop. 65

None of the ingredients are listed with California Proposition 65.

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
N-BUTYL ACETATE 123-86-4	X	X	X
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	X	X	

16. OTHER INFORMATION

NFPA	Health 2	Flammability 2	Instability 1	Physical hazard *
HMIS (Hazardous Material Information System)	Health 2*	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 05-Feb-2024
 Revision Summary
 9 4 5 7 10 8 11 2 14 15 1 13 6

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS

