

# MATERIAL SAFETY DATA SHEET



## SECTION 1 - PRODUCT AND COMPANY INFORMATION

Refinish Products  
19699 Progress Drive  
Strongsville, OH 44149

**EMERGENCY PHONE NUMBERS (412) 434-4515 (U.S.)**  
(24 hours/day):

(514) 645-1320 (Canada)  
01-800-00-21-400 (Mexico)  
0532-83889090 (China)

**TECHNICAL INFORMATION:** (440) 572-2800

**PRODUCT SAFETY/MSDS INFORMATION:** (412) 492-5555 7:00 a.m. - 4:30 p.m. EST

**Product ID:** DX579 (0808)  
**PRODUCT NAME:** METAL CLEANER  
**SYNONYMS:** None  
**ISSUE DATE:** 05/02/2006  
**EDITION NO.:** 5  
**CHEMICAL FAMILY:** MIXTURE

### EMERGENCY OVERVIEW:

CAUSES IRREVERSIBLE EYE DAMAGE. MAY BE CORROSIVE. THIS PRODUCT CONTAINS A MATERIAL WHICH CAUSES SKIN BURNS. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. VAPOR AND/OR SPRAY MIST HARMFUL IF INHALED. VAPOR IRRITATES EYES, NOSE, AND THROAT. VAPOR GENERATED AT ELEVATED TEMPERATURES IRRITATES EYES, NOSE AND THROAT. HARMFUL OR FATAL IF SWALLOWED. STABLE - HAZARDOUS REACTIONS POSSIBLE AT EXTREMELY HIGH TEMPERATURES/PRESSURES. This product is not expected to present any unusual hazards under fire or spill conditions. Read entire MSDS before use.

## SECTION 2 - COMPOSITION INFORMATION

The following ingredient(s) marked with an "x" are considered hazardous under applicable U.S. OSHA and/or Canadian WHMIS regulations. If no ingredients are listed, then there are no U.S. OSHA and/or Canadian WHMIS hazardous ingredients in this product.

Material/ CAS Number	Percent	Hazardous
PHOSPHORIC ACID 7664-38-2	10 - 30	X
2-BUTOXY ETHANOL 111-76-2	5 - 10	X
DIETHYLENE GLYCOL MONOBUTYL ETHER 112-34-5	5 - 10	X

## SECTION 3 - HAZARDS IDENTIFICATION

### ACUTE OVEREXPOSURE EFFECTS

#### EYE CONTACT:

This product contains a material which causes irreversible eye damage. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact.

#### SKIN CONTACT:

May be corrosive. This product contains a material which causes skin burns. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

#### SKIN ABSORPTION:

May be harmful if absorbed through the skin.

#### INHALATION:

Vapor and/or spray mist harmful if inhaled. Vapor irritates eyes, nose, and throat. Vapor generated at elevated temperatures irritates eyes, nose and throat.

### INGESTION:

Harmful or fatal if swallowed.

### SIGNS & SYMPTOMS OF OVEREXPOSURE:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are indications that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Not applicable.

### CHRONIC OVEREXPOSURE EFFECTS

Avoid long-term and repeated contact.

Repeated exposure to vapors above recommended exposure limits (see Section 8) may cause irritation of the respiratory system and permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. The effects of long-term, low level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the prevention of all contact with this material to avoid any effects from repetitive acute exposures. See Section 11, of this MSDS for a detailed list of chronic health effects information available on individual ingredients in this product.

## SECTION 4 - FIRST AID MEASURES

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available.

### EYE CONTACT:

Remove contact lens and pour a gentle stream of warm water through the affected eye for at least 15 minutes. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.

### SKIN CONTACT:

Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.

### INHALATION:

Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information.

### INGESTION:

Gently wipe or rinse the inside of the mouth with water. Sips of water may be given if person is fully conscious. Never give anything by mouth to an unconscious or convulsing person. Do Not induce vomiting. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.

## SECTION 5 - FIRE FIGHTING MEASURES

### FLAMMABLE PROPERTIES

**FLASHPOINT:** >300 Degrees F (>149 Degrees C)

### FLASHPOINT TEST METHOD:

Pensky-Martens Closed Cup

**UEL:** Not Available.

**LEL:** Not Available.

### AUTOIGNITION TEMPERATURE:

Not Available.

### EXTINGUISHING MEDIA:

Use extinguishers appropriate for surrounding fire.

### PROTECTION OF FIREFIGHTERS:

Water spray may be ineffective. Water spray may be used to cool closed containers that are exposed to extreme heat. If water is used, fog nozzles are preferable. Firefighters should wear self-contained breathing apparatus and full protective clothing.

#### UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers may explode or burst (due to the build-up of steam pressure) when exposed to extreme heat. May produce hazardous decomposition products when exposed to extreme heat. Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

#### SECTION 6 - ACCIDENTAL RELEASE MEASURE

##### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.

#### SECTION 7 - HANDLING AND STORAGE

##### PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE:

If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

##### STORAGE:

Protect from freezing.

#### SECTION 8 - EXPOSURE CONTROLS & PERSONAL PROTECTION

##### ENGINEERING CONTROLS:

Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 8 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

#### PERSONAL PROTECTIVE EQUIPMENT

##### EYES:

Wear chemical-type splash goggles and full face shield when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.

##### SKIN/GLOVES:

Wear protective clothing sufficient to cover exposed skin surfaces. For applications where skin contact is likely and impermeable clothing is necessary, select clothing constructed of: neoprene rubber or nitrile rubber. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment. Clean contaminated clothing and shoes.

##### RESPIRATOR:

Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. A NIOSH- approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may also reduce exposure. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used. Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

##### GENERAL HYGIENE - ESTABLISHED EXPOSURE LIMITS

If Threshold Limit Values (TLVs) have been established by ACGIH, OSHA, Ontario or PPG, they will be listed below. These limits are intended for use in the practice of industrial hygiene as guidelines or recommendations in the control of potential workplace health hazards. These limits are not a relative index of toxicity and should not be used by anyone without industrial hygiene training.

Material/ CAS Number	Percent	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL
PHOSPHORIC ACID 7664-38-2	10 - 30	1 mg/m <sup>3</sup>	3 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>	3 mg/m <sup>3</sup>
2-BUTOXY ETHANOL 111-76-2	5 - 10	20 PPM	Not established	S- 25 ppm	Not established

Material/ CAS Number	Percent	Ontario TWA	Ontario STEL	PPG IPEL	PPG STEL
PHOSPHORIC ACID 7664-38-2	10 - 30	1 mg/m <sup>3</sup>	3 mg/m <sup>3</sup>	Not established	Not established
2-BUTOXY ETHANOL 111-76-2	5 - 10	S- 20 PPM	Not established	Not established	Not established
DIETHYLENE GLYCOL MONOBUTYL ETHER 112-34-5	5 - 10	Not established	Not established	35 ppm	Not established

**Key:** ACGIH=American Conference of Governmental Industrial Hygienists; OSHA=Occupational Safety and Health Administration; TLV=Threshold Limit Value; TWA=Time Weighted Average; PEL=Permissible Exposure Limit; IPEL=Internal Permissible Exposure Limit; Ceiling=TLV or PEL Ceiling Limit; STEL=TLV or PEL Short-Term Exposure Limit; Skin= Skin Absorption Designation. [C- Ceiling Limit; S- Potential Skin Absorption; R-Respirable Dust]

**Additional Information** Not applicable.

#### SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

##### (FORMULA VALUES, NOT SALES SPECIFICATIONS)

<b>SPECIFIC GRAVITY:</b>	1.153
<b>PHYSICAL STATE:</b>	Liquid
<b>Percent Solids:</b>	30.96
<b>Percent Volatile by Volume:</b>	81.450
<b>pH:</b>	Not available.
<b>ODOR THRESHOLD:</b>	Not available.
<b>Vapour Pressure:</b>	16.6 mmHg
<b>ODOR/APPEARANCE:</b>	Viscous liquid with an odor characteristic of the chemical family and any solvents listed in Section 2.
<b>VAPOR DENSITY:</b>	HEAVIER THAN AIR
<b>Evaporation Rate:</b>	26
<b>BOILING POINT OR RANGE:</b>	212- 446Degrees F
<b>Freezing Point or Range:</b>	Not Applicable.
<b>Melting Point or Range(°C):</b>	Not Applicable.
<b>Partition coefficient (n-octanol/water):</b>	Not Applicable.
<b>WEIGHT PER GALLON:</b>	9.61 (U.S.) / 11.5 (IMPERIAL)

#### SECTION 10 - STABILITY AND REACTIVITY

##### STABILITY:

This product is normally stable but may undergo hazardous reactions at extremely high temperatures and pressures.

##### CONDITIONS TO AVOID:

None Known.

##### INCOMPATIBLE MATERIALS:

Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.

##### HAZARDOUS POLYMERIZATION:

None Known.

##### HAZARDOUS DECOMPOSITION PRODUCTS:

- Carbon monoxide - Carbon dioxide - Phosphorus pentoxide

#### SECTION 11 - TOXICOLOGICAL INFORMATION

##### ACUTE TOXICITY

Material/ CAS Number	Percent	ORAL LD50 (g/kg)	DERMAL LD50 (g/kg)	INHALATION LC50 (mg/l)
PHOSPHORIC ACID 7664-38-2	10 - 30	1.53 g/kg	2.74 g/kg	Not Available
2-BUTOXY ETHANOL 111-76-2	5 - 10	.47 g/kg	.22 g/kg	2.18 g/L. 4 hr.
DIETHYLENE GLYCOL MONOBUTYL ETHER 112-34-5	5 - 10	6.56 g/kg	4.12 g/kg	Not Available

##### CHRONIC TOXICITY

###### Ingredient Target Organ/Chronic Effects:

- Bone marrow and blood tissues - Blood - Carcinogen - Brain - Central nervous system - Lung - Kidney - Liver - Spleen

##### Mutagenicity Toxicity:

This has not been tested for this product.

##### Reproductive Toxicity:

This has not been tested for this product.

#### SUPPLEMENTAL HEALTH INFORMATION:

Material/ CAS Number	Percent	Ingredient Specific Animal Data:
2-BUTOXY ETHANOL 111-76-2	5 - 10	This product contains an ethylene series glycol ether and/or acetate which has been shown to cause adverse effects on the kidneys, liver, blood and/or blood-forming tissue. In a two-year NTP inhalation study, there was no significant increase in the incidence of any type of tumor in rats exposed to 2-butoxy ethanol at concentrations up to 125 ppm except a questionable trend in the incidence of adrenal gland tumors in female rats. When mice were exposed to concentrations of 62.5, 125, and 250 ppm, there was some evidence of carcinogenicity found in the liver of male mice and the forestomach of female mice at 250 ppm. This product contains an ingredient which has been shown to cause adverse reproductive effects in animals at doses which are also toxic to the mother.
DIETHYLENE GLYCOL MONOBUTYL ETHER 112-34-5	5 - 10	This product contains diethylene glycol monobutyl ether (DEGBE). DEGBE consumed in drinking water at low levels by rats for 30 days caused microscopic injury to either the liver, kidney, spleen, or testes. Further studies on the reproductive effects of DEGBE have not produced evidence of toxic effects in tissue culture or animal assays.

#### SECTION 12 - ECOLOGICAL INFORMATION

##### POTENTIAL ENVIRONMENTAL EFFECTS

Ecotoxicity: No Information Available.

##### ENVIRONMENTAL FATE

Mobility: No information available.

Biodegradation: No information available.

Bioaccumulation: No Information Available.

##### PHYSICAL/CHEMICAL

Hydrolysis: No information available.

Photolysis: No information available.

#### SECTION 13 - DISPOSAL CONSIDERATIONS

Provide maximum ventilation, only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Take up spilled material with sawdust, vermiculite, or other absorbent material and place in containers for disposal.

Waste material must be disposed of in accordance with federal, state, provincial and local environmental control regulations. Empty containers should be recycled by an appropriately licensed reconditioner/salvager or disposed of through a permitted waste management facility. Additional disposal information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

#### SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name: Phosphoric Acid Liquid Solution

NOS Technical Name: None

Hazard Class: 8

Subsidiary Class(es): None

UN Number: UN1805

Packing Group: III

USA - RQ Hazardous Substances: Phosphoric Acid

USA-RQ Hazardous Substance Phosphoric Acid>16666.69 Pounds

Threshold Ship Weight:

Marine Pollutant Name: None

USA Shipments Only - RQ Threshold Ship Weight: This is the total weight of this product that must be shipped to exceed the RQ quantity.

#### SECTION 15 - REGULATORY INFORMATION

##### INVENTORY STATUS

U.S. TSCA: This product and/or all of its components are listed on the U.S. TSCA Inventory or is otherwise exempt from TSCA Inventory reporting requirements.

##### FEDERAL REGULATIONS

###### US Regulations

Material/ CAS Number	Percent	CERCLA HS - RQ (LBS)	SARA EHS - TPQ (LBS)	SARA 313
PHOSPHORIC ACID 7664-38-2	10 - 30	5000 lbs	Not Listed	Not Listed
2-BUTOXY ETHANOL 111-76-2	5 - 10	Not Listed	Not Listed	Not Listed
DIETHYLENE GLYCOL MONOBUTYL ETHER 112-34-5	5 - 10	Not Listed	Not Listed	Not Listed

##### SARA 311/312

Health (acute): Yes

Health (chronic): Yes

Fire (flammable): No

Pressure: No

Reactivity: No

WHMIS HAZARD CLASS: - Class D, Division 1, Subdivision B - Class D, Division 2, Subdivision A - Class D, Division 2, Subdivision B - Class E

##### STATE/PROVINCIAL REGULATIONS

###### Additional Information

Key: IARC- International Agency on the Research of Cancer; ACGIH- American Conference of Governmental Industrial Hygienists; NTP- National Toxicology Program \*Denotes chemical as NTP Known Carcinogen; + Denotes NTP Possible Carcinogen; OSHA- Occupational Safety and Health Administration.

<b>SECTION 16 - OTHER INFORMATION</b>
---------------------------------------

**Hazard Rating Systems**

**NFPA Rating:** 3 11

**HMIS Rating:** 3\*11

**Rating System:** 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe,  
\*=Chronic Effects.

HMIS=Hazardous Materials Identification System; NFPA=National Fire  
Protection Association;

Safe handling of this product requires that all of the information on the  
MSDS be evaluated for specific work environments and conditions of use.

**PREPARED BY:** Product Safety Department

**REASON FOR REVISION:** Section 1 has been updated. Section 5 has  
been updated. Section 7 has been updated. Section 8 has been updated.  
Section 9 has been updated. Section 10 has been updated. Date.

Edition.

Updated MSDS

format.

This Material Safety Data Sheet has been prepared in accordance with  
Canada's Workplace Hazardous Materials Information System (WHMIS)  
and the OSHA Hazard Communication Standard (29 CFR 1910.1200),  
the supplier notification requirements of SARA Title III, Section 313 and  
other applicable right-to-know regulations.

Additional environmental information is contained on the Environmental  
Data Sheet for this product, which can be obtained from your PPG  
representative.

DX579 000001 (00324992.001)(01/14/05)

050103, 000, 0808

\*\*\* END OF MSDS \*\*\*