



MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 40mm Skat-Shell Round Smoke		DATE: March 11, 2010	
PRODUCT NUMBER: 6173			
TRADE NAME: 40mm Skat-Shell Round Smoke GENERAL USE: Practice Round CHEMICAL FAMILY: Incendiary PRODUCT DESCRIPTION: Canister containing white powder. (Explosive Device)	 DEFENSE TECHNOLOGY		
MANUFACTURED FOR: Safariland L.L.C.		DATE PREPARED: March 11, 2010	
		SUPERSEDES: August 11, 2008	
ADDRESS (NUMBER, STREET, P.O. BOX): 13386 International Parkway		TELEPHONE NUMBER FOR INFORMATION / Customer Service: 904-741-5400	
(CITY, STATE AND ZIP CODE): Jacksonville, FL 32218		CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBER:	
COUNTRY: USA			
		1-800-255-3924 01-813-248-0585 North America Toll Free International	

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION! EXPLOSIVE/DEFLAGRATING (FAST BURN RATE) PRODUCT. KEEP AWAY FROM HEAT. DO NOT SUBJECT TO MECHANICAL OR ELECTRICAL SHOCK. EXPLODING CARTRIDGES MAY EJECT SHRAPNEL AT HIGH VELOCITIES. PARTICLES FROM FIRING MAY BE HARMFUL IF INHALED. DO NOT TAKE INTERNALLY. COMPONENTS MAY HARM ENVIRONMENT.

Individual cartridges may ignite if the primer is struck or if the cartridge is exposed to excess heat. Oxides of Barium, Lead, Antimony, Aluminum, Magnesium, Nitrogen, Carbon, and Sulfur. Lead and Antimony fumes may also be produced on thermal decomposition.

POTENTIAL HEALTH EFFECTS

INHALATION:

Both pre and post ignition ingredients are hazardous and capable of producing long term health effects due primarily to the presence of zinc, lead, antimony in the product. While normal handling of the undetonated product poses little or no health hazards, one should avoid inhalation by wearing appropriate respiratory protection when exposed to the chemical ingredients of the product above listed TLV's or when exposed to the post ignition by-products. This product is a finished cartridge or canister which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is used, particles may be generated which may be slightly irritating to the eyes and the respiratory tract. The particles may contain trace amounts of the following harmful substances:

Lead: Ingestion of large amounts of lead can cause abdominal pain, constipation, cramps, nausea and/or vomiting. Chronic exposure to lead can cause kidney damage, anemia, reproductive effects, developmental effects and permanent nervous system damage in humans including changes in cognitive function. It is unlikely that the amount of particles that someone would be exposed to from firing a loaded round would be sufficient to cause any of these effects.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: There are no medical conditions known to be aggravated by exposure to this product in its solid form. Exposure to lead compounds in the primer can aggravate anemia, cardiovascular and respiratory disease.

SKIN:

No exposure to chemical hazards anticipated with normal handling procedures.

EYES:

No exposure to chemical hazards anticipated with normal handling procedures.

INGESTION:

No exposure to chemical hazards anticipated with normal handling procedures. Contents of this product are toxic by ingestion and in the unlikely event this should occur immediate medical attention is advised.

CARCINOGENICITY:

NTP? Yes-Lead cpds.	IARC MONOGRAPHS? Yes-Lead products (2B)	OSHA REGULATED? Yes- Lead
CALIFORNIA, Prop.65? Yes, Lead compounds and Antimony trioxide formed during use of product	ESIS NOTATION?	Yes

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:		40mm Skat-Shell Round Smoke		DATE:		March 11, 2010	
PRODUCT NUMBER:		6173					
SECTION 3 - HAZARDOUS INGREDIENTS							
<i>Powder Charge- Product will contain 1 or more of the following hazardous components</i>							
Hazardous Components	% (by Weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES (Full Text Section 15)		
Potassium perchlorate	NR	7778-74-7	231-912-9	Xn, O	R9, R22		
Potassium nitrate	NR	7757-79-1	231-818-8	Xn, O	R8, R36/37/38		
Sulfur	100	7704-34-9	231-722-6	F, Xi	R11, 36/37/38		
Charcoal	NR	16291-96-6	240-383-3	None	None		
Rosin	NR	8050-09-7	232-475-7	Xi	R43		
Graphite	NR	7782-42-5	231-955-3	None	None		
<i>Primer - Product will contain 1 or more of the following hazardous components</i>							
Normal Lead styphnate	NR	15245-44-0	239-290-0	E,T,N	R3, R20/22, R33, R50/53, R61, R62		
Basic Lead styphnate	NR	12403-82-6	235-642-2	E,T,N	R3, R20/22, R33, R50/53, R61, R62		
Lead Azide	NR	13424-46-9	236-542-1	E,T,N	R3, R20/22, R33, R50/53, R61, R62		
Lead Thiocyanate	NR	592-87-0	209-774-6	T	R23/24/25		
Nitrocellulose	NR	9004-70-0	NR	E,F	R1, R2, R5 ,R11		
Tetracene	NR	109-27-3	203-659-4	E	R3, R5, R20/22		
Potassium chlorate	NR	3811-04-9	223-289-7	Xn, O	R9, R20/22		
Potassium nitrate	NR	7757-79-1	231-818-8	Xn, O	R8, R36/37/38		
Barium nitrate	NR	10022-31-8	233-020-5	T, O	R8, R23/24/25		
Antimony Sulfide	NR	1345-04-6	231-146-5	Xn, N	R20/22, R51/53		
Zinc	NR	7440-66-6	231-175-3	N	R17, 50/53		
<i>Remainder of Product - Product will contain 1 or more of the following hazardous components</i>							
Potassium Chlorate	NR	3811-04-9	231-104-6	F, Xn, N	R9, R20/22, R51/53		
Sugar	NR	57-50-1	200-334-9	None	None		
Magnesium Carbonate	NR	546-93-0	208-915-9	None	None		
Nitrocellulose	NR	9004-70-0	NR	E, F	R1, R2, R5,R11		
Terephthalic Acid	NR	100-21-0	202-830-0	None	None		
Tin	NR	7440-31-5	231-141-8	F, Xi	R11, R36/37/38		
Zinc	NR	7440-66-6	231-175-3	N	R17, 50/53		
Chromium	NR	7440-47-3	231-157-5	None	None		
Copper	NR	7440-50-8	231-159-6	None	None		
Iron	NR	7439-89-6	231-096-4	None	None		
Aluminum	NR	7429-90-5	231-072-3	F	R15,R17		
<p>NOTES: This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006 (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European (GHS) directive 1907/2006 and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directive 67/548/EEC.</p>							

MATERIAL SAFETY DATA SHEET

Page 3 of 8

PRODUCT NAME: 40mm Skat-Shell Round Smoke
PRODUCT NUMBER: 6173 DATE: March 11, 2010

SECTION 4 - FIRST AID MEASURES

INHALATION:

For symptoms of lung irritation occur (coughing, wheezing or breathing difficulty), remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep affected person warm and at rest. Get medical attention.

EYES:

Remove contact lenses, then wash for 15 minutes with clean potable water lifting upper and lower lids occasionally. Seek medical attention if irritation persists.

SKIN:

Wash with plenty of soap and water. Seek medical attention if delayed dermatitis develops. For contact with burning (ignited) particles, medical treatment may be needed for thermal burns.

INGESTION:

Contact medical authorities immediately. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs naturally, have victim lean forward to avoid aspiration of regurgitant. Give 1-2 glasses of water to victim if victim is conscious and able to swallow and seek immediate medical assistance. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS:

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. Shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

EXTINGUISHING MEDIA:

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used. If the fire reaches the cargo, withdraw and let fire burn.

FIRE FIGHTING PROCEDURES:

In case of fire, use normal fire fighting equipment. Protection concerns must also address the potential of the physical characteristic of this product as explosive. Quarantine area for at least 1500 feet from fires involving product.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

If fire reaches cargo, do not fight; withdraw personnel to safe distance. Evacuate all persons, including emergency responders from the area for 1500 feet (1/3 mile) in all directions.

HAZARDOUS COMBUSTION PRODUCTS:

Metal Compounds, Carbon Monoxide, Carbon Dioxide, Nitrous Oxides, Various complex oxides of metals, Nitrogen.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTEL AT 1-800-255-3924. Spills of this material should be handled carefully. Do not subject materials to mechanical shock or extreme heat. A spill of this material will normally not require emergency response team capabilities.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

HANDLING: Cartridge may detonate or burn if case is punctured or severely damaged.

STORAGE: Avoid storage near extreme heat, ignition sources or open flame.

Shelf Life Limitations: Not known

Incompatible Materials for Packaging: None known

Incompatible Materials for Storage or Transport: Acids, Class A & B explosives, strong oxidizers, and caustics

CONDITIONS TO AVOID: Mechanical impact or shock, electrical discharge, high energy EM fields (radar stations).

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	40mm Skat-Shell Round Smoke	DATE:	March 11, 2010
PRODUCT NUMBER:	6173		
SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION			
Hazardous Components	CAS #	ACGIH Exposure Limits	OSHA Exposure Limits
Antimony Sulfide	1345-04-6	0.5 mg/m3	0.5 mg/m3
Arsenic	7440-38-2	0.01 mg/m3	0.01 mg/m3
Barium nitrate	10022-31-8	0.5 mg/m3	0.5 mg/m3
Calcium Carbonate	1317-65-3	10 mg/m3	5 mg/m3
Charcoal	7782-42-5	2 mg/m3	2.5 mg/m3 (respirable dust)
Copper	7440-50-8	0.2mg/m3 (fume), 1mg/m3 (dusts and mists)	0.1mg/m3 (fume) 1mg/m3 (dusts & mists)
Dibutyl phthalate	84-74-2	5 mg/m3	5 mg/m3
Diphenylamine	122-39-4	10 mg/m3	10 mg/m3
Ethyl Acetate	141-78-6	400 ppm (1400 mg/m3)	400 ppm (1400 mg/m3)
Glass Powder	65997-17-3	10 mg/m3 (particulate)	15 mg/m3
Graphite	7782-42-5	2 mg/m3	2.5 mg/m3 (respirable dust)
Lead	7439-92-1	0.05mg/m3 (Ceiling)	0.05mg/m3 (Ceiling)
Magnesium Carbonate	546-93-0	NE	15 mg/m3 total , 5 mg/m3 respirable
Manganese	7439-96-5	0.2 mg/m3	5 mg/m3 (Ceiling)
Nickel	7440-02-0	1.5 mg/m3 (inhalable)	1 mg/m3
Graphite	7782-42-5	2 mg/m3 (respirable)	NE
Nickel	7440-02-0	1.5 (respirable)	1
Sugar	57-50-1	5 mg/m3 (respirable)(NIOSH)	15 mg/m3 total , 5 mg/m3 respirable
Sulfur	7704-34-9	15 mg/m3	15 mg/m3
Terephthalic Acid	100-21-0	10 mg/m3	NE
Tin	7440-31-5	2 mg/m3	2 mg/m3
Tin Dioxide	18282-10-5	2 mg/m3	2 mg/m3 (as Tin)
Tungsten	7440-33-7	5 mg/m3 TWA, 10 mg/m3 (STEL)	NE
Components not listed above do not have published exposure limits from ACGIH or OSHA.			
PERSONAL PROTECTION			
RESPIRATORY PROTECTION:			
Respiratory protection not normally needed. Mask should be worn while cleaning debris from weapons			
PROTECTIVE GLOVES:			
None required for normal handling.			
EYE PROTECTION:			
Safety glasses with side shields required.			
OTHER PROTECTIVE CLOTHING OR EQUIPMENT:			
Local exhaust ventilation is recommended if significant dusting occurs or fumes are generated. Otherwise, use general exhaust ventilation. Use hearing protection with this product.			
WORK / HYGIENIC PRACTICES:			
Avoid breathing fumes from ignition. DO NOT EAT/DRINK/SMOKE WHILE HANDLING PRODUCT!!!			

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: 40mm Skat-Shell Round Smoke		DATE: March 11, 2010	
PRODUCT NUMBER: 6173			
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES			
APPEARANCE AND ODOR Canister containing white powder. (Explosive Device)		VAPOR PRESSURE Not applicable.	
pH Not applicable.		SPECIFIC GRAVITY (WATER = 1) Not applicable	
MELTING POINT Not applicable.		SOLUBILITY IN WATER Insoluble - some components are soluble in water	
FLASH POINT Not applicable.		VISCOSITY Not applicable	
FLAMMABLE LIMITS EXPLOSIVE!! LEL: None UEL: None		VAPOR DENSITY (AIR = 1) Not applicable.	
AUTOIGNITION TEMPERATURE NR		EVAPORATION RATE (WATER = 1) Not applicable.	
VOLATILE ORGANIC COMPOUND (VOC) INFORMATION Not applicable.			
NOTES:			
SECTION 10 - STABILITY AND REACTIVITY			
STABILITY STABLE X		CONDITIONS TO AVOID: Cartridge may detonate if case is punctured or severely damaged.	
INCOMPATIBILITY (MATERIALS TO AVOID): Acids, Class A & B explosives, strong oxidizers, and caustics.			
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Nitrogen oxides, carbon monoxide, lead oxides, carbon dioxide, lead dust/fume.			
HAZARDOUS POLYMERIZATION: Will not occur.		CONDITIONS TO AVOID: None related to polymerization.	
SECTION 11 - TOXICOLOGICAL INFORMATION			
Complete Product			
Oral LD ₅₀	NA		
Dermal LD ₅₀	NA		
Inhalation LC ₅₀	Not applicable for product. Particles generated from use may be irritating or slightly toxic.		
Irritation	Not a skin or eye irritant as a loaded round. Particulate dusts and gases from spent round may be a mild respiratory / eye irritant.		
Product Components			
Hazardous Components	CAS #	LD50 of Ingredient (Oral, Rat - unless otherwise specified)	LC50 of Ingredient (Inhalation, Rat - unless otherwise specified)
Antimony	7440-36-0	7 g/kg	Not Established
Antimony Sulfide	1345-04-6	7000 mg/kg	Not Established
Basic Lead styphnate	12403-82-6	650 mg/kg	Not Established
Bismuth	7440-69-9	5000 mg/kg	Not Established
Boron	7440-42-8	650 mg/kg	Not Established
Chromium	7440-47-3	5045 mg/kg	Not Established
Copper	7440-50-8	413 mg/kg (oral, mouse)	> 1000 mg/m3
Dibutyl phthalate	84-74-2	8 g/kg	4250 mg/m3
Diphenylamine	122-39-4	1120 mg/kg	Not Established
Ethyl Acetate	141-78-6	5620 mg/kg	200 gm/m3
Iron	7439-89-6	30 g/kg	Not Established
Lead	7439-92-1	Not Established	IARC: Group 2A carcinogen
Normal Lead styphnate	15245-44-0	650 mg/kg	Not Established
Rosin	8050-09-7	3.0 mg/kg	110 mg/m3

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: 40mm Skat-Shell Round Smoke
PRODUCT NUMBER: 6173 **DATE:** March 11, 2010

Product Components (Continued)

Hazardous Components	CAS #	LD50 of Ingredient (Oral, Rat - unless otherwise specified)	LC50 of Ingredient (Inhalation, Rat - unless otherwise specified)
Sugar	57-50-1	29,700 mg/kg	110 mg/m3
Potassium chlorate	3811-04-9	1870 mg/kg	Not Established
Magnesium Carbonate	546-93-0	8000 mg/kg	Not Reported
Tetracene	109-27-3	1 – 3 g/kg	Not Established
Terephthalic Acid	100-21-0	64000 mg/kg	Not Established
Tin Dioxide	18282-10-5	>20 gm/kg	Not Established
Zinc	7440-66-6	> 8,437 mg/kg	Not Established

No LD50 or LC50 information is available for the following components: Aluminum, Calcium Silicide, Charcoal, Glass Powder, Graphite, Lead, Lead Azide, Lead Thiocyanate, Magnesium, Nickel, Nitrosodiphenylamine, Polyester Adipate, Potassium perchlorate, Tin, Tungsten

SECTION 12 - ECOLOGICAL INFORMATION

No data is available on this product, but leachates of metal components may be harmful or toxic to aquatic life and waterfowl. Collection and careful disposal of spent rounds is highly advisable. Lead and nickel are especially problematic when introduced into many ecosystems.



SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous. Damaged materials pose a danger to anyone in the immediate area; consult experts for disposal of damaged products.



SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Ammunition Smoke, Explosive 1.4G, PGII, UN0303

DOT HAZARD CLASS / Pack Group: Explosives, 1.4G/ II	IATA HAZARD CLASS / Pack Group: 1.4G / II, 75Kg Cargo Aircraft Only
REFERENCE: 49CFR	IMDG HAZARD CLASS: Explosives, 1.4G/ II
UN / NA IDENTIFICATION NUMBER: UN0303	RID/ADR Dangerous Goods Code: Explosives, 1.4G/ II
LABEL: Explosives 1.4G	UN TDG Class / Pack Group: Explosives, 1.4G/ II
HAZARD SYMBOLS: <div style="display: flex; justify-content: space-around;">   </div>	Hazard Identification Number (HIN): NA

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	40mm Skat-Shell Round Smoke	DATE:	March 11, 2010
PRODUCT NUMBER:	6173		
SECTION 15 - REGULATORY INFORMATION			
TSCA (USA - Toxic Substance Control Act): Components are listed under Section 8b.			
SARA TITLE III (USA - Superfund Amendments and Reauthorization Act):			
Acute Health:	YES	Chronic Health:	YES
Fire:	YES	Sudden Release of Pressure:	YES
Reactive:	NO		
SARA 313 REPORTABLE INGREDIENTS: Copper, Zinc (fume or dust), Lead, Antimony.			
CERCLA (USA - Comprehensive Response Compensation and Liability Act): Copper, R.Q. = 5000 lbs.; Zinc, R.Q. = 1000 lbs.; Lead, R.Q. = 10 lbs.; Antimony, R.Q. = 5000 lbs. (No reporting is required if diameter of the pieces of metal is equal to or exceeds 100 micrometers (0.004 inches)).			
California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: Lead Compounds / Antimony Trioxide from Use.			
State Right To Know Laws: This product contains chemicals listed on the Right-to-Know Laws of CA, FL, MA, MI, MN, NJ, PA, & RI.			
CPR (Canadian Controlled Products Regulations): Exempt under WHMIS regulations as explosive.			
IDL (Canadian Ingredient Disclosure List): Components are listed in Section 2.			
DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List): Listed or exempt on both CDSL and NDSL.			
EINECS (European Inventory of Existing Commercial Chemical Substances): Referenced.			
WGK Water Quality Index: NA for product.			
EUROPEAN (GHS) HAZARD SYMBOLS			
 			
EU RISK PHRASES			
R2: Risk of explosion by shock, friction, fire or other sources of ignition.			
R20/22: Harmful by inhalation and if swallowed.			
R33: Danger of cumulative effects.			
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.			
R61: May cause harm to the unborn child.			
R62: Possible risk of impaired fertility.			
EU SAFETY PHRASES			
S1/2: Keep locked up and out of the reach of children.			
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).			
S53: Avoid exposure — obtain special instructions before use.			
S60: This material and its container must be disposed of as hazardous waste.			

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	40mm Skat-Shell Round Smoke	DATE:	March 11, 2010
PRODUCT NUMBER:	6173		
SECTION 16 - OTHER INFORMATION			
HMIS HAZARD RATINGS			
	HEALTH:	2	0 = INSIGNIFICANT
	FLAMMABILITY:	3	1 = SLIGHT
	PHYSICAL HAZARD:	2	2 = MODERATE
	Personal Protective Equipment: K		3 = HIGH
			4 = EXTREME

Legend:

ACGIH - American Congress of Government Industrial Hygienists , CAS - Chemical Abstracts Service
 EINECS- European Inventory of Existing Commercial Chemical Substances
 HMIS - Hazardous Materials Identification System, IARC - International Agency for Research on Cancer
 NA - Not Available , ND - Not Determined, NE - Not Established, NR - Not Reported
 NIOSH - National Institute for Occupational Safety and Health, NTP - National Toxicology Program
 OSHA - Occupational Safety and Health Administration

Full R-Phrases:R1 Explosive when dry. R2 Risk of explosion by shock, friction, fire or other sources of ignition. R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition. R5 Heating may cause an explosion. R8 Contact with combustible material may cause fire. R9 Explosive when mixed with combustible material. R11 Highly flammable. R15 Contact with water liberates extremely flammable gases. R17 Spontaneously flammable in air. R20 Harmful by inhalation. R20/22 Harmful by inhalation and if swallowed. R22 Harmful if swallowed. R23/24/25 Toxic by inhalation, in contact with skin and if swallowed. R23/25 Toxic by inhalation and if swallowed. R33 Danger of cumulative effects. R36 Irritating to eyes. R36/37/38 Irritating to eyes, respiratory system and skin.

R40 Limited evidence of a carcinogenic effect. R43 May cause sensitisation by skin contact. R45 May cause cancer. R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed. R50 Very toxic to aquatic organisms. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. R61 May cause harm to the unborn child. R62 Possible risk of impaired fertility. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. R68 Possible risk of irreversible effects.

REVISION SUMMARY:

MSDS Prepared by:

ChemTel Inc.
 1305 North Florida Avenue
 Tampa, Florida USA 33602-2902
 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
 Website: www.chemtelinc.com



The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.