

Issue date 19-Jul-2018

Revision date 19-Jul-2018

Revision Number 1

1. IDENTIFICATION

Product identification

Product identifier Lawson Gloss Black High Solids Paint
 Other means of identification 1509224
 Recommended use Coating
 Restrictions on use Not available

Supplier

Corporate Headquarters:
 Lawson Products, Inc.
 8770 W. Bryn Mawr Ave., Suite 900
 Chicago, IL 60631
 (866) 837-9908

Canadian Distribution Center:
 Lawson Canada
 7315 Rapistan Court
 Mississauga, ON L5N 5Z4
 (800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

2. HAZARD(S) IDENTIFICATION

Hazard Classification

Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

Symbol



Signal word

DANGER

Hazard statements

H222 - Extremely flammable aerosol
 H280 - Contains gas under pressure; may explode if heated
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness
 H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements

General	P101 - If medical advice is needed, have product container or label at hand P102 - Keep out of reach of children P103 - Read label before use.
Prevention	P211 - Do not spray on an open flame or other ignition source P223 - Keep away from any possible contact with water, because of violent reaction and possible flash fire P233 - Keep container tightly closed P251 - Pressurized container: Do not pierce or burn, even after use P271 - Use only outdoors or in a well-ventilated area
Response	
Eyes	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P337 + P313 - If eye irritation persists: Get medical advice/attention
Skin	P264 - Wash hands thoroughly after handling P280 - Wear protective gloves/protective clothing/eye protection/face protection
Inhalation	P260 - Do not breathe dust/fume/gas/mist/vapors/spray P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Ingestion	P312 - Call a POISON CENTER or doctor if you feel unwell
Fire	P370 + P378 - In case of fire: Use appropriate method to extinguish
Spill	P391 - Collect spillage
Storage	P405 - Store locked up P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P403 - Store in a well-ventilated place
Disposal	P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable
Hazard(s) Not Otherwise Classified (HNOC)	None known.
Physical Hazards Not Otherwise Classified (PHNOC)	None known.
Unknown acute toxicity	None known

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Mixture.

Chemical name	CAS-No	Weight %
Acetone	67-64-1	21.59
Propane	74-98-6	15.74
N-Butane	106-97-8	9.24
Barium Sulfate	7727-43-7	9.17
Ethylene glycol monopropyl ether		

	2807-30-9	6.88
Isobutyl acetate	110-19-0	6.82
n-Butyl acetate	123-86-4	3.78
Methyl Propyl Ketone	107-87-9	1.47
Methyl isobutyl ketone	108-10-1	<1.0
Ethylbenzene	100-41-4	<1.0
Carbon Black	1333-86-4	<1.0

4. FIRST-AID MEASURES

Necessary first-aid measures

Inhalation	Remove to fresh air. If symptomatic, contact a Poison Control Center, emergency room, or a physician for treatment information.
Ingestion	Rinse mouth with water and spit out rinse. Do NOT induce vomiting.
Skin contact	Remove contaminated clothing and footwear. Wash off immediately with soap and plenty of water.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Most important symptoms (acute) Dizziness.

Most important symptoms (over-exposure) Dizziness.

Indication of any immediate medical attention and special treatment needed Not available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Carbon dioxide (CO ₂). Dry powder. Water spray. For large fire, use water spray, fog or foam.
Unsuitable extinguishing media	Not available.
Specific hazards	Can form explosive gas-air mixtures.
Special protective equipment for fire-fighters	If necessary, respiratory protective equipment (with the appropriate protection factor) should be provided and worn.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and materials for containment and cleaning up	Absorb with liquid-binding material (sand, diatomite, universal binders).

7. HANDLING AND STORAGE

Precautions for safe handling use in well ventilated areas.

Conditions for safe storage, including any incompatibilities Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store away from direct sunlight. Do not allow to freeze. Store locked up.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Acetone	1000 ppm TWA 2400 mg/m ³ TWA	500 ppm STEL 250 ppm TWA	250 ppm TWA 590 mg/m ³ TWA
Propane	1000 ppm TWA 1800 mg/m ³ TWA	-	1000 ppm TWA 1800 mg/m ³ TWA
N-Butane	-	1000 ppm STEL	800 ppm TWA 1900 mg/m ³ TWA
Barium Sulfate	15 mg/m ³ TWA 5 mg/m ³ TWA	5 mg/m ³ TWA	10 mg/m ³ TWA 5 mg/m ³ TWA
Ethylene glycol monopropyl ether	-	-	-
Isobutyl acetate	150 ppm TWA 700 mg/m ³ TWA	150 ppm STEL 50 ppm TWA	150 ppm TWA 700 mg/m ³ TWA
n-Butyl acetate	150 ppm TWA 710 mg/m ³ TWA	150 ppm STEL 50 ppm TWA	200 ppm STEL 950 mg/m ³ STEL 150 ppm TWA 710 mg/m ³ TWA
Methyl Propyl Ketone	200 ppm TWA 700 mg/m ³ TWA	150 ppm STEL	150 ppm TWA 530 mg/m ³ TWA
Methyl isobutyl ketone	100 ppm TWA 410 mg/m ³ TWA	75 ppm STEL 20 ppm TWA	75 ppm STEL 300 mg/m ³ STEL 50 ppm TWA 205 mg/m ³ TWA
Ethylbenzene	100 ppm TWA 435 mg/m ³ TWA	20 ppm TWA	125 ppm STEL 545 mg/m ³ STEL 100 ppm TWA 435 mg/m ³ TWA
Carbon Black	3.5 mg/m ³ TWA	3 mg/m ³ TWA	3.5 mg/m ³ TWA 0.1 mg/m ³ TWA

Appropriate engineering controls Not available.

Individual protection measures, such as personal protective equipment

Eye protection Tightly fitting safety goggles.

Skin and body protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Nitrile gloves are recommended.

Respiratory protection None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapors. In confined areas, use an approved air line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits. Standard reference sources regarding industrial ventilation (i.e. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation.

Hygiene measures Remove and wash contaminated clothing before re-use. Wash hands after handling the

product. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Avoid contact with skin and eyes.

Canadian Province Occupational Exposure Limits

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland and Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Acetone	750 ppm STEL 1800 mg/m ³ STEL 500 ppm TWA 1200 mg/m ³ TWA	500 ppm STEL 250 ppm TWA	250 ppm TWA 500 ppm STEL	750 ppm STEL 1782 mg/m ³ STEL 500 ppm TWA 1188 mg/m ³ TWA	500 ppm STEL 250 ppm TWA	500 ppm STEL 250 ppm TWA	500 ppm STEL 250 ppm TWA	500 ppm STEL 250 ppm TWA	1000 ppm STEV 2380 mg/m ³ STEV 500 ppm TWA 1190 mg/m ³ TWA	750 ppm STEL 500 ppm TWA
Propane	1000 ppm TWA	1000 ppm TWA 1000 ppm TWA	-	-	-	-	-	-	1000 ppm TWA 1800 mg/m ³ TWA	1250 ppm STEL 1000 ppm TWA 1000 ppm TWA
N-Butane	1000 ppm TWA	750 ppm STEL 600 ppm TWA 1000 ppm TWA	1000 ppm STEL	800 ppm TWA 1900 mg/m ³ TWA	1000 ppm STEL	1000 ppm STEL	1000 ppm STEL	1000 ppm STEL	800 ppm TWA 1900 mg/m ³ TWA	1250 ppm STEL 1000 ppm TWA 1000 ppm TWA
Barium Sulfate	10 mg/m ³ TWA	10 mg/m ³ TWA 3 mg/m ³ TWA	5 mg/m ³ TWA	10 mg/m ³ TWA	5 mg/m ³ TWA	5 mg/m ³ TWA	5 mg/m ³ TWA	5 mg/m ³ TWA	10 mg/m ³ TWA 5 mg/m ³ TWA	20 mg/m ³ STEL 10 mg/m ³ TWA
Ethylene glycol monopropyl ether	-	-	-	-	-	-	25 ppm TWA 110 mg/m ³ TWA	-	-	-
Isobutyl acetate	150 ppm TWA 713 mg/m ³ TWA	150 ppm TWA	50 ppm TWA 150 ppm STEL	150 ppm TWA 713 mg/m ³ TWA	150 ppm STEL 50 ppm TWA 50 ppm TWA	150 ppm STEL 50 ppm TWA	150 ppm TWA	150 ppm STEL 50 ppm TWA 50 ppm TWA	150 ppm TWA 713 mg/m ³ TWA	188 ppm STEL 150 ppm TWA
n-Butyl acetate	200 ppm STEL 950 mg/m ³ STEL 150 ppm TWA 713 mg/m ³ TWA	20 ppm TWA	50 ppm TWA 150 ppm STEL	200 ppm STEL 950 mg/m ³ STEL 150 ppm TWA 713 mg/m ³ TWA	150 ppm STEL 50 ppm TWA 50 ppm TWA	150 ppm STEL 50 ppm TWA	200 ppm STEL 150 ppm TWA	150 ppm STEL 50 ppm TWA 50 ppm TWA	200 ppm STEV 950 mg/m ³ STEV 150 ppm TWA 713 mg/m ³ TWA	200 ppm STEL 150 ppm TWA
Methyl Propyl Ketone	250 ppm STEL 881 mg/m ³ STEL 200 ppm TWA 705 mg/m ³ TWA	250 ppm STEL 150 ppm TWA	150 ppm STEL	250 ppm STEL 881 mg/m ³ STEL 200 ppm TWA 705 mg/m ³ TWA	150 ppm STEL	150 ppm STEL	150 ppm STEL	150 ppm STEL	150 ppm TWA 530 mg/m ³ TWA	250 ppm STEL 200 ppm TWA
Methyl isobutyl ketone	75 ppm STEL 307 mg/m ³ STEL 50 ppm TWA 205 mg/m ³ TWA	75 ppm STEL 20 ppm TWA	20 ppm TWA 75 ppm STEL	75 ppm STEL 307 mg/m ³ STEL 50 ppm TWA 205 mg/m ³ TWA	75 ppm STEL 20 ppm TWA	75 ppm STEL 20 ppm TWA	75 ppm STEL 20 ppm TWA	75 ppm STEL 20 ppm TWA	75 ppm STEV 307 mg/m ³ STEV 50 ppm TWA 205 mg/m ³ TWA	75 ppm STEL 50 ppm TWA
Ethylbenzene	125 ppm	20 ppm	20 ppm	125 ppm	20 ppm	20 ppm	20 ppm	20 ppm	125 ppm	125 ppm

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland and Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
	STEL 543 mg/m ³ STEL 100 ppm TWA 434 mg/m ³ TWA	TWA	TWA	STEL 543 mg/m ³ STEL 100 ppm TWA 434 mg/m ³ TWA	TWA	TWA	TWA	TWA	STEV 543 mg/m ³ STEV 100 ppm TWA 434 mg/m ³ TWA	STEL 100 ppm TWA
Carbon Black	3.5 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3.5 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3.5 mg/m ³ TWA	7 mg/m ³ STEL 3.5 mg/m ³ TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Aerosol
Color	Black
Odor	Aromatic
Odor threshold	Not available
pH	Not available
Melting point/range °C	Not available
Melting point/range °F	Not available
Boiling point/range °C	-44 °C
Boiling point/range °F	-47 °F
Flash point °C	-19
Flash point °F	-2
Evaporation rate	Not applicable
Flammability (Solid, Gas)	Extremely flammable
Lower explosion limit	1.7 %
Upper explosion limit	10.9 %
Vapor pressure	Not available
Vapor density	Not available
Relative density	0.77-0.85
Solubility	Not available
Partition coefficient (n-octanol/water)	Not available
Autoignition temperature °C	Product is not self-igniting

Autoignition temperature °F Product is not self-igniting

Decomposition temperature °C Not available

Decomposition temperature °F Not available

Viscosity Not available

10. STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

Chemical stability Not available.

Possibility of hazardous reactions None known.

Conditions to avoid Do not puncture, incinerate or expose to temperatures above 120 degrees F. Do not allow to freeze.

Incompatible materials Not available.

Hazardous decomposition products Not available.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure Eyes.

Symptoms Eye irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure Not available.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Acetone	= 50100 mg/m ³ (Rat) 8 h	> 15700 mg/kg (Rabbit)	= 5800 mg/kg (Rat)
Propane	> 800000 ppm (Rat) 15 min	-	-
N-Butane	= 658 g/m ³ (Rat) 4 h	-	-
Barium Sulfate	-	-	= 307000 mg/kg (Rat)
Ethylene glycol monopropyl ether	= 1530 ppm (Rat) 7 h	= 870 mg/kg (Rabbit) = 960 µL/kg (Rabbit)	= 3089 mg/kg (Rat)
Isobutyl acetate	-	> 17400 mg/kg (Rabbit)	= 15400 mg/kg (Rat)
n-Butyl acetate	= 390 ppm (Rat) 4 h	> 17600 mg/kg (Rabbit)	= 10768 mg/kg (Rat)
Methyl Propyl Ketone	2000 - 4000 ppm (Rat) 4 h	= 6480 mg/kg (Rat) = 6500 mg/kg (Rabbit)	= 1600 mg/kg (Rat)
Methyl isobutyl ketone	= 8.2 mg/L (Rat) 4 h	= 3000 mg/kg (Rabbit)	= 2080 mg/kg (Rat)
Ethylbenzene	= 17.4 mg/L (Rat) 4 h > 5.04 mg/L (Rat) 4 h	= 15400 mg/kg (Rabbit) > 2000 mg/kg (Rabbit)	= 3500 mg/kg (Rat) = 4820 mg/kg (Rat)
Carbon Black	-	> 3 g/kg (Rabbit)	> 15400 mg/kg (Rat)

ATEmix (dermal) Not available

ATEmix (oral)	Not available
ATEmix (inhalation-gas)	Not available
ATEmix (inhalation-vapor)	Not available
ATEmix (inhalation-dust/mist)	Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Acetone	A4	-	-	-
Propane	-	-	-	-
N-Butane	-	-	-	-
Barium Sulfate	-	-	-	-
Ethylene glycol monopropyl ether	-	-	-	-
Isobutyl acetate	-	-	-	-
n-Butyl acetate	-	-	-	-
Methyl Propyl Ketone	-	-	-	-
Methyl isobutyl ketone	A3	Group 2B	Listed	-
Ethylbenzene	A3	Group 2B	Listed	-
Carbon Black	A3	Group 2B	Listed	-

Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Acetone	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
Propane	-	-	-	-	-	-
N-Butane	-	-	-	-	-	-
Barium Sulfate	-	-	-	-	-	-
Ethylene glycol monopropyl ether	-	-	-	-	-	-
Isobutyl acetate	-	-	-	-	-	-
n-Butyl acetate	-	-	-	ACGIH A4	-	-
Methyl Propyl Ketone	-	-	-	-	-	-
Methyl isobutyl ketone	-	IARC 2B	ACGIH A3	-	ACGIH A3	-
Ethylbenzene	-	IARC 2B	ACGIH A3	-	ACGIH A3	-
Carbon Black	-	IARC 2B	ACGIH A3	ACGIH A4	ACGIH A3	-

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish
Acetone	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50
Propane	-	-

Chemical name	Algae/aquatic plants	Fish
N-Butane	-	-
Barium Sulfate	-	-
Ethylene glycol monopropyl ether	-	-
Isobutyl acetate	-	101: 48 h Leuciscus idus melanotus mg/L LC50 static 101 - 123: 48 h Leuciscus idus melanotus mg/L LC50 flow-through
n-Butyl acetate	674.7: 72 h Desmodemus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static
Methyl Propyl Ketone	-	1190 - 1290: 96 h Pimephales promelas mg/L LC50 flow-through
Methyl isobutyl ketone	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through
Ethylbenzene	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 11: 72 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through
Carbon Black	-	-

Persistence and degradability Not expected to be rapidly degradable.

Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)
Acetone 67-64-1	67-64-1	-0.24
Propane 74-98-6	74-98-6	2.3 <=2.8
N-Butane 106-97-8	106-97-8	2.89 <=2.8
Barium Sulfate 7727-43-7	7727-43-7	-
Ethylene glycol monopropyl ether 2807-30-9	2807-30-9	-
Isobutyl acetate 110-19-0	110-19-0	1.72
n-Butyl acetate 123-86-4	123-86-4	1.81 23 °C
Methyl Propyl Ketone 107-87-9	107-87-9	0.91
Methyl isobutyl ketone 108-10-1	108-10-1	1.19
Ethylbenzene 100-41-4	100-41-4	3.2
Carbon Black 1333-86-4	1333-86-4	-

Mobility in soil Not available.

Other adverse effects Hazardous for water, do not empty into drains.

13. DISPOSAL CONSIDERATIONS

Disposal information	Dispose of all product, residues and clean-up materials in accordance with local, state, and federal regulations. Do not puncture, incinerate, or crush. Do not heat or cut empty containers with electric or gas torches.
Contaminated packaging	Please recycle empty container whenever possible.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

ID-No	UN1950
Proper shipping name	Aerosols, flammable
Hazard Class(es)	2.1
Special Provisions	LTD QTY

TDG

ID-No	UN1950
Proper shipping name	Aerosols, flammable
Hazard Class(es)	2.1
Special Provisions	LTD QTY

IATA

ID-No	UN1950
Proper shipping name	Aerosols, flammable
Hazard Class(es)	2.1
Special Provisions	LTD QTY

IMDG/IMO

ID-No	UN1950
Proper shipping name	Aerosols, flammable
Hazard Class(es)	2.1
EmS No	F-D, S-U
Special Provisions	LTD QTY, 1L

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Acetone	67-64-1	-	-	-
Propane	74-98-6	-	-	-
N-Butane	106-97-8	-	-	-
Barium Sulfate	7727-43-7	-	-	-
Ethylene glycol monopropyl ether	2807-30-9	-	-	-
Isobutyl acetate	110-19-0	-	-	-
n-Butyl acetate	123-86-4	-	-	-
Methyl Propyl Ketone	107-87-9	-	-	-
Methyl isobutyl ketone	108-10-1	-	-	-
Ethylbenzene	100-41-4	-	-	-
Carbon Black	1333-86-4	-	-	-

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Acetone	67-64-1	X	X	X
Propane	74-98-6	X	X	X
N-Butane	106-97-8	X	X	X
Barium Sulfate	7727-43-7	X	X	X
Ethylene glycol monopropyl ether	2807-30-9	-	X	X
Isobutyl acetate	110-19-0	X	X	X
n-Butyl acetate	123-86-4	X	X	X
Methyl Propyl Ketone	107-87-9	X	X	X
Methyl isobutyl ketone	108-10-1	X	X	X
Ethylbenzene	100-41-4	X	X	X
Carbon Black	1333-86-4	X	X	X

California Prop. 65

Chemical name	CAS-No	California Prop. 65
Acetone	67-64-1	-
Propane	74-98-6	-
N-Butane	106-97-8	-
Barium Sulfate	7727-43-7	-
Ethylene glycol monopropyl ether	2807-30-9	-
Isobutyl acetate	110-19-0	-
n-Butyl acetate	123-86-4	-
Methyl Propyl Ketone	107-87-9	-
Methyl isobutyl ketone	108-10-1	Carcinogen Developmental
Ethylbenzene	100-41-4	Carcinogen
Carbon Black	1333-86-4	Carcinogen

California Proposition 65

WARNING: This product contains a chemical(s) known to the state of California to cause cancer, birth defects or other reproductive harm

U.S. Federal Regulations

US EPA SARA 313

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Acetone	67-64-1	5000 lb 2270 kg	-
Propane	74-98-6	-	-
N-Butane	106-97-8	-	-
Barium Sulfate	7727-43-7	-	1.0 %
Ethylene glycol monopropyl ether	2807-30-9	-	1.0 %
Isobutyl acetate	110-19-0	5000 lb 2270 kg	-
n-Butyl acetate	123-86-4	5000 lb 2270 kg	-
Methyl Propyl Ketone	107-87-9	-	-
Methyl isobutyl ketone	108-10-1	5000 lb 2270 kg	1.0 %

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Ethylbenzene	100-41-4	1000 lb 454 kg	0.1 %
Carbon Black	1333-86-4	-	-

**US EPA SARA 311/312
hazardous categorization**

Not available

International inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA 8(b)), Canada (DSL/NDSL) or are exempt.

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Acetone	X	X	-
Propane	X	X	-
N-Butane	X	X	-
Barium Sulfate	X	X	-
Ethylene glycol monopropyl ether	X	X	-
Isobutyl acetate	X	X	-
n-Butyl acetate	X	X	-
Methyl Propyl Ketone	X	X	-
Methyl isobutyl ketone	X	X	-
Ethylbenzene	X	X	-
Carbon Black	X	X	-

Legend X - Listed

16. OTHER INFORMATION**NFPA**

Health	Not available
Flammability	Not available
Instability	Not available

HMIS

Health	Not available
Flammability	Not available
Physical hazards	Not available

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs**Issue date** 19-Jul-2018**Revision date** 19-Jul-2018**Revision note**

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
ATE (Average Toxicity Estimate)
DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
HMIS (Hazardous Materials Identification System)
IARC (International Agency for Research on Cancer)
IATA (International Air Transport Association)
IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
NFPA (National Fire Protection Association)
NTP (National Toxicology Program)
OEL (Occupational Exposure Level)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
TSCA (Toxic Substance Control Act)
USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet