

MATERIAL SAFETY DATA SHEET

SPOTCHECK ® PENETRANT SKL-WP

1. IDENTIFICATION

COMPANY : ITW INDIA PRIVATE LIMITED

ADDRESS : PLOT NO 51, 52,207 & 208, PHASE - 2, IDA

TSIIC, PASHAMMYLARAM, MEDAK – 502 307, TELANGANA

INDIA.

TELEPHONE : 91 – 8455 – 224710

FAX : 91 – 8455 – 224709

PRODUCT USE : Visible inspection penetrant

PACKAGES : Aerosol, 1 L, 5 L & 200

NFPA Rating : Health 1, Flammability 1(Aerosol Flammability 4), Reactivity 0.

Revision Date : September 24, 2014.

2. HAZARDOUS INGREDIENTS

Ingredient	Wt/Wt%	CAS#	<u>TLV</u>	<u>PEL</u>	LD 50	LC 50
Paraffin's (petroleum), normal C5 – C20	30 -60%	64771-72-8	NA	NA	NA	NA
Poly (oxy – 1, 2 – ethanediyl-nonylphenyl)						
-hydroxyl:	30 - 60%	9016-45-9	NA	NA	2g/kg (oral/rat)	NA
Heavy aromatic solvent naphtha:	0.5 - 1.5%	64742-94-5	NA	NA	1.8g/kg(oral/rat)	NA
Isobutane (propellant):	30%	75 - 28-5	NA	NA	NA	NA

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Bland, oily liquid which may irritate the skin and eyes. Bulk material is difficult to ignite, but will burn vigorously if engulfed in fire. Aerosol is extremely flammable

POTENTIAL HEALTH EFFECTS

Skin Contact : Can irritate by removing natural skin oils on long or repeated exposures

Eyes : Irritating.

Inhalation : Not significant at room temperatures. When heated or sprayed, vapors may cause dizziness or nausea

Ingestion : Not significant in small(mouthful) quantities

Medical conditions known to be aggravated by exposure to product: None

4. FIRST AID

Skin Contact : Wash off with soap water .Use soothing lotion

Eyes : Rinse carefully under upper and lower eyelids using plenty of water

Inhalation : Remove to fresh air if dizzy or nauseated

Ingestion : Do not induce vomiting. Accidental ingestion of a small mouthful quantity is not expected to cause significant harm

NOTE: In all severe cases, contact physician immediately.

5. **FIRE HAZARD**

Conditions of flammability : Aerosol : Spraying near an ignition source will ignite spray mist

Bulk: None unless heated over 93 deg C near ignition source

Flash point : Min 93 deg C (PMCC)

Flammable limits in air : 1 to 6%

Extinguishing media : Carbon dioxide , Foam

Special fire fighting procedures : Keep containers cool with water spray. Donot spray water directly on burning SKL-WP.lt

may float and spread the fire

Hazardous combustion products : Smoke, soot, oxides or carbon and nitrogen

Unusual fire hazards : Aerosol containers may burst at temperatures over 54 deg C and spray contents into a fire

6. ACCIDENTAL RELEASE MEASURES

Mop up or Sweep up with absorbent (For disposal see Section 13)

MSDS/SKL WP/23 dated 07/2015 Page 1 of 2



ITW India Private Limited, Plot no:51, 52, 207 & 208, Phase -2, IDA, TSIIC, Pashammylaram, Medak Dist.-502307, Telangana State, India Telephone: +91 8455 224710. Facsimile: +91 8455 224709. E-mail: magnafluxinfo@magnafluxindia.com, Website: www.magnaflux.com



7. HANDLING AND STORAGE

Store away from heat source. Avoid eye contact. Avoid repeated or prolonged skin contact. Avoid breathing spray mist.Donot spray around arcs or flames

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Controls : None,unless sprayed. Use where ventilation will carry spray mist away from occupied areas
Personal protection : Wear safety glasses to protect eyes. Wear nitrile rubber gloves if hand exposure is unavoidable.

Respirator with filter if sprayed in enclosed unventilated space.

9. PHYSICAL PROPERTIES

Initial boiling point (bulk) : Min 235 deg C Vapor pressure : Aerosol 60 psi, Bulk <0.1 mm @ 24 deg C

Percent volatile : None (30% in aerosol) Vapor density : Heavier than air Density/sp. gravity : 0.89 Evaporation rate : Negligible

Water solubility : 0 (emulsifies into water) Appearance : Dark Red oily liquid pH : Neutral Odor : Mild oily odour

10. STABILITY AND REACTIVITY

Stability : Stable Incompatibility : None

Hazardous decomposition products : Soot, oxides of carbon and nitrogen when burning

Reactivity : None

11. TOXICOLOGICAL INFORMATION

Carcinogenicity : Contains no known or suspected carcinogens listed with OSHA, IARC, NTP or ACGIH

Threshold limit value : 5mg/cubic meter for oily mist

WHMIS information (Canada) : According to available information, the ingredients have not been found to show reproductive toxicity,

Teratogenicity, Mutagenicity, Skin sensitization, or Synergistic toxic effects with other material.

12. ECOLOGICAL INFORMATION

No data is available on SKL-WP. It emulsifies into water and is bio degradable. Its low bulk vapor pressure may exempt it from VOC restrictions. The hydrocarbon propellant is not an ozone depleter.

13. DISPOSAL

As a non-hazardous oily waste, incinerate or send to waste handler who can blend it into secondary fuels. Empty aerosol cans before disposal. Non hazardous waste as per classification in The Hazardous Wastes (Management and Handling) Rules 1989, of CPB,India

RCRA: Not a hazardous waste U.S EPA Waste number: None

14. TRANSPORTATION

U.S.DOT: 49 CFR 172.101 Hazardous Material Table

Non-aerosol Aerosol

Proper shipping name : None, not restricted Consumer commodity

Hazard class or division : None ORM-D Identification No. : None None Packing Group : None None

15. REGULATORY INFORMATION

TSCA : All ingredients are listed in TSCA inventory.

CERCLA : Not reportable

SARA TITLE III, Section 313 : No reportable ingredients
California Proposition 65 : Contains nothing on this list

16. OTHER INFORMATION

Revision Statement : New logo & address
Prepared by : Sunil N S, Q.C Dept..

MSDS/SKL WP/23 dated 07/2015 Page 2 of 2



ITW India Private Limited, Plot no:51, 52, 207 & 208, Phase -2, IDA, TSIIC, Pashammylaram, Medak Dist.-502307, Telangana State, India Telephone: +91 8455 224710. Facsimile: +91 8455 224709. E-mail: magnafluxinfo@magnafluxindia.com, Website: www.magnaflux.com