



Revision Number: 004.4

Issue date: 02/17/2015

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Loctite® Naval Jelly® Rust Dissolver  
**Product type:** Rust dissolver  
**Restriction of Use:** None identified  
**Company address:**  
 Henkel Corporation  
 One Henkel Way  
 Rocky Hill, Connecticut 06067

**IDH number:** 1381191  
**Item number:** 1381191  
**Region:** United States  
**Contact information:**  
 Telephone: (860) 571-5100  
 MEDICAL EMERGENCY Phone: Poison Control Center  
 1-877-671-4608 (toll free) or 1-303-592-1711  
 TRANSPORT EMERGENCY Phone: CHEMTREC  
 1-800-424-9300 (toll free) or 1-703-527-3887  
 Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** MAY BE CORROSIVE TO METALS.  
 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.  
 MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
CORROSIVE TO METALS	1
SKIN CORROSION	1A
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

### PICTOGRAM(S)



### Precautionary Statements

**Prevention:** Keep only in original container. Do not breathe vapors, mist, or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.  
**Response:** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.  
**Storage:** Store locked up. Store in corrosive resistant container with a resistant inner liner.  
**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

2 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Phosphoric acid	7664-38-2	10 - 30
2-Propanol	67-63-0	1 - 5
Xanthan gum	11138-66-2	1 - 5
Sulfuric acid	7664-93-9	0.1 - 1
Silica, amorphous, fumed, crystal-free	112945-52-5	0.1 - 1
Diliron trioxide	1309-37-1	0.1 - 1
Magnesium oxide	1309-48-4	0.1 - 1
Aluminium oxide	1344-28-1	0.1 - 1
Alcohols, C11-14-Iso-, C13 rich, EO~	78330-21-9	0.1 - 1

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Not flammable, however Hydrogen gas may be liberated if product contacts powdered metals or metals above 185°F.
Hazardous combustion products:	Hydrogen.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
----------------------------	---

**Clean-up methods:**

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Flush with water. Neutralize acid using lime or a lime based agent compatible with the product. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:**

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

**Storage:**

Keep from freezing. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Phosphoric acid	3 mg/m3 STEL 1 mg/m3 TWA	1 mg/m3 PEL	None	None
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
Xanthan gum	None	None	None	None
Sulfuric acid	0.2 mg/m3 TWA Thoracic fraction.	1 mg/m3 PEL	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Diiron trioxide	5 mg/m3 TWA Respirable fraction.	10 mg/m3 PEL Fume.	None	None
Magnesium oxide	10 mg/m3 TWA Inhalable fraction.	15 mg/m3 PEL Total particulate.	None	None
Aluminium oxide	1 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Alcohols, C11-14-iso-, C13 rich, EO~	None	None	None	None

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:**

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Gel
Color:	Pink
Odor:	Lime
Odor threshold:	Not available.
pH:	1.5 - 2.5
Vapor pressure:	Not available.
Boiling point/range:	212 °F (100°C) None Approximately
Melting point/ range:	Not applicable
Specific gravity:	1.191
Vapor density:	Not available.
Flash point:	Not determinable.
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Soluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	2.4 %; 28.6 g/l (calculated)
Viscosity:	Not available.
Decomposition temperature:	Not available.

## 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Hydrogen, by reaction with metals.
Incompatible materials:	Caustics. Powdered metals.
Reactivity:	Not available.
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
------------------------------	-----------------------------------

## Potential Health Effects/Symptoms

**Inhalation:** Causes respiratory tract irritation. Respiratory tract burns.  
**Skin contact:** Causes skin irritation. Causes skin burns. May cause allergic skin reaction.  
**Eye contact:** Causes serious eye damage. Causes eye irritation. May cause eye burns.  
**Ingestion:** Harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Phosphoric acid	Oral LD50 (RAT) = 1,530 mg/kg Dermal LD50 (RABBIT) = 2,740 mg/kg	Irritant, Corrosive
2-Propanol	Oral LD50 (RAT) = 5,045 mg/kg Oral LD50 (RABBIT) = 6,410 mg/kg Oral LD50 (RAT) = 4.7 g/kg Oral LD50 (RABBIT) = 8.0 g/kg Oral LD50 (RABBIT) = 5.03 g/kg Dermal LD50 (RABBIT) = 12,800 mg/kg	Allergen, Blood, Brain, Central nervous system, Irritant, Kidney, Liver, Spleen
Xanthan gum	None	Irritant
Sulfuric acid	Inhalation LC50 (RAT, 1 h) = 347 mg/l	Carcinogen, Corrosive, Irritant, Lung
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
Dilron trioxide	None	Allergen, Cardiac, Central nervous system, Irritant, Kidney, Liver, Lung
Magnesium oxide	None	Blood, Central nervous system, Immune system, Irritant
Aluminium oxide	None	Irritant, Nuisance dust, Corrosive
Alcohols, C11-14-Iso-, C13 rich, EO~	None	Central nervous system, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Phosphoric acid	No	No	No
2-Propanol	No	No	No
Xanthan gum	No	No	No
Sulfuric acid	Known To Be Human Carcinogen.	Group 1	No
Silica, amorphous, fumed, crystal-free	No	No	No
Dilron trioxide	No	No	No
Magnesium oxide	No	No	No
Aluminium oxide	No	No	No
Alcohols, C11-14-Iso-, C13 rich, EO~	No	No	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.  
Hazardous waste number: Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Phosphoric acid solution  
Hazard class or division: 8  
Identification number: UN 1805  
Packing group: III  
DOT Hazardous Substance(s): Phosphoric acid

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Phosphoric acid, solution  
Hazard class or division: 8  
Identification number: UN 1805  
Packing group: III

#### Water Transportation (IMO/IMDG)

Proper shipping name: PHOSPHORIC ACID SOLUTION  
Hazard class or division: 8  
Identification number: UN 1805  
Packing group: III

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
TSCA 12 (b) Export Notification: None above reporting de minimis  
CERCLA/SARA Section 302 EHS: Sulfuric acid (CAS# 7664-93-9).  
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health  
CERCLA/SARA Section 313: None above reporting de minimis  
CERCLA Reportable quantity: Phosphoric acid (CAS# 7664-38-2) 5,000 lbs. (2,270 kg)  
2-Propanol (CAS# 67-63-0) 100 lbs. (45.4 kg)  
California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

#### Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist  
Issue date: 02/17/2015

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

