



SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : SP1000 Snow Impression Wax
Product code : SP1000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Crime Scene Investigation

1.3. Details of the supplier of the safety data sheet

SIRCHIE Finger Print Laboratories
100 Hunter Place
Youngsville, NC 27596 - USA
T 919-554-2244; 800-356-7311 - F 919-554-2266; 800-899-8181
<http://www.sirchie.com>

1.4. Emergency telephone number

Emergency number : 1.800.424.9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Carc. 2 H351
Repr. 2 H361
STOT SE 3 H336
STOT RE 2 H373

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe fume, gas, mist, spray, vapors
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash all exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, protective gloves
P302+P352 - If on skin: Wash with plenty of water/...

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a poison center/doctor/... if you feel unwell
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment (see information on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use CO₂, dry chemical, foam, water spray to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
2-propanol	(CAS No) 67-63-0	34	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
propane	(CAS No) 74-98-6	14	Compressed gas, H280
butane, liquefied, under pressure	(CAS No) 106-97-8	13	Flam. Gas 1, H220 Compressed gas, H280
toluene	(CAS No) 108-88-3	10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
isobutyl acetate	(CAS No) 110-19-0	9	Flam. Liq. 2, H225
acetone	(CAS No) 67-64-1	5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
chalk	(CAS No) 1317-65-3	1	Not classified
ethylbenzene	(CAS No) 100-41-4	1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351
xylene, mixture of isomers	(CAS No) 1330-20-7	1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
talc	(CAS No) 14807-96-6	1	Not classified

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SP1000 Snow Impression Wax		
ACGIH	Not applicable	
OSHA	Not applicable	
2-propanol (67-63-0)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	200 ppm

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-propanol (67-63-0)		
OSHA	Not applicable	

acetone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	500 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

butane, liquefied, under pressure (106-97-8)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	Not applicable	

chalk (1317-65-3)		
ACGIH	Not applicable	
OSHA	Not applicable	

ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
OSHA	Not applicable	

xylene, mixture of isomers (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
OSHA	Not applicable	

isobutyl acetate (110-19-0)		
ACGIH	ACGIH TWA (ppm)	150 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	Not applicable	

propane (74-98-6)		
ACGIH	Not applicable	
OSHA	Not applicable	

talc (14807-96-6)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
OSHA	Not applicable	

toluene (108-88-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
OSHA	Not applicable	

8.2. Exposure controls

Personal protective equipment

: Gas mask. Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection

: Wear protective gloves.

Eye protection

: Chemical goggles or safety glasses.

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection : Wear appropriate mask.
Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid under pressure.
Color : Dark red to red-brown
Odor : Irritating/pungent odour
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Vapor pressure : No data available
Relative density : No data available
Relative vapor density at 20 °C : No data available
Solubility : Insoluble in water.
Water: Solubility in water of component(s) of the mixture :
• : • : • : 0.0061 g/100ml • : < 0.1 g/100ml • : 0.02 g/100ml • : < 0.02 g/100ml • : 0.7 g/100ml • : 0.0061 g/100ml • : < 0.1 g/100ml • : 0.05 g/100ml
Log Pow : No data available
Log Kow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. High temperature. Open flame. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

2-propanol (67-63-0)	
LD50 oral rat	5045 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 5840 mg/kg bodyweight; Rat)
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)
ATE US (oral)	5045.000 mg/kg body weight
ATE US (dermal)	12870.000 mg/kg body weight
ATE US (vapors)	73.000 mg/l/4h
ATE US (dust, mist)	73.000 mg/l/4h
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
ATE US (oral)	5800.000 mg/kg body weight
ATE US (dermal)	20000.000 mg/kg body weight
ATE US (gases)	30000.000 ppmV/4h
ATE US (vapors)	71.000 mg/l/4h
ATE US (dust, mist)	71.000 mg/l/4h
butane, liquefied, under pressure (106-97-8)	
LC50 inhalation rat (mg/l)	658 mg/l/4h (Rat; Literature)
LC50 inhalation rat (ppm)	276000 ppm/4h (Rat; Literature)
ATE US (gases)	276000.000 ppmV/4h
ATE US (vapors)	658.000 mg/l/4h
ATE US (dust, mist)	658.000 mg/l/4h
chalk (1317-65-3)	
LD50 oral rat	6450 mg/kg (Rat; Literature study)
ATE US (oral)	6450.000 mg/kg body weight
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
ATE US (oral)	3500.000 mg/kg body weight
ATE US (dermal)	15415.000 mg/kg body weight
ATE US (gases)	4000.000 ppmV/4h
ATE US (vapors)	17.800 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h
xylene, mixture of isomers (1330-20-7)	
LD50 oral rat	3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
ATE US (oral)	3523.000 mg/kg body weight
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

isobutyl acetate (110-19-0)	
LD50 oral rat	13400 mg/kg (Rat)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit)
ATE US (oral)	13400.000 mg/kg body weight

propane (74-98-6)	
LC50 inhalation rat (mg/l)	513 mg/l/4h (Rat; Literature)
LC50 inhalation rat (ppm)	280000 ppm/4h (Rat; Literature)
ATE US (gases)	280000.000 ppmV/4h
ATE US (vapors)	513.000 mg/l/4h
ATE US (dust, mist)	513.000 mg/l/4h

toluene (108-88-3)	
LD50 oral rat	> 2000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	12223 mg/kg (Rabbit; Literature study; Other; >5000 mg/kg bodyweight; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 20 mg/l/4h (Rat; Literature study)
ATE US (dermal)	12223.000 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Based on available data, the classification criteria are not met
Carcinogenicity : Suspected of causing cancer.

2-propanol (67-63-0)	
IARC group	3 - Not classifiable

ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

xylene, mixture of isomers (1330-20-7)	
IARC group	3 - Not classifiable

talc (14807-96-6)	
IARC group	3 - Not classifiable

toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
Based on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

2-propanol (67-63-0)	
LC50 fish 1	4200 mg/l (96 h; Rasbora heteromorpha; Flow-through system)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna)
LC50 fish 2	9640 mg/l (96 h; Pimephales promelas; Lethal)

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-propanol (67-63-0)	
EC50 Daphnia 2	13299 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
Threshold limit algae 2	1800 mg/l (72 h; Algae; Cell numbers)
acetone (67-64-1)	
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)
TLM fish 2	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)
butane, liquefied, under pressure (106-97-8)	
LC50 fish 1	> 1000 mg/l (96 h; Pimephales promelas)
LC50 fish 2	6.0 mg/l (96 h; Pisces)
TLM fish 1	1000 mg/l (96 h; Pisces)
Threshold limit other aquatic organisms 1	0.6 - 0.9,504 h; Daphnia magna
Threshold limit algae 1	0.88 - 1.76,Algae
ethylbenzene (100-41-4)	
LC50 fish 1	9.09 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	77 mg/l (24 h; Daphnia magna)
EC50 other aquatic organisms 1	48 mg/l (72 h; Scenedesmus subspicatus)
LC50 fish 2	4.2 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	75 mg/l (48 h; Daphnia magna)
TLM fish 1	29 ppm (96 h; Lepomis macrochirus; Hard water)
TLM fish 2	42.3 mg/l (96 h; Pimephales promelas)
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 1	> 160 mg/l (192 h; Scenedesmus quadricauda; Toxicity test)
Threshold limit algae 2	33 mg/l (192 h; Microcystis aeruginosa; Toxicity test)
xylene, mixture of isomers (1330-20-7)	
LC50 fish 1	13.5 mg/l (96 h; Lepomis macrochirus; Lethal)
EC50 Daphnia 1	150 mg/l (24 h; Daphnia magna)
LC50 fish 2	3.77 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	7.4 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	72 mg/l (336 h; Selenastrum capricornutum; Growth)
Threshold limit algae 2	10 mg/l (72 h; Skeletonema costatum)
isobutyl acetate (110-19-0)	
LC50 fish 1	100 mg/l (96 h; Lepomis macrochirus)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	44 mg/l (48 h; Daphnia magna; Nocivity test)
LC50 fish 2	101 mg/l (48 h; Leuciscus idus)
EC50 Daphnia 2	146 - 192 mg/l (Daphnia magna)
TLM fish 1	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	10 - 100,96 h; Protozoa
Threshold limit other aquatic organisms 2	411 mg/l (72 h)
Threshold limit algae 1	205 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	80 mg/l (192 h; Scenedesmus quadricauda)
propane (74-98-6)	
LC50 fish 1	13.0 mg/l (96 h; Pisces)
EC50 Daphnia 1	10 - 100 mg/l (48 h; Invertebrata)
EC50 other aquatic organisms 1	10 - 100 mg/l (Activated sludge; Estimated value)
LC50 fish 2	> 1000 mg/l (96 h; Pisces)

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

propane (74-98-6)	
EC50 Daphnia 2	7 mg/l (Daphnia magna)
TLM fish 1	17.8 - 19.7,96 h; Pimephales promelas
Threshold limit algae 1	1.45 - 4.53,72 h; Algae
Threshold limit algae 2	8 mg/l (72 h; Algae)
talc (14807-96-6)	
LC50 fish 1	> 100 g/l (24 h; Brachydanio rerio; Intermittent flow)
toluene (108-88-3)	
LC50 fish 1	24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	84 mg/l (24 h; Daphnia magna; Locomotor effect)
LC50 fish 2	13 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 2	11.5 - 19.6 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 400 mg/l (168 h; Scenedesmus quadricauda; Toxicity test)
Threshold limit algae 2	105 mg/l (192 h; Microcystis aeruginosa)

12.2. Persistence and degradability

SP1000 Snow Impression Wax	
Persistence and degradability	Not established.
2-propanol (67-63-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.40 g O ₂ /g substance
BOD (% of ThOD)	0.49 % ThOD
acetone (67-64-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.20 g O ₂ /g substance
BOD (% of ThOD)	(20 day(s)) 0.872
butane, liquefied, under pressure (106-97-8)	
Persistence and degradability	Readily biodegradable in water.
chalk (1317-65-3)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	(20 day(s)) 45.4
xylene, mixture of isomers (1330-20-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air.

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

isobutyl acetate (110-19-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photolysis in the air.
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.60 % ThOD
propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
talc (14807-96-6)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69 % ThOD

12.3. Bioaccumulative potential

SP1000 Snow Impression Wax	
Bioaccumulative potential	Not established.
2-propanol (67-63-0)	
Log Pow	0.05 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
acetone (67-64-1)	
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3
Log Pow	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.
butane, liquefied, under pressure (106-97-8)	
Log Pow	2.89 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
chalk (1317-65-3)	
Bioaccumulative potential	No bioaccumulation data available.
ethylbenzene (100-41-4)	
BCF fish 1	1 (6 weeks; Oncorhynchus kisutch)
BCF fish 2	15 - 79 (Carassius auratus)
BCF other aquatic organisms 1	4.68 (Lamellibranchiata)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
xylene, mixture of isomers (1330-20-7)	
BCF fish 1	15 8 weeks; Salmo gairdneri (Oncorhynchus mykiss)
BCF fish 2	7 - 26 (8 weeks; Oncorhynchus mykiss)
Log Pow	3.2 (Conclusion by analogy; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
isobutyl acetate (110-19-0)	
BCF fish 1	4 - 9.7 (Pisces; Estimated value)
Log Pow	1.59 - 1.78
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

propane (74-98-6)	
BCF fish 1	9 - 25 (Pisces)
Log Pow	2.28 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

toluene (108-88-3)	
BCF fish 1	13.2 (Anguilla japonica)
BCF fish 2	90 (72 h; Leuciscus idus)
BCF other aquatic organisms 1	380 (24 h; Chlorella sp.; Fresh weight)
BCF other aquatic organisms 2	4.2 (Mytilus edulis; Fresh weight)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

2-propanol (67-63-0)	
Surface tension	0.021 N/m (25 °C)

acetone (67-64-1)	
Surface tension	0.0237 N/m

butane, liquefied, under pressure (106-97-8)	
Surface tension	< 0.1 N/m (0 °C)

ethylbenzene (100-41-4)	
Surface tension	0.029 N/m

xylene, mixture of isomers (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

isobutyl acetate (110-19-0)	
Surface tension	0.024 N/m (20 °C)

propane (74-98-6)	
Surface tension	0.016 N/m (-47 °C)

toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols, flammable (FLAMMABLE GAS), 2.1, II

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols, flammable
FLAMMABLE GAS

Department of Transportation (DOT) Hazard Classes : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 2.1 - Flammable gas



Packing group (DOT) : II - Medium Danger

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN UN 1950

Transport by sea

No additional information available

Air transport

UN-No.(IATA) : UN1950
Proper Shipping Name (IATA) : Aerosols, flammable
Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

15.1. US Federal regulations

SP1000 Snow Impression Wax

Listed on United States SARA Section 313
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.3; R63

F+; R12

Xn; R65

Xn; R48/20

Xi; R36

R67

Full text of R-phrases: see section 16

National regulations

No additional information available

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

SP1000 Snow Impression Wax()	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

SECTION 16: Other information

Indication of changes	: Revision - See : *.
Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Training advice	: Normal use of this product shall imply use in accordance with the instructions on the packaging. Keep in tightly closed container. Keep cool and dry. Avoid all ignition sources - heat, open flame, sparks. Avoid incompatible materials. Avoid dust creation and accumulation. Avoid inhalation and ingestion. Avoid contact with eyes. Wash thoroughly after handling.
Other information	: None.

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

SP1000 Snow Impression Wax

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Personal Protection

: G

G - Safety glasses, Gloves, Vapor respirator

SDS US (GHS HazCom 2012)

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.