

Section One: Identification

Sanford, L.P.
2707 Butterfield Road
Oak Brook, IL 60523 USA
800-323-0749 or 630-481-2000

EMERGENCY MEDICAL NUMBER:

888-786-0972

Product Name: Liquid Paper Correction Pens

Colors: White

Includes: Correction Pen and Correction Pen Mini

Section Two: Hazard Identification

Warning: Content is flammable. Do not use near heat or sources of ignition. May cause eye, skin or respiratory tract irritation. Avoid contact with eyes & skin. May cause gastrointestinal tract irritation. Do not ingest. Use only with proper ventilation.

Section Three: Composition

Methylcyclohexane (108-87-2), titanium dioxide (13463-67-7), resins, colorants, fragrances

Section Four: First Aid Measures

Inhalation: This product is considered safe under normal use conditions.

Skin Contact: This product is considered safe under normal use conditions.

Eye Contact: This product is considered safe under normal use conditions.

Ingestion: This product is considered safe under normal use conditions.

Section Five: Fire Fighting Measures

Flash Point: 22.5F (Closed Cup)

Flammability Limits (% by volume): Lower: 1.2% Upper: 6.7%

Extinguishing Media: Dry chemical, foam, carbon dioxide

Special Fire Fighting Measures: In fires involving large quantities, use self-contained breathing apparatus. Cool fire-exposed containers with water fog/spray.

Unusual Fire and Explosion Hazards: Product is flammable. May produce hazardous decomposition products.

Section Six: Accidental Release Measures

In Case of Spill or Accidental Release: Wipe up with absorbent material.

Section Seven: Handling and Storage

Handling: Do not use near heat or flame.

Storage: Do not store near heat or flame.

Section Eight: Exposure Controls and Personal Protection

Eye Protection: None under normal use conditions.

Clothing: None under normal use conditions.

Respirator: None under normal use conditions.

Ventilation: None under normal use conditions.

Life Cycle Status: Released

Iteration: 4.1

Section Nine: Physical and Chemical Properties

For product unless otherwise specified:

Boiling Point: 212F
 Specific Gravity: 1.16
 Vapor Pressure: 83 mm Hg at 100F
 Solubility in Water: Negligible
 Evaporation Rate: >1
 Appearance/Odor: White fluid; solvent odor

Section Ten: Stability and Reactivity

Stability: Stable
 Conditions to Avoid: Open flames or other ignition sources
 Chemical Incompatibility: Strong oxidizers
 Hazardous Decomposition: May produce oxides of carbon, nitrogen, and various hydrocarbons in fire situation.
 Hazardous Polymerization: Will not occur

Section Eleven: Toxicological Information

See Section Two: Hazard Identification for any hazards

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations.

Section Fourteen: Transport Information

Refer to Shipping Paper, if applicable.

Section Fifteen: Regulatory Information

TSCA: The product listed on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory. All ingredients used to manufacture this product are listed on the TSCA Inventory

Section Sixteen: Other Information

HMIS Code	
Health	2
Flammability	3
Reactivity	0
Personal Protection	N/A

0=Minimal / 4 = Severe

NewellRubbermaid, Inc (Sanford L.P) has been advised by Counsel that the OSHA Hazard Communication Standard and the Health Canada Workplace Hazardous Materials Information Standard do not apply to the product described in this Material Safety Data Sheet. The reasons for the exemptions are contained in 29 CFR 1910.1200(b)(6)(ix) as amended Sept 14, 2009 per the Code of Federal Regulations and also Canadian Hazardous Products Act part 12 section (f) as amended June 1, 2009. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by nor is this MSDS meant to comply with all requirements of the hazard communication standards.

*Life Cycle State: Released
 Iteration: 4.1*

Modify Timestamp: 2014-04-01 15:01:40 CDT