



# AmerSeal Premium Heavy Duty Tire Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/01/2015      Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : AmerSeal Premium Heavy Duty Tire Sealant

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Tire Sealant

#### 1.3. Details of the supplier of the safety data sheet

American Sealants Company Inc.  
1808 Limestone Road  
Clay Center, Kansas 67432 - USA  
T 785-632-2322  
<http://www.amerseal.com>

#### 1.4. Emergency telephone number

Emergency number : 785-632-2322

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Acute Tox. 4 (Oral) H302  
Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : H302 - Harmful if swallowed

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P264 - Wash hands and other exposed areas thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P280 - Wear protective gloves/protective clothing/eye protection  
P301 + P312 - If swallowed: Call a poison center/doctor if you feel unwell  
P308 + P313 - If exposed or concerned: Get medical advice/attention

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

None of the ingredients are of unknown toxicity.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable – the product is a mixture

# AmerSeal Premium Heavy Duty Tire Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 3.2. Mixture

Name	Product identifier	%
Ethylene glycol	(CAS No) 107-21-1	46.9
Titanium dioxide	(CAS No) 13463-67-7	0.61
Attapulgate	(CAS No) 12174-11-7	0.56

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician. Rinse mouth.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.
-----------------------------------	--

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Product is not combustible; use media suitable for surrounding flammable material such as: Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
------------	--

### 5.3. Advice for firefighters

Firefighting instructions	: Product is not combustible; use water spray or fog for cooling exposed containers located in a fire area. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

#### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# AmerSeal Premium Heavy Duty Tire Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
- Hygiene measures : Wash hands and other exposed areas thoroughly after handling. Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place. Keep container tightly closed.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : None known.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

AmerSeal Premium Heavy Duty Tire Sealant		
ACGIH	Not applicable	
OSHA	Not applicable	
Ethylene glycol (107-21-1)		
ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
OSHA	Not applicable	
Titanium dioxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
Attapulgate (12174-11-7)		
ACGIH	Not applicable	
OSHA	Not applicable	

#### 8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Not typically required if exposures are maintained below established limits. When needed, wear NIOSH approved mask.
- Environmental exposure controls : Avoid release to the environment.
- Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Viscous liquid
- Color : Off white
- Odor : Slightly ammonia-like
- Odor threshold : No data available
- pH : 8.2 - 8.8
- Melting point : Not applicable
- Freezing point : < -42.8 °C

# AmerSeal Premium Heavy Duty Tire Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point	: > 127 °C
Flash point	: No data available, None detected
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: 1.08
Relative vapor density at 20 °C	: No data available
Solubility	: Emulsifies in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

This product is stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Fumes. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

AmerSeal Premium Heavy Duty Tire Sealant	
Acute Toxicity Estimate (ATE) US (oral)	1066.098 mg/kg body weight
Ethylene glycol (107-21-1)	
LD50 oral rat	4000 mg/kg
ATE US (oral)	500.000 mg/kg body weight
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg

Skin corrosion/irritation	: Not classified pH: 8.2 - 8.8
Serious eye damage/irritation	: Not classified pH: 8.2 - 8.8
Respiratory or skin sensitization	: Not classified

# AmerSeal Premium Heavy Duty Tire Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans (respirable dust form only)

<b>Attapulgite (12174-11-7)</b>	
IARC group	2B - Possibly carcinogenic to humans (respirable dust form only)

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Harmful if swallowed.

Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>Ethylene glycol (107-21-1)</b>	
LC50 fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	6500 - 13000 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

### 12.2. Persistence and degradability

<b>AmerSeal Premium Heavy Duty Tire Sealant</b>	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

<b>AmerSeal Premium Heavy Duty Tire Sealant</b>	
Bioaccumulative potential	Not established.

<b>Ethylene glycol (107-21-1)</b>	
Log Pow	-1.93

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local, state and federal regulations.

Ecology - waste materials : Avoid release to the environment.

# AmerSeal Premium Heavy Duty Tire Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

#### Additional information

##### ADR

No additional information available

##### Transport by sea

No additional information available

##### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

AmerSeal Premium Heavy Duty Tire Sealant	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Ethylene glycol (107-21-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 % reporting deminimis

#### 15.2. International regulations

##### CANADA

Ethylene glycol (107-21-1)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Titanium dioxide (13463-67-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

##### EU-Regulations

Ethylene glycol (107-21-1)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Titanium dioxide (13463-67-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

#### National regulations

Ethylene glycol (107-21-1)	
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Canadian IDL (Ingredient Disclosure List)	

# AmerSeal Premium Heavy Duty Tire Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Titanium dioxide (13463-67-7)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### Attapulgite (12174-11-7)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Pollutant Release and Transfer Register Law (PRTR Law)  
Listed on INSQ (Mexican national Inventory of Chemical Substances)

### 15.3. US State regulations

No additional information available

## SECTION 16: Other information

Other information : None.

Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
H302	Harmful if swallowed

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*