

COMPANY IDENTITY: Packaging Service Co., Inc.
 PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
 SDS NUMBER: DNAL01

SDS DATE: 02/14/2013
 REPLACES: 01/05/2010

SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this SDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
 COMPANY IDENTITY: Packaging Service Co., Inc.
 COMPANY ADDRESS: 1904 Mykawa Road / P O Box 875
 COMPANY CITY: Pearland, TX 77581
 COMPANY PHONE: 1-281-485-1458
 EMERGENCY PHONES: CHEMTREC: 1-800-424-9300 (USA)
 CANUTEC: 1-613-996-6666 (CANADA)

SECTION 2. HAZARDS IDENTIFICATION

DANGER!!



EXPOSURE PREVENTION: PREVENT DISPERSION OF MISTS OR DUST!
 AVOID EXPOSURE OF ADOLESCENTS, CHILDREN!

HAZARD STATEMENTS:

H100s = General, H200s = Physical, H300s = Health, H400s = Environmental

H225 Highly flammable liquid and vapor.
 H301 Toxic if swallowed.
 H311 Toxic in contact with skin.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H331 Toxic if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H370 Causes damage to organs.

PRECAUTIONARY STATEMENTS:

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal

P210 Keep away from heat/sparks/open flames/hot surfaces - No smoking.
 P262 Do not get in eyes, on skin, or on clothing.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do - Continue rinsing.
 P309+311 If exposed or you feel unwell: Call a POISON CENTER or doctor/physician.
 P403 Store in a well-ventilated place.
 P404 Store in a closed container.
 P502 Do not empty into drains.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT %
Methanol	67-56-1	200-659-6	65-75
Ethanol	64-17-5	200-578-6	20-30
Isopropanol	67-63-0	200-661-7	0- 5
Methyl Isobutyl Ketone	108-10-1	203-550-1	0- 1

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
SDS NUMBER: DNAL01

SDS DATE: 02/14/2013
REPLACES: 01/05/2010

Trace components: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

SECTION 4. FIRST AID MEASURES

GENERAL ADVICE:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists, refer to Section 8 for specific personal protective equipment.

EYE CONTACT:

If this product enters the eyes, open eyes while under gently running water. Use sufficient force to open eyelids. "Roll" eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.

SKIN CONTACT:

If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, medical attention may be necessary. Wash contaminated clothing before reuse, discard contaminated shoes.

INHALATION:

After high vapor exposure, remove to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

SWALLOWING:

Do not induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY. If person is fully conscious give 1 cup or 8 ounces of water. If medical advice is delayed and if an adult has swallowed several ounces of chemical, then give 3-4 ounces (1/3-1/2 cup) (90-120 ml) of hard liquor such as 80 proof whiskey. For children, give proportionally less liquor at a dose of 0.3 ounce (1 1/2 tsp) (8 ml) liquor for each 10 pounds of body weight, or 2 ml per kg body weight (for example: 1.2 ounce (2 1/3 tablespoon) for a 40 pound child or 36 ml for an 18 kg child).

NOTES TO PHYSICIAN:

In cases where several ounces (60 - 100 ml) have been ingested, consider the use of ethanol and hemodialysis in the treatment. Consult standard literature for details of treatment. If ethanol is used, a therapeutically effective blood concentration in the range of 100 - 150 mg/dl may be achieved by a rapid loading dose followed by a continuous intravenous infusion. Consult standard literature for details of treatment. 4-Methyl pyrazole (Antizol TM) is an effective blocker of alcohol dehydrogenase and should be used in the treatment of ethylene glycol, di- or triethylene glycol, ethylene glycol butyl ether, or methanol intoxication if available. Fomepizol protocol (Brent, J. et al, New England Journal of Medicine, Feb 8, 2001, 344:6, p. 424-9): loading dose 15 mg/kg intravenously, follow by bolus dose of 10 mg/kg every 12 hours; after 48 hours, increase bolus dose to 15 mg/kg every 12 hours. Continue fomepizol until serum methanol, EG, DEG, or TEG are undetectable. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late stage cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed.

COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
SDS NUMBER: DNAL01

SDS DATE: 02/14/2013
REPLACES: 01/05/2010

SECTION 4. FIRST AID MEASURES (CONTINUED)

NOTES TO PHYSICIAN:

Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Foliates may be administered to enhance the metabolism of formaldehyde. Acidosis must be treated by means of intravenous sodium bicarbonate. Maintain adequate ventilation and oxygenation of the patient. In severe poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably an ophthalmologist. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighted against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5. FIRE FIGHTING MEASURES

FIRE & EXPLOSION PREVENTIVE MEASURES

NO open flames, NO sparks, & NO smoking. NO contact with oxidants.
Above flash point, use a closed system, ventilation,
explosion-proof electrical equipment, lighting.
Do NOT use compressed air for filling, discharging, or handling.

EXTINGUISHING MEDIA

Use dry powder, AFFF, alcohol-resistant foam, water in large amounts,
carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters
& cool closed containers. Use fog nozzles if water is used.
Do not enter confined fire-space without full bunker gear.
(Helmet with face shield, bunker coats, gloves & rubber boots).
Use NIOSH approved positive-pressure self-contained breathing apparatus.

UNUSUAL EXPLOSION AND FIRE PROCEDURES

HIGHLY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE
Isolate from oxidizers, heat, sparks, electric equipment & open flame.
Closed containers may explode if exposed to extreme heat.
Applying to hot surfaces requires special precautions.
Empty container very hazardous! Continue all label precautions!

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE AND ENVIRONMENTAL PRECAUTIONS:

Uncontrolled releases should be responded to by trained personnel using pre-planned
procedures. Proper protective equipment should be used. In case of a spill, clear the
affected area, protect people, and respond with trained personnel.

PERSONAL PROTECTIVE EQUIPMENT

The proper personal protective equipment for incidental releases (such as: 1 Liter of the
product released in a well-ventilated area), use impermeable gloves (triple-gloves (rubber
gloves and nitrile gloves, over latex gloves), goggles, face shield, and appropriate body
protection. In the event of a large release, use impermeable gloves, specific for the
material handled, chemically resistant suit and boots, and hard hat. Self-Contained
Breathing Apparatus or respirator may be required where engineering controls are not
adequate or conditions for potential exposure exist. When respirators are required, select
NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance
with latest OSHA and/or ANSI recommendations.

ENVIRONMENTAL PRECAUTIONS:

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily
available material to prevent spreading of the material. Close or cap valves and/or
block or plug hole in leaking container and transfer to another container. Keep from
entering storm sewers and ditches which lead to waterways, and if necessary, call the
local fire or police department for immediate emergency assistance.

COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
SDS NUMBER: DNAL01

SDS DATE: 02/14/2013
REPLACES: 01/05/2010

SECTION 6. ACCIDENTAL RELEASE MEASURES (CONTINUED)

CONTAINMENT AND CLEAN-UP MEASURES:

Absorb spilled liquid with polypads or other suitable absorbent materials. If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 - Disposal Considerations).

SECTION 7. HANDLING AND STORAGE

HANDLING

Isolate from oxidizers, heat, sparks, electric equipment & open flame.
Use only with adequate ventilation. Avoid breathing of vapor or spray mist.
Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.
Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

STORAGE

Keep in fireproof surroundings. Keep separated from strong oxidants, food & feedstuffs.
Keep cool. Do not store above 49 C/120 F.
Keep container tightly closed & upright when not in use to prevent leakage.

NONBULK: CONTAINERS:

Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers or in a diked area, as appropriate. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity). Post warning and "NO SMOKING" signs in storage and use areas, as appropriate. Empty containers should be handled with care. Never store food, feed, or drinking water in containers which held this product.

BULK CONTAINERS:

All tanks and pipelines which contain this material must be labeled. Perform routine maintenance on tanks or pipelines which contain this product. Report all leaks immediately to the proper personnel.

TANK CAR SHIPMENTS:

Tank cars carrying this product should be loaded and unloaded in strict accordance with tank-car manufacturer's recommendation and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section 8, Engineering Controls and Personal Protective Equipment.). All loading and unloading equipment must be inspected, prior to each use. Loading and unloading operations must be attended, at all times. Tank cars must be level, brakes must be set or wheels must be locked or blocked prior to loading or unloading. Tank car (for loading) or storage tanks (for unloading) must be verified to be correct for receiving this product and be properly prepared, prior to starting the transfer operations. Hoses must be verified to be in the correct positions, before starting transfer operations. A sample (if required) must be taken and verified (if required) prior to starting transfer operations. All lines must be blown-down and purged before disconnecting them from the tank car or vessel.

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:

Follow practices indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Always use this product in areas where adequate ventilation is provided. Collect all rinsates and dispose of according to applicable Federal, State, Provincial, or local procedures.

COMPANY IDENTITY: Packaging Service Co., Inc.
 PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
 SDS NUMBER: DNAL01

SDS DATE: 02/14/2013
 REPLACES: 01/05/2010

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
Methanol	67-56-1	200-659-6	200 ppm S	200 ppm S
Ethanol	64-17-5	200-578-6	1000 ppm	1000 ppm A4
Isopropanol	67-63-0	200-661-7	400 ppm	200 ppm A4
Methyl Isobutyl Ketone	108-10-1	203-550-1	100 ppm	20 ppm A3

MATERIAL	CAS#	EINECS#	CEILING	STEL (OSHA/ACGIH)	HAP
Methanol	67-56-1	200-659-6	None Known	250 ppm	Yes
Isopropanol	67-63-0	200-661-7	None Known	400 ppm	No
Methyl Isobutyl Ketone	108-10-1	203-550-1	None Known	75 ppm	Yes

Each component showing 'Yes' under "HAP" is an EPA Hazardous Air Pollutant.

RESPIRATORY EXPOSURE CONTROLS

Seek professional advice prior to respirator selection and use. Maintain airborne contaminant concentrations below exposure limits given above. If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134, European Standard EN 149, or applicable State regulations. If adequate ventilation is not available or there is potential for airborne exposure above the exposure limits, a respirator may be worn up to the respirator exposure limitations, check with respirator equipment manufacturer's recommendations/limitations. For a higher level of protection, use positive pressure supplied air respiration protection or Self-Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

EMERGENCY OR PLANNED ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS

Positive pressure, full-face piece Self-Contained Breathing Apparatus; or positive pressure, full-face piece Self-Contained Breathing Apparatus with an auxilliary positive pressure Self-Contained Breathing Apparatus.

VENTILATION

LOCAL EXHAUST: Necessary MECHANICAL (GENERAL): Necessary
 SPECIAL: None OTHER: None
 Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

EYE PROTECTION:

Splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

HAND PROTECTION:

Wear appropriate impervious gloves for routine industrial use. Use impervious gloves for spill response, as stated in Section 6 of this SDS (Accidental Release Measures).
 NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

BODY PROTECTION:

Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from impervious materials are generally acceptable, depending on the task.

WORK & HYGIENIC PRACTICES:

Provide readily accessible eye wash stations & safety showers. Wash at end of each shift & before eating, smoking or using the toilet. Remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

COMPANY IDENTITY: Packaging Service Co., Inc.
 PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
 SDS NUMBER: DNAL01

SDS DATE: 02/14/2013
 REPLACES: 01/05/2010

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Liquid, Water-White
ODOR:	Alcohol
ODOR THRESHOLD:	Not Available
pH (Neutrality):	Not Applicable
MELTING POINT/FREEZING POINT:	Not Available
BOILING RANGE (IBP,50%,Dry Point):	63 66 83 C / 147 152 182 F
FLASH POINT (TEST METHOD):	8 C / 48 F (TCC)
EVAPORATION RATE (n-BUTYL ACETATE=1):	1.7
FLAMMABILITY CLASSIFICATION:	Class I B
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	6.4
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg)@20 C	86.1
VAPOR DENSITY (air=1):	1.2
GRAVITY @ 68/68 F / 20/20 C:	
SPECIFIC GRAVITY (Water=1):	0.792
POUNDS/GALLON:	6.597
WATER SOLUBILITY:	Complete
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	398 C / 750 F
DECOMPOSITION TEMPERATURE:	Not Available
VOCs (>0.044 Lbs/Sq In) :	100.0 Vol% / 792.0 g/L / 6.5 Lbs/Gal
TOTAL VOC'S (TVOC)*:	100.0 Vol% / 792.0 g/L / 6.5 Lbs/Gal
NONEXEMPT VOC'S (CVOC)*:	100.0 Vol% / 792.0 g/L / 6.5 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	73.0 Wt% / 578.2 g/L / 4.8 Lbs/Gal
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	86.1

* Using California Air Resources Board (CARB) Rule 310.

SECTION 10. STABILITY & REACTIVITY

STABILITY

Stable under normal conditions.

CONDITIONS TO AVOID

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

MATERIALS TO AVOID

The substance can presumably form explosive peroxides, under the influence of light and air, Check for peroxide prior to distillation, eliminate if found. Reacts violently with strong oxidants, strong reducing agents, causing fire & explosion hazard. Attacks

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION

Will not occur.

COMPANY IDENTITY: Packaging Service Co., Inc.
 PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
 SDS NUMBER: DNAL01

SDS DATE: 02/14/2013
 REPLACES: 01/05/2010

SECTION 11. TOXICOLOGICAL INFORMATION

ACUTE HAZARDS

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.
 Primary irritation to eyes, redness, tearing, blurred vision.
 Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful. Breathing vapor can cause irritation. Acute overexposure can cause harm to kidneys, blood, nerves, liver, lungs. Repeated exposure over TLV can cause blindness.

SWALLOWING:

Can be fatal or cause blindness if swallowed. Cannot be made non-poisonous. POISON ! Can cause irreversible nervous system damage & death. Harmful or fatal if swallowed. Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

CONDITIONS AGGRAVATED

Chronic overexposure can cause harm to kidneys, blood, nerves, liver, lungs. Persons with severe skin, liver or kidney problems should avoid use.

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

Potential Cancer Hazard based on tests with laboratory animals using Methyl Isobutyl Ketone. Overexposure may create cancer risk. Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus. Depending on degree of exposure, periodic medical examination is indicated.

IRRITANCY OF PRODUCT: This product is irritating to contaminated tissue.

SENSITIZATION TO THE PRODUCT: No component of this product is known to be a sensitizer.

MUTAGENICITY: This product is not reported to produce mutagenic effects in humans.

EMBRYOTOXICITY: This product is not reported to produce embryotoxic effects in humans.

TERATOGENICITY: This product is not reported to produce teratogenic effects in humans.

REPRODUCTIVE TOXICITY: This product is not reported to cause reproductive effects in humans.

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical which causes damage to a developing embryo (such as: within the eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

MAMMALIAN TOXICITY INFORMATION

MATERIAL	CAS#	EINECS#	LOWEST KNOWN LETHAL DOSE DATA
Methanol	67-56-1	200-659-6	LOWEST KNOWN LD50 (ORAL) 1000.0 mg/kg(Man)
Isopropanol	67-63-0	200-661-7	LOWEST KNOWN LC50 (VAPORS) 1600 ppm (Rats)
Isopropanol	67-63-0	200-661-7	LOWEST KNOWN LD50 (SKIN) 16400.0 mg/kg (Rabbits)

COMPANY IDENTITY: Packaging Service Co., Inc.
 PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
 SDS NUMBER: DNAL01

SDS DATE: 02/14/2013
 REPLACES: 01/05/2010

SECTION 12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

EFFECT OF MATERIAL ON AQUATIC LIFE:

The most sensitive known aquatic group to any component of this product is: Chub 250 ppm or mg/L (24 hour exposure). Keep out of sewers and natural water supplies.

MOBILITY IN SOIL

This material is a mobile liquid.

DEGRADABILITY

This product is completely biodegradable.

ACCUMULATION

This product does not accumulate or biomagnify in the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste management options. Recycle / dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If in doubt, contact appropriate agencies.

SECTION 14. TRANSPORT INFORMATION

IF > 6868 LB / 3121 KG OF THIS PRODUCT IS IN 1 CONTAINER, IT EXCEEDS THE RQ OF METHANOL. "RQ" MUST BE PUT BEFORE THE DOT SHIPPING NAME.

DOT/TDG SHIP NAME: NA1987, Denatured Alcohol
 3, PG-II
 DRUM LABEL: (FLAMMABLE LIQUID)
 IATA / ICAO: UN1986, Alcohols, Toxic, n.o.s.
 (contains: Methanol, Ethanol, Methyl Isobutyl Ketone),
 3, (6.1), PG-II
 IMO / IMDG: UN1986, Alcohols, Toxic, n.o.s.
 (contains: Methanol, Ethanol, Methyl Isobutyl Ketone),
 3, (6.1), PG-II
 EMERGENCY RESPONSE GUIDEBOOK NUMBER: 127

SECTION 15. REGULATORY INFORMATION



EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS#	EINECS#	WT%	(REG. SECTION)	RQ(LBS)
*Methanol	67-56-1	200-659-6	65-75	(311,312,313,RCRA)	5000
*Methyl Isobutyl Ketone	108-10-1	203-550-1	0- 5	(311,312,313,RCRA)	5000

COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN DENATURED ALCOHOL
SDS NUMBER: DNAL01

SDS DATE: 02/14/2013
REPLACES: 01/05/2010

SECTION 15. REGULATORY INFORMATION (CONTINUED)

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State & local regulations may be more restrictive than federal regulations.

STATE REGULATIONS:

THIS PRODUCT MEETS REQUIREMENTS OF SOUTHERN CALIFORNIA AQMD RULE 443.1 & SIMILAR REGULATIONS

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):

This product contains the following chemical known to the State of California to cause cancer: Methyl Isobutyl Ketone

This product contains the following chemical known to the State of California to cause reproductive toxicity: Methanol

INTERNATIONAL REGULATIONS

The components of this product are listed on the chemical inventories of the following countries:

Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS)G
Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC),
Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

B2: Flammable Liquid.

D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

SECTION 16. OTHER INFORMATION

HAZARD RATINGS:

HEALTH (NFPA): 1, HEALTH (HMIS): 3, FLAMMABILITY: 3, PHYSICAL HAZARD: 0
(Personal Protection Rating to be supplied by user based on use conditions.)

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

EMPLOYEE TRAINING

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

Unless updated, the Safety Data Sheet is valid until 02/14/2016.