



Safety Data Sheet CLEAR GUARD

Supersedes Date MAY 2019

Issuing Date JUNE 2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name CLEAR GUARD

Recommended use Recommended use Aerosol based clear rubberised coating. Moisture displacer & corrosion inhibitor

Manufacturer, importer, supplier

NCH AUSTRALIA PTY LTD, DIV. OF NCH CORPORATION
N2, 391, PARK ROAD, REGENTS PARK, NSW 2143

Telephone inquiry

+61-2-96690260

Emergency Telephone Number

+61-2-96690237 / 0401718972

Fax number

+61-2-96931562

Product Code 5687

Chemical nature Polymer suspension

Distributor

NCH AUSTRALIA PTY LTD
N2, 391, PARK ROAD, REGENTS PARK, NSW 2143

Telephone Number

+61-2-96690260

Emergency Telephone Number

+61-2-96690237 / 0401718972

Fax number

+61-2-96931562

2. HAZARD IDENTIFICATION

Colour Colourless - Light Yellow
Mixture or Pure Substance: Mixture

Physical State Liquid

Odour Petroleum distillates

GHS

Classification

Physical Hazards

Flammable aerosols
Gases under pressure

Category 1
Compressed gases

Health Hazard

Aspiration Toxicity
Skin Corrosion/Irritation
Reproductive Toxicity
Specific target organ systemic toxicity
(single exposure)
Specific target organ systemic toxicity
(repeated exposure)
Chronic Aquatic Toxicity

Category 1
Category 2
Category 2
Category 3

Category 2

Category 2

Other Hazards

Labelling

Signal Word

Danger



Hazard

Statements

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Precautionary

Statements

P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P260 - Do not breathe vapour or mist.
P261 - Avoid breathing dust/fume gas/mist/vapours/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302+ P352 - IF ON SKIN: Wash with plenty of soap and water
P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a physician.
P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P331 - Do NOT induce vomiting
P362 - Take off contaminated clothing and wash before reuse
P308 + P313 - IF exposed or concerned, get medical attention
P337 + P313 - If eye irritation persists, get medical attention.
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C
P405 - Store locked up
P501 - Dispose of contents and container in accordance with applicable local regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	ENCS	Weight %
Hexanes	110-54-3	Present	10-30
Xylenes (o-, m-, p- isomers)	1330-20-7	Present	20-30
Styrene-butadiene polymer	9003-55-8	Present	10-20
INGREDIENTS DETERMINED NOT TO BE HAZARDOUS			UP TO 100 %

4. FIRST AID MEASURES

General advice	Avoid breathing vapours, mist, or gas. Avoid contact with skin, eyes and clothing.
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.
Skin Contact	Wipe up with absorbent material (e.g. cloth, fleece). Wash off with soap and plenty of water. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.
Inhalation	Move to fresh air. In case of shortness of breath, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.
Ingestion	Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if irritation develops and persists.
Notes to physician	Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed & enter airways.

5. FIRE-FIGHTING MEASURES

Flash Point	-93 °C	Method	Seta closed cup
Auto ignition Temperature	No information available.		
Flammability Limits in Air %	Solvent mixture. Upper 9.5	Lower	0.9
Suitable Extinguishing Media	Foam. Alcohol-resistant foam. Dry chemical. Water spray. Carbon dioxide (CO ₂), Foam, Dry Chemical or Water fog. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Specific hazards arising from the chemical	Solvent vapours are heavier than air and may spread along floors. Vapours may ignite and explode. Flame extension: >30 inches / >75 cm and Burn back: 6 inch / 15 cm.		
Protective Equipment and Precautions for Firefighters	Wear self-contained breathing apparatus pressure-demand, Safe Work, Australia (approved or equivalent) and full protective gear.		

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Wear protective gloves/clothing. Remove all sources of ignition. Ensure adequate ventilation. Prevent further leakage or spillage if safe to do so.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material.
Neutralizing Agent	Not applicable.

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition Avoid breathing vapours, mist or gas			
Storage	Avoid contact with skin, eyes and clothing Keep away from heat and sources of ignition Keep out of the reach of children			
Storage Temperature	Minimum	2 °C	Maximum	49 °C
Storage Conditions	Indoor	X	Outdoor	Heated Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ES-TWA	ISHL	ACGIH TLV
Hexanes	TWA: 20 ppm TWA: 72 mg/m ³	ACL: 40 ppm	TWA: 50 ppm Skin
Xylenes (o-, m-, p- isomers)	STEL: 150 ppm STEL: 655 mg/m ³ TWA: 80 ppm TWA: 350 mg/m ³	ACL: 50 ppm	TWA: 100 ppm STEL: 150 ppm
Styrene-butadiene polymer		no data available	3 mg/m ³ PNOS
INGREDIENTS DETERMINED NOT TO BE HAZARDOUS		no data available	No data available

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal Protective Equipment

Respiratory Protection

In case of inadequate ventilation wear respiratory protection When workers are facing concentrations above the exposure limit, they must use appropriate certified respirators

Eye/Face Protection

Safety glasses with side-shields.

Hand Protection

Protective gloves

Skin Protection

Wear suitable protective clothing, Impervious gloves.

General Hygiene Considerations

Wear protective clothing when handling. Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Transparent -- Hazy
Colour	Colourless - Light Yellow
Physical State	Liquid
Odour	Petroleum distillates
Odour Threshold	No data available
pH	Not applicable
Melting Point/Range	No data available
Freezing Point	No information available
Boiling Point/Range	No information available
Flash Point	-93 °C
Method	Seta closed cup
Evaporation Rate	> 1.0
Vapour Pressure	No information available
Solubility	Negligible
Vapour Density	> 1 (Air = 1)
Specific Gravity	0.77(Water =1)
Auto ignition Temperature	No information available.
Viscosity	Semi-viscous
Molecular Weight	No data available
Percent Volatile (Volume)	0

VOC Content (%) 83
VOC Content (g/L) 639

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	None known
Incompatible Products	Strong oxidizing agents
Hazardous Decomposition Products	Carbon oxides
Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information

Principle Route of Exposure Eye contact, Skin contact, Inhalation.

The following values are calculated based on chapter 3.1 of the GHS document (Rev. 3, 2009):

Oral LD50	3,500.00	mg/kg
Dermal LD50	1,790.00	mg/kg
Inhalation LC50		
Gas	4,500.00	mg/L
Mist	2.00	mg/L
Vapour	25.00	mg/L

Primary Routes of Entry Inhalation, Skin Absorption.

Main Symptoms

Acute Effects

Eyes	Causes eye irritation.
Skin	Causes skin irritation. May be absorbed through the skin in harmful amounts.
Inhalation	Causes respiratory tract irritation. Causes headache, drowsiness or other effects to the central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed & enter airways.

Chronic Effects

Repeated and prolonged exposure to solvents may cause brain and nervous system damage, May cause irregular heartbeats, especially under conditions of stress, Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood, Suspect reproductive hazard - contains material which may injure unborn child, May cause polymer fume fever, a temporary flu-like illness accompanied by chills, fever, and a cough. This can last up to 24 hours in duration.

Target Organ Effects

Eyes, Skin, Respiratory system, Central nervous system, Peripheral Nervous System (PNS), Ears, Heart, Liver, Kidney, Blood.

Aggravated Medical Conditions

Skin disorders, Respiratory disorders, Neurological disorders, Blood disorders, Heart disease, Liver disorders, Kidney disorders.

Component Information

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Hexanes	no data available	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h	no data available	no data available
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h	no data available	no data available
Styrene-butadiene polymer	no data available	no data available	no data available	no data available	no data available
INGREDIENTS DETERMINED NOT TO BE HAZARDOUS	no data available	no data available	no data available	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Hexanes	no data available	no data available	no data available	no data available	eyes,CNS,respiratory system,skin,PNS
Xylenes (o-, m-, p- isomers)	no data available	no data available	no data available	no data available	heart, lung, CNS, PNS, respiratory system, ears, liver, kidney
Styrene-butadiene polymer	no data available	no data available	no data available	no data available	no data available
INGREDIENTS DETERMINED NOT TO BE HAZARDOUS	no data available	no data available	no data available	no data available	no data available

Carcinogenicity There are no known carcinogenic chemicals in this product.

Component	ES	ACGIH	IARC	NTP	Other
Hexanes	not applicable	not applicable	not applicable	not applicable	not applicable
Xylenes (o-, m-, p- isomers)	not applicable	not applicable	not applicable	not applicable	not applicable
Styrene-butadiene polymer	not applicable	not applicable	not applicable	not applicable	not applicable
INGREDIENTS DETERMINED NOT TO BE HAZARDOUS	not applicable	not applicable	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION**Product Information** No data available**Component Information**

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Hexanes	no data available	LC50 2.1 - 2.98 mg/L Pimephales promelas 96 h	no data available	no data available	N/A
Xylenes (o-, m-, p- isomers)	no data available	LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 = 13.4 mg/L Pimephales promelas 96 h LC50 = 19 mg/L Lepomis macrochirus 96 h LC50 = 780 mg/L Cyprinus carpio 96 h LC50 > 780 mg/L Cyprinus carpio 96 h	EC50 = 0.0084 mg/L 24 h	LC50= 0.6 mg/L 48 h EC50= 3.82 mg/L 48 h	2.77 - 3.15
Styrene-butadiene polymer	no data available	no data available	no data available	no data available	N/A
INGREDIENTS DETERMINED NOT TO BE HAZARDOUS	no data available	no data available	no data available	no data available	N/A

Eco toxicity effects

No information available

Persistence & Degradability

Persistence & Degradability

Bioaccumulation

No information available

Immobile in soil.

No information available

13. DISPOSAL CONSIDERATIONS**Product Disposal**

Dispose of in accordance with local regulations.

Container Disposal

Warning! Container under pressure. Do not puncture. Empty remaining contents.

14. TRANSPORT INFORMATION**ADG 7**

UN-No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Hazchem Code	2YE
Shipping Description	UN1950, Aerosols,2.1 LIMITED QTY

15. REGULATORY INFORMATION

Australia	
POISON SCHEDULE	Schedule 5

16. OTHER INFORMATION

Prepared By	Arvind Rane
Super cedes Date	MAY 2019
Issuing Date	JUNE 2020
Reason for Revision	GHS-SDS Format
Glossary	No information available.
List of References.	No information available.

NCH AUSTRALIA, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.