MATERIAL SAFETY DATA SHEET

Page 1

24-hour Emergency Phone: (800) 255-3924

PRODUCT CODE: 7157

PRODUCT NAME: SNO-GO (A/11) HMIS CODES: H C F R P

PRODUCT CODE: 7157 2 3 0 B

WHMIS CLASS: A & B, 5 & D, 2, B

MANUFACTURER'S NAME: ATCO International ADDRESS : 1401 Barclay Circle Marietta, GA 30060

INFORMATION PHONE: (770) 424-7550 **DATE PRINTED**: 08/30/2011

PREPARED BY: Allen Buckalew, TECHNICAL SERVICES

REVISION DATE: 08/30/2011

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =======

REPORTABLE COMPONENTS WEIGHT CAS NUMBER PEL TLV PERCENT 110-54-3 500ppm NA 35-45% 63148-62-9 NA NA POLYDIMETHYLSILOXANE 2-12% 8032-32-4 300ppm NA 20-40% PETROLEUM ETHER NA 1000ppm 15-25% PROPANE 74-98-6 1000ppm 10-20% BUTANE 106-97-8 NA

======= SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ========

BOILING RANGE: ND **SPECIFIC GRAVITY (H20=1):** 0.65

VAPOR DENSITY:NDEVAPORATION RATE:NDDENSITY:5.4 lb/glMATERIAL V.O.C.:90%

SOLUBILITY IN WATER: NEGLIGIBLE. pH (Concentrate): NA APPEARANCE AND ODOR: CLEAR LIQUID. pH (Diluted): NA

ODOR: SOLVENT.

======== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =========

OSHA FLAMMABILITY CLASSIFICATION: EXTREMELY FLAMMABLE AEROSOL FLASH POINT: -7 F (Conc. Only) METHOD USED: TCC FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND UPPER: ND

EXTINGUISHING MEDIA: In case of fire, use water fog, dry chemical carbon dioxide, or "alcohol" foam. Water stream may be ineffective and may result in spreading the fire. Water spray (fog) is particularly effective.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to cool closed containers in order to prevent pressure build up which may result in containers rupturing. Use self contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. However, containers may burst if overheated in fire. Cool containers using water spray or water fog nozzles.

MATERIAL SAFETY DATA SHEET

Page 2

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 7157

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

PRIMARY ROUTES OF ENTRY: Inhalation \underline{X} Eye Contact \underline{X} Skin Contact \underline{X} Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of fumes or mist can result in irritation or burns to the upper respiratory tract and lungs, pulmonary edema can also occur.

EYE CONTACT: May cause stinging of eyes followed by irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORBTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: Harmful if swallowed. Can cause mouth, throat, and gastro-intestinal tract irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

CHRONIC EFFECTS OF OVEREXPOSURE: Chronic effects and medical conditions aggravated by overexposure to this product have not been established. Unnecessary exposure to this product or any chemical should be avoided.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid immediately.

EYE CONTACT: IN CASE OF CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician. Wash skin with soap and water.

SKIN CONTACT: Wash skin with warm soapy water to remove.

MATERIAL SAFETY DATA SHEET

Page 3

24-hour Emergency Phone: (800) 255-3924

PRODUCT CODE: 7157

INGESTION: IF SWALLOWED: Call a physician immediately. Do NOT induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person.

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat, sparks, or flame. Store only in well-ventilated areas.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Sufficient, in volume and pattern, to keep workroom concentration

below current applicable OSHA safety and health requirements.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required. WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

PROTECTIVE GLOVES: Impervious gloves recommended.

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard___

Acute Health Hazard X Chronic Health Hazard Pressure Hazard X

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.